



Figure similar

Article No. : 1FK7011-5AK74-1JH3

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

### Engineering data

Rated speed (100 K)	6,000 rpm
Number of poles	8
Rated torque (100 K)	0.1 Nm
Rated current	0.8 A
Static torque (60 K)	0.15 Nm
Static torque (100 K)	0.18 Nm
Stall current (60 K)	1.20 A
Stall current (100 K)	1.50 A
Moment of inertia	0.083 kgcm <sup>2</sup>
	62.0 %

### Physical constants

Torque constant	0.12 Nm/A
Voltage constant at 20° C	8.0 V/1000*min <sup>-1</sup>
Winding resistance at 20° C	3.00 Ω
	4.2 mH
Electrical time constant	1.40 ms
Mechanical time constant	4.00 ms
Thermal time constant	14 min
Shaft torsional stiffness	1,400 Nm/rad
Net weight of the motor	1.0 kg

### Mechanical data

Motor type	Permanent-magnet synchronous motor
Motor type	Compact
	20
Cooling	Natural cooling
	0.000 mm
Concentricity tolerance	0.00 mm
Axial runout tolerance	0.00 mm
	Grade A
Connector size	0.5
Degree of protection	IP54
	IM B5 (IM V1, IM V3)
Temperature monitoring	Pt1000 temperature sensor
	Connectors for signals and power rotatable
	Standard (Anthracite RAL 7016)
Holding brake	with holding brake
Shaft end	Plain shaft
Encoder system	Encoder AM16S/R: absolute encoder 16 S/R, 4096 revolutions multi-turn, with EnDat interface

### Optimum operating point

Optimum speed	5,000 rpm
Optimum power	0.1 kW

### Limiting data

Max. permissible speed (mech.)	8,000 rpm
Max. permissible speed (inverter)	8,000 rpm
Maximum torque	0.5 Nm
Maximum current	4.2 A

### Holding brake

Holding brake version	Permanent-magnet brake
Holding torque	0.4 Nm
Power supply voltage	DC 24 V ± 10 %
Coil current	0.3 A
Opening time	30 ms
Closing time	20 ms
Highest braking work	2 J

### Recommended Motor Module

Rated inverter current	3 A
Maximum inverter current	6 A
Maximum torque	0.50 Nm