




---

 PRODUCT-DETAILS

## ST201M-K32

# Miniature Circuit Breaker - ST200M - 1P - 32 A - K




---

### General Information

<b>Extended Product Type:</b>	ST201M-K32
<b>Product ID:</b>	2CDS271334R0537
<b>EAN:</b>	4016779018388
<b>Catalog Description:</b>	Miniature Circuit Breaker - ST200M - 1P - 32 A - K
<b>Long Description:</b>	ST201M-K32 Miniature Circuit Breaker ST201M-K32 Miniature Circuit Breaker K-Char., 10kA, 32A, 1P
<b>Display Name:</b>	ST201M-K32

---

### ABB EcoSolutions

**Recyclability Rate of the Product acc. to EN45555:** Design for Closing Resource Loops - Standard EN45555 - 80.7 %

**ABB Site Meeting Group Waste To Landfill Target:** No non-hazardous waste is sent to a landfill

**Extended Product Lifetime:** Product Durability

**End Of Life Disassembling Instructions:** 9AKK108468A3132

Environmental Product Declaration - EPD: 9AKK108467A7832

## Technical

Rated Ultimate Short-Circuit Breaking Capacity ( $I_{cu}$ ):	(230 V AC) 15 kA (230 V) 15 kA
Rated Service Short-Circuit Breaking Capacity ( $I_{cs}$ ):	(230 V AC) 11.2 kA
Energy Limiting Class:	3
Number of Protected Poles:	1
Number of Poles:	1P
Accessories Available:	Yes
Connecting Capacity:	Flexible 25 ... 25 mm <sup>2</sup> Rigid 35 ... 35 mm <sup>2</sup>
Terminal Type:	Double Clamp

## Electrical

Tripping Characteristic:	K
Rated Operational Voltage:	acc. to IEC 60947-2 230 V
Rated Insulation Voltage ( $U_i$ ):	acc. to IEC/EN 60664-1 440 V
Rated Impulse Withstand Voltage ( $U_{imp}$ ):	4 kV
Input Voltage Type:	AC/DC
Rated Current ( $I_n$ ):	32 A
Rated Conditional Short-Circuit Current ( $I_{nc}$ ):	(230 V) 15 kA (400 V) 15 kA
Rated Frequency (f):	50 / 60 Hz
Overvoltage Category:	III

## Technical UL/CSA

Interrupting Rating acc. to UL1077:	(277 V AC) 10 kA (60 V DC) 10 kA
-------------------------------------	-------------------------------------

## Material Compliance

RoHS Declaration:	9AKK108472A0372
RoHS Information:	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Date:	20260312
REACH Declaration:	9AKK107492A1906
REACH Information:	False - does not contain substances > 0.1 mass percentage
REACH Date:	20260312
Conflict Minerals Reporting Template (CMRT):	9AKK108468A3363

<b>Toxic Substances Control Act - TSCA:</b>	9AKK108468A8104
<b>SCIP:</b>	171856b6-03a8-4c04-9bae-ec01c5a7d7da Germany
<b>WEEE Category:</b>	5. Small Equipment (No External Dimension More Than 50 cm)
<b>WEEE B2C / B2B:</b>	Business To Business

---

## Environmental

<b>Ambient Air Temperature:</b>	Operation -25 ... +55 °C
<b>Degree of Protection:</b>	IP20
<b>Pollution Degree:</b>	3

---

## Dimensions

<b>Width in Number of Modular Spacings:</b>	1
<b>Product Net Width:</b>	17.5 mm
<b>Product Net Height:</b>	88 mm
<b>Product Net Depth / Length:</b>	69 mm
<b>Product Net Weight:</b>	0.12 kg
<b>Built-In Depth (t<sub>2</sub>):</b>	69 mm

---

## Ordering

<b>Package Level 1 Units:</b>	carton 10 piece
<b>Package Level 1 Gross Weight:</b>	1.24 kg

---

## Certificates and Declarations

<b>Declaration of Conformity - CE:</b>	2CDK400679D2703
<b>Declaration of Conformity - UKCA:</b>	9AKK108467A5200

---

## Installation

<b>Instructions and Manuals:</b>	9AKK107046A3150
----------------------------------	-----------------

---

## Popular Downloads

<b>Data Sheet, Technical Information:</b>	9AKK107046A3150
---	-----------------

---

## External Classifications and Standards

<b>ETIM 9:</b>	EC000042 - Miniature circuit breaker (MCB)
----------------	--

<b>ETIM 10:</b>	EC000042 - Miniature circuit breaker (MCB)
<b>UNSPSC:</b>	39121603
<b>eClass:</b>	V11.0 : 27141901
<b>IDEA Granular Category Code (IGCC):</b>	4899 >> Miniature circuit breaker (MCB) screw-in model
<b>Standards:</b>	CSA 22.2 No. 235 IEC/EN 60947-2 UL 1077
<b>Certification Agency:</b>	CSA EN IEC UL

## Categories

Products > Low Voltage Products and Systems > Modular DIN Rail Products > Miniature Circuit Breakers MCBs > Miniature Circuit Breakers MCBs > ST200M



360°

ABB  
**Eco**  
Solutions™