



131G5672

FC-302P22KT5E20H1BXXDXSXXXXAXBXXXXDX

Frequency converter
 FC-302P22KT5E20H1BXXDXSXXXXAXBXXXXDX
 VLT® AutomationDrive FC-302
 (P22K) 22 KW / 30 HP, Three phase
 380 - 500 VAC, (E20) IP20 / Chassis
 (H1) RFI Class A1/B (C1)
 Brake chopper
 No Loc. Cont. Panel
 Not coated PCB, Loadsharing
 Latest release std. SW.
 Frame: B4
 No C1 option, No D option
 No A Option, No B Option

Other options according to Model code

Model code: FC-302P22KT5E20H1BXXDXSXXXXAXBXXXXDX

The VLT® AutomationDrive represents a single drive concept that controls the entire range of operations from ordinary to servo like applications on any machine or production line.

[View Efficiency Data](#)

PRODUCT DETAILS

Gross weight	21.66 kg	
Net weight	20.7 kg	
Volume	57.75 l	
EAN	5702427663558	
VLT® AUTOMATIONDRIVE FC 300 SERIES		
Product View (Switch)	GLBL	Global (Standard)
Product Group	FC-	VLT® AutomationDrive FC-
Series	302	302
Power Rating	P22K	(P22K) 22 KW / 30 HP
Phase	T	Three phase
Mains Voltage	5	380 - 500 VAC
Enclosure	E20	(E20) IP20 / Chassis
RFI Filter	H1	(H1) RFI Class A1/B (C1)
Brake - Safe Stop	B	Brake chopper
LCP	X	No Loc. Cont. Panel
Coating PCB	X	Not coated PCB
Mains Option	D	Loadsharing
Adaptation A	X	Standard Cable Entries
Adaptation B	X	No adaptation
Software Release	SXXX	Latest release std. SW.
Software Language Pack	X	Standard Language Pack
A Option	AX	No A Option
B Option	BX	No B Option
C0 Option MCO	CX	No C0 option

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Product Detail | FC-302P22KT5E20H1BXXDXXSXXXXAXBXCXXXXDX

PRODUCT DETAILS

C1 Option	X	No C1 option
C Option Software	XX	No software option
D Option	DX	No D option
Frame Size	B4	B4
Typecode Part 1		FC-302P22KT5E20H1BXX
Typecode Part 2		DXXSXXXXAXBXCXXXXDX
Product Catalog	GLBL	Global (Standard)
Power 160% (HO) [KW]		22
Power 110% (NO) [KW]		30
Height [mm]		516,0
Width w/ no C options [mm]		229,0
Depth [mm]		242,0
Depth with Option A/B [mm]		242,0
kVA		30.5
Power Loss NO [W]		739
Power Loss NO [W]		739
Power Loss HO [W]		547
Power Loss HO [W]		547
Continuous Current (NO) [A]		61
Intermittent Current (NO) [A]		67.1
Continuous Current (NO) [A]		52
Intermittent Current (NO) [A]		57.2
Continuous Current (HO) [A]		44
Intermittent Current (HO) [A]		70.4
Continuous Current (HO) [A]		40
Intermittent Current (HO) [A]		64
Calculated Gross Weight [kg]		21.66
Calculated Net Weight [kg]		20.7
ECCN EU		Y901
ECCN US		3A999.a
Plant from Orderline		B901
Vendor	ERR01	Cannot Determine Vendor
Recommended Factory	ERR01	Cannot Determine Vendor
Modelcode01		FC-302P22KT5E20H1BXX
Modelcode02		DXXSXXXXAXBXCXXXXDX

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Accessories

Image
coming
soon

130B3290 [🔗](#)**VLT® Safe option MCB 151, coated**

VLT® Safe option MCB 151, painted for HTL feedback, can be used up to PL d or SIL 2

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories



130B3280 [🔗](#)

VLT® Safe option MCB 150, coated

Safety modules enable machines to interact intelligently with operators to increase safety, reduce system costs, improve flexibility and increase productivity.

VLT® MCB 15x Safe options provide an intelligent, user-friendly solution to meet the IEC 61800-5-2 functional safety standard and helps to reduce cabling.

The new safety module is certified according to ISO 13849-1 PL d Category 3 and SIL 2 according to IEC 61508.



130B4172 [🔗](#)

Back plate IP20/Chassis, B4

Back plate IP20/Type 1, enclosure size B4



130B7533 [🔗](#)

Mounting Kit C Option, B/C/D/E/F(not B3)

MCF105 C Option, Mounting Kit A2 and A3



130B7635 [🔗](#)

VLT® Lift Controller MCO 361

VLT® Motion Control MCO 305 with special software for lift application



130B7145 [🔗](#)

VLT® SALT Controller MCO 360



130B9860 [🔗](#)

VLT® Safety Option MCB152, coated

Safety modules enable machines to interact intelligently with operators to increase safety, reduce system costs, improve flexibility and increase productivity.

VLT® Safety Option MCB152 provides an intelligent, user-friendly solution to meet the IEC 61800-5-2 functional safety standard and helps to reduce cabling. MCB152 enables activation of the Safe Torque Off (STO) irrespective of where a hazard occurs.

The new safety module is certified according to ISO 13849-1 PL d Category 3 and SIL 2 according to EN IEC 61508.

The combination of VLT® Safety Option MCB152, PROFINET fieldbus option MCA120, and the control card of the VLT® AutomationDrive constitutes a PROFIsafe device.

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories

**130B5765** [🔗](#)**Leakage Current Monitor Kit, B4****130B5646** [🔗](#)**VLT® EtherCAT MCA 124, coated**

MCA 124 Ethercat option painted The VLT® EtherCat MCA 124 option enables Connection to EtherCat-based networks via the EtherCat protocol.

The option allows an EtherCat connection with full Speed and a connection to the frequency converter with a time interval of 4 ms in both Directions. This enables the MCA124 to be used in Networks from low-power applications to Servo applications.

- EoE EtherNet over EtherCat support
- HTTP (Hypertext Transfer Protocol) for diagnosis via integrated web server
- SMTP (Single Mail Transfer Protocol) for email notification
- TCP / IP for easy access to frequency converters Configuration data via MCT 10

**130B5436** [🔗](#)**Side Fixture Mounting Kit**

Side Fixture Mounting Kit for enclosure size A5 / B1 / B2 / C1 / C2

To be used when retrofitting the following MCA options:

- MCA 120 Profinet
- MCA 121 EtherNet
- MCA 122 Modbus TCP
- MCA 123 POWERLINK
- MCA 124 EtherCAT
- Product group: R1

**130B5435** [🔗](#)**DIN Rail Mounting Kit****130B1235** [🔗](#)**VLT® PROFINET MCA 120, coated**

MCA 120 PROFINET interface

With reinforced coating (class 3C3 / IEC 60721-3-3)

- Supports operation on PROFINET network with extensive characteristics
- DCP support for easy setting u. Communication parameters via the PLC
- on Board web-Page with Drive Status
- parameterization with the MCT10 software
- 2-port version, reduced external hardware

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories

**130B1234** **VLT® Motion Control MCO 305, coated**

Integrated and programmable motion controller for VLT® AutomationDrive FC 301 and FC 302

- Adds additional functionality and flexibility as it is a freely programmable module
- Optimized for all types of positioning and synchronization applications
- Make your own program specially adapted to your application

Contains:

- synchronization (electronic shaft), positioning and electronic cam control
- 2 inputs support both stepwise and absolute encoders
- 1 encoder output (virtual master function)

10 digital inputs

- 8 digital outputs

- Sends and receives data via fieldbus interface (requires fieldbus option)

- PC software for programming and commissioning

Remember to order the Mounting kit if the above MCO option is required retrofitted.

130B7530 - Mounting kit for enclosures A2 and A3

130B7531 - Mounting kit for MCO Option, together with MCB 113, in enclosures A2 and A3

130B1413 - Mounting kit for enclosure B3

130B1414 - Mounting kit for MCO Option, together with MCB 113, in enclosure B3

130B7532 - Mounting kit for enclosure A5

130B7533 - Mounting kit for all enclosures B, C, D, E and F (B3 excepted)

Danfoss MCO options are not sold without prior advice.

Danfoss can offer help with programming / setting up MCO options.

Contact Danfoss for advice and prices.

Product group: R

**130B1245** **VLT® PROFIBUS Converter MCA 113, ctd**

Ensures easy and quick replacement of VLT®3000 to VLT® AutomationDrive

.

VLT® 3000 can then be replaced by VLT® AutomationDrive or

- the system Can be expanded without costly changes to the PLC program
- Flexible investment as it is easy to remove and replace option when upgrading to another fieldbus

Product group: R1

**130B1227** **VLT® Resolver Input MCB 103, coated**

Resolver extension for FC 300. Enables the connection of the following

Resolver types:

Input voltage: 4..8 Vrms

Input frequency: 2.5..15 kHz

Number of resolver poles: 2 or 4

For more information, please use this link to visit the product page on Danfoss Product Store 

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories

**130B1220** [🔗](#)**VLT® Safe PLC I/O MCB 108, coated**

Increases security and helps you meet requirement security levels

- VLT® AutomationDrive FC 302 has a safety input based on a single pole 24 V DC input

- Security in a cost-effective way

Possibility of connection to two conductor safety system

Possibility to interrupt on the plus or minus side without disturbing the sensor signal

**130B1219** [🔗](#)**VLT® EtherNet IP MCA 121, coated**

EtherNet/IP extends commercial off-the-shelf Ethernet to the Common Industrial Protocol (CIP™) – the same upper-layer protocol and object model found in DeviceNet. Built-in high-performance switch enabling line-topology, and eliminating the need for external switches. Device Level Ring (DLR) topology for higher system availability. Based on CIP™, makes the reuse of PLC program possible when migrating from DeviceNet to EtherNet/IP. Built-in web server provides remote diagnosis and reading out of basic drive parameters. E-mail notification provides fast access to warnings or alarm information. Unicast and Multicast communication for improved network utilization. Certified by ODVA for fulfilment of the newest standard.

**130B1264** [🔗](#)**VLT® Extended Relay Card MCB 113, ctd**

Adds 7 digital inputs and 2 analog outputs for increased flexibility. 4

SPDT relays. Meets NAMUR recommendations. Galvanic isolation capability.

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories

**130B1253** [🔗](#)**VLT® Position Controller MCO 351, ctd**

Extends the functional characteristics of the frequency converter in positioning applications

- Direct positioning via fieldbus, relative positioning, absolute positioning and touch probe positioning
- End stop handling (software and hardware)
- Mechanical brake handling (programmable hold delay)

Error handling

- Jog speed / manual operation
- None for programming, as it is pre-programmed

Remember to order the Mounting kit if the above MCO option is required retrofitted.

130B7530 - Mounting kit for enclosures A2 and A3

130B7531 - Mounting kit for MCO Option, together with MCB 113, in enclosures A2 and A3

130B1413 - Mounting kit for enclosure B3

130B1414 - Mounting kit for MCO Option, together with MCB 113, in enclosure B3

130B7532 - Mounting kit for enclosure A5

130B7533 - Mounting kit for all enclosures B, C, D, E and F (B3 excepted)

Danfoss MCO options are not sold without prior advice.

Danfoss can offer help with programming / setting up MCO options.

Contact Danfoss for advice and prices.

Product group: R

**130B1252** [🔗](#)**VLT® Synchronizing Ctrl. MCO 350, ctd**

MCO 350 - synchronous controller

Based on the MCO 305 prefabricated controller for Synchronization tasks. The adjustment takes place through parameter settings. Specific Programming skills are not required.

- 2 encoder inputs, both for incremental as well as absolute encoder
 - 1 encoder output (virtual master function)
 - 10 additional digital inputs
 - 8 additional digital outputs
 - fieldbus Communication (requires fieldbus card) with reinforced coating
-

**130B1246** [🔗](#)**VLT® PROFIBUS Converter MCA 114, ctd**

A special version of the PROFIBUS options that emulates VLT® 5000 commands in the VLT® AutomationDrive. The VLT® 5000 can be replaced by the VLT® AutomationDrive, or an existing system can be expanded without costly change of the PLC program. For upgrade to a different fieldbus, the installed converter is easily removed and replaced with a new option. This secures the investment without losing flexibility. The option supports DPV1.

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories

**130B1196** [🔗](#)**VLT® Modbus TCP MCA 122**

MCA 122 Modbus TCP interface Complex compatibility tests make the perfect operation in Modbus TCP systems for sure.

- On Board web-Page with Drive Status
- Parameterization with MCT10 software
- 2 port version reduces effort for external hardware (switch, cables, etc.) and allows flexible bus topologies

**130B1190** [🔗](#)**IP21 conversion kit, top, B4**

IP21 top cover for enclosure B4

Product group: R1

**130B1189** [🔗](#)**IP21 conversion kit for B4 frame.**

IP21 cover for enclosure B4

Product group: R1

**130B1172** [🔗](#)**VLT® Sensor Input Card MCB 114, unctd**

Protects the motor from being overheated by monitoring the temperature of bearings and windings in the motor. Three self-detecting sensor inputs for 2 or 3 wire PT100/PT1000 sensors. One additional analog input 4–20 mA.

**130B1170** [🔗](#)**LCP Panel Mounting Kit**

The kit includes fasteners and gasket. No LCP and no cable included.

**130B1212** [🔗](#)**VLT® General Purpose I/O MCB 101, ctd**

MCB 101 - Advanced I / O option

Expands the number of freely programmable

Control inputs and outputs around the following I / Os:

- 3 digital inputs opto-decoupled 0 - 24 V.
 - 2 analog inputs 0 - 10 V.
 - 2 digital outputs NPN / PNP switchable 24 V
 - 1 analog output 0/4 - 20 mA
- with reinforced coating

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories

**130B1210** [🔗](#)**VLT® Relay Option MCB 105, coated**

Relay extension for FC 100 and FC 300.

Extension with 3 additional load relays (changeover contacts), easy to retrofit thanks to modular technology.

Painted version for harsh environments,

easy to retrofit thanks to modular technology.

Max. Load 240V AC (resistive): 2 A

Max. Load 240V AC (Cos Phi 0.4): 0.2 A

Max. Load 24V DC (ohmic): 1 A

Max. Load 24V DC (inductive): 0.1 A

**130B1208** [🔗](#)**1xMCB 107 24V DC coat w. mount. brackets**

Connect an external DC supply to keep the control section and any installed option alive during power failure. Enables full operation of the LCP (including the parameter setting) and all installed options without connection to mains.

**130B1205** [🔗](#)**VLT® CAN Open MCA 105, coated**

CANopen interface for FC 300. Max. Baud rate 500 kBit / s. Support that DSP402 drive profile and PDO / SDO communication. Painted version for harsh environments. Easy to retrofit thanks to modular technology.

**130B1203** [🔗](#)**VLT® Encoder Input MCB 102, coated**

Offers the possibility to connect various types of incremental and absolute encoders. The connected encoder can be used for closed-loop speed control as well as closed-loop flux motor control.

**130B1202** [🔗](#)**VLT® DeviceNet MCA 104, coated**

MCA 104 - DeviceNet interface Option for FC300 and FC100 for mounting on the control card. Painted version

**130B1200** [🔗](#)**VLT® Profibus DP V1 MCA 101, coated**

Provides wide compatibility, a high level of availability, support for all major PLC vendors and compatibility with future versions. Fast, efficient communication, transparent installation, advanced diagnosis and parameterization and auto-configuration of process data using GSD-file. Acyclic parameterization using PROFIBUS DP-V1, -PROFIdrive or Danfoss FC profile state machines, PROFIBUS DP-V1, Master Class 1 and 2.

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories



130B1387 [🔗](#)
5xMCB107 24VDC no coat w.out mount brack



130B1386 [🔗](#)
VLT® Profibus DP V1 MCA 101, ctd, 5pcs



130B1385 [🔗](#)
VLT® Profibus DP V1 MCA101, unctd 5pcs



130B1272 [🔗](#)
VLT® Sensor Input Card MCB 114, coated
MCB 114 - PT100 / PT1000 option
For FC100-FC200 and FC302 (painted version)
Enables the evaluation of up to 3 PT 100 or 3 PT 1000 sensors
- Connection of 2 and 3 wire sensors
- Automatic detection of the sensor type
- Additional 4-20mA input



130B1296 [🔗](#)
VLT® Modbus TCP MCA 122, coated
The first industrial Ethernet-based protocol for automation. Connects to Modbus-TCP-based networks. Able to handle connection interval down to 5 ms in both directions, positioning it among the fastest performing Modbus TCP devices in the market. For master redundancy it features hot swapping between two masters.



130B1164 [🔗](#)
VLT® Extended Relay Card MCB 113
Adds 7 digital inputs and 2 analog outputs for increased flexibility. 4 SPDT relays. Meets NAMUR recommendations. Galvanic isolation capability.



130B1135 [🔗](#)
VLT® PROFINET MCA 120, uncoated
MCA 120 PROFINET interface
-Supports operation on PROFINET network with extensive properties
-DCP support for easy setting u. Communication parameters via the PLC
- On Board web-Page with Drive Status
- Parameterization with the MCT10 software
- 2 port version, reduced external hardware

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories

**130B1134** [🔗](#)**VLT® Motion Control MCO 305, uncoated**

Integrated and programmable motion controller for VLT® AutomationDrive FC 301 and FC 302

- Adds additional functionality and flexibility as it is a freely programmable module
- Optimized for all types of positioning and synchronization applications
- Make your own program specially adapted to your application

Contains:

- synchronization (electronic shaft), positioning and electronic cam control
- 2 inputs support both stepwise and absolute encoders
- 1 encoder output (virtual master function)

10 digital inputs

8 digital outputs

- Sends and receives data via fieldbus interface (requires fieldbus Option)
- PC software for programming and commissioning.

Remember to order the Mounting kit if the above MCO option is required retrofitted.

130B7530 - Mounting kit for enclosures A2 and A3

130B7531 - Mounting kit for MCO Option, together with MCB 113, in enclosures A2 and A3.

130B1413 - Mounting kit for enclosure B3

130B1414 - Mounting kit for MCO Option, together with MCB 113, in enclosure B3

130B7532 - Mounting kit for enclosure A5

130B7533 - Mounting kit for all enclosures B, C, D, E and F (B3 excepted)

Danfoss MCO options are not sold without prior advice. Danfoss can offer help with programming / setting up MCO options. Contact Danfoss for advice and prices.

Product group: R

**130B1127** [🔗](#)**VLT® Resolver Input MCB 103, uncoated**

Enables connection of a resolver to provide speed feedback from the motor. Spring loaded connection.

**130B1125** [🔗](#)**VLT® General Purpose I/O MCB 101, uncoated**

MCB 101 - Advanced I / O option

Expands the number of freely programmable Control inputs and outputs around the following I / Os:

- 3 digital inputs opto-decoupled 0 - 24 V.
 - 2 analog inputs 0 - 10 V.
 - 2 digital outputs NPN / PNP switchable 24 V
 - 1 analog output 0/4 - 20 mA
-

**130B1124** [🔗](#)**VLT® Control Panel LCP 101, numeric**

Numerical control unit for FC 100 and FC 300. Allows access to all device parameters.

Quick menu for brief commissioning. Manual / auto switchover and alarm acknowledgment.

**130B1120** [🔗](#)**VLT® Safe PLC I/O MCB 108, uncoated**

Connection converter for FC 300 with control input for a safe stop. Allows secure connection.

Output modules with diagnostic pulse (Cross-circuit monitoring).

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories



130B1119 [🔗](#)

VLT® EtherNet/IP MCA 121, uncoated

MCA 121 EtherNet / IP interface

- Allows connection to EtherNet / IP based Automation systems via CIP (CommonInterface Protocol)
- 2 port design reduces external components
- HTTP for diagnosis via built-in web server
- SMTP, DHCP and FTP protocols
- Prepared for parameterization with the MCT 10 software via TCP / IP
- Certified according to ODVA



130B1117 [🔗](#)

LCP Mounting Kit, w/ no LCP

The kit includes fasteners, 3m cable and gasket - There is no LCP included.



130B1115 [🔗](#)

VLT® Encoder Input MCB 102, uncoated

Offers the possibility to connect various types of incremental and absolute encoders. The connected encoder can be used for closed-loop speed control as well as closed-loop flux motor control.



130B1114 [🔗](#)

LCP Mounting Kit w/ numerical LCP101, 3m

The kit includes numerical LCP, fasteners, 3m cable and gasket.



130B1113 [🔗](#)

lcp panel kit/fc300 fg-lcp panel kit

The kit includes graphical LCP, fasteners, 3m cable and gasket.



130B1110 [🔗](#)

VLT® Relay Option MCB 105, uncoated

Relay extension for FC 100 and FC 300. Extension with 3 additional load relays (changeover contacts), easy to retrofit thanks to modular technology.

Max. Load 240V AC (resistive): 2 A

Max. Load 240V AC (Cos Phi 0.4): 0.2 A

Max. Load 24V DC (ohmic): 1 A

Max. Load 24V DC (inductive): 0.1 A

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories



130B1153 [🔗](#)

VLT® Position Controller MCO351, unctd

Extends the functional characteristics of the frequency converter in positioning applications

- Direct positioning via fieldbus, relative positioning, absolute positioning and touch probe positioning
 - End stop handling (software and hardware)
 - Mechanical brake handling (programmable hold delay)
- Error handling

- Jog speed / manual operation
- None for programming, as it is pre-programmed

Remember to order the Mounting kit if the above MCO option is required retrofitted.

130B7530 - Mounting kit for enclosures A2 and A3

130B7531 - Mounting kit for MCO Option, together with MCB 113, in enclosures A2 and A3

130B1413 - Mounting kit for enclosure B3

130B1414 - Mounting kit for MCO Option, together with MCB 113, in enclosure B3

130B7532 - Mounting kit for enclosure A5

130B7533 - Mounting kit for all enclosures B, C, D, E and F (B3 excepted)

Danfoss MCO options are not sold without prior advice. Danfoss can offer help with programming / setting up MCO options. Contact Danfoss for advice and prices.

Product group: R



130B1152 [🔗](#)

VLT® Synchronizing Contr. MCO350, unctd

Expands the functional properties of the VLT® AutomationDrive in synchronizing applications, and replaces traditional mechanical solutions. Speed synchronizing. Position (angle) synchronizing with or without marker correction. Online adjustable gear ratio. Online adjustable position (angle) offset. Encoder output with virtual master function for synchronization of multiple followers. Control via I/Os or fieldbus. Home function. Configuration as well as read-out of status and data via the Local Control Panel of the drive.



130B1137 [🔗](#)

VLT® PTC Thermistor Card MCB 112, ctd

MCB 112 PTC - thermistor relay MS220DA In connection with ATEX certified explosion-proof motors for full motor protection. Certified PTC sensors are the sole protection required.

Integrable module with ATEX-compliant full thermal motor protection

- 1 PTB-certified PTC thermistor input
- 1 switch-off signal for using the Safe Stop function
- 1 logic output for error identification



130B1077 [🔗](#)

Blindcover, w/ Danfoss logo, IP55/66

LCP Blindcover IP66



130B1071 [🔗](#)

6 Pole Connector, FC series, 10 pcs

6-pole spring cage connectors 10 pcs

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories



130B1070 [🔗](#)

RS485 plug, FC series,10 pcs

10pcs RS485 connectors for FC-series.
Product group: R



130B1108 [🔗](#)

VLT® 24V DC Supply MCB 107, uncoated

Connect an external DC supply to keep the control section and any installed option alive during power failure. Enables full operation of the LCP (including the parameter setting) and all installed options without connection to mains.



130B1107 [🔗](#)

VLT® Control Panel LCP 102

Graphic operating unit LCP102 Illuminated graphic display with plain text. Supports all languages and characters. Quick menu for brief commissioning.Saving and copying parameter sets.Online help for each function



130B1103 [🔗](#)

VLT® CAN Open MCA 105, uncoated

Standardized handling and interoperability for high flexibility and low costs. Fully equipped with both high-priority access to control and status of the drive (PDO Communication) and access to all parameters through acyclic data (SDO Communication). For interoperability the option has implemented the DSP402 AC-drive profile.



130B1102 [🔗](#)

VLT® DeviceNet MCA 104, uncoated

Robust, efficient data handling thanks to advanced Producer/Consumer technology. ODVA's strong conformance testing policies ensure products are interoperable, and the AC-drive profile, supported using I/O instance 20/70.21/71, secures compatibility to existing systems.



130B1100 [🔗](#)

VLT® Profibus DP V1 MCA 101

Provides wide compatibility, a high level of availability, support for all major PLC vendors and compatibility with future versions. Fast, efficient communication, transparent installation, advanced diagnosis and parameterization and auto-configuration of process data using GSD-file. Acyclic parameterization using PROFIBUS DP-V1, -PROFIdrive or Danfoss FC profile state machines, PROFIBUS DP-V1, Master Class 1 and 2.



130B1088 [🔗](#)

LCP Blindcover, w/ Danfoss logo, IP20/21

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories



130B1490 [↗](#)

VLT® POWERLINK MCA 123, coated

Represents the second generation of fieldbus. The high bit rate of industrial Ethernet can now be used to make the full power of IT technologies used in the automation world available for the factory world.



175Z0929 [↗](#)

LCP Cable, 3m

Cable for control panel (LCP), 3 meters
 Works with the following LCP:
 Alphanumeric control panel LCP3 - 175N0131
 VLT® LCP 102 Graphic Display - 130B1107
 VLT® LCP 101 Numeric Display - 130B1124
 VLT® LCP 102 Graphic display IP66 - 130B1078
 Product group: F1

Image coming soon

175U0009 [↗](#)

Mounting bracket Kit, 216 x 30 x 18mm

Mounting angle for flatpack resistor 200W



175N2584 [↗](#)

VLT® EtherNet/IP Modbus TCP gateway

Image coming soon

134B5225 [↗](#)

Remote LCP unit, 10m

Remote mounting kit for LCP with cover for outdoor mounting with 10 m (33 ft) cable

Image coming soon

134B5224 [↗](#)

Remote LCP unit, 5m

Remote mounting kit for LCP with cover for outdoor mounting with 5 m (16 ft) cable



134B5223 [↗](#)

Remote LCP unit, 3m

Remote mounting kit for LCP with cover for outdoor mounting with 3 m (10 ft) cable

For more information, please use this link to visit the product page on Danfoss Product Store [↗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories



134B0460

LCP 103 Wireless Communication Panel

With VLT® Wireless Communication Panel LCP 103 you can communicate with MyDrive® Connect - an app that can be downloaded for iOS and Android based smartphones. MyDrive® Connect makes commissioning easy, monitor and maintain tasks on your frequency converter. VLT® Wireless Communication Panel LCP 103 shows the current status of the drive (On, Warning, Alarm, Wifi connection) via built-in LED. Detailed information is also available using MyDrive® Connect. Here do you have access to i.a. status, menu and alerts. You can also see graphs over the latest available data.

The new VLT® Wireless Communication Panel LCP 103 allows you to wireless communication to the following drives:

- VLT® HVAC Drive FC 102
- VLT® Refrigeration Drive FC 103
- VLT® AQUA Drive FC 202
- VLT® AutomationDrive FC 302

[!] Note!

LCP 103 only works on frequency converters produced in 2018 (White USB stik).

Product group: R1

Image coming soon

134B1992

Control Terminals w/ screw connections



130B1266

VLT MCB 115 Programmable I/O, coated

VLT® MCB 115 programmable I / O, coated



134B6544

Real Time Clock D slot option MCB117

The VLT® Real-time clock option MCB 117 option provides advanced data-logging functionality to the following drives

- VLT® HVAC Drive FC 102
- VLT® Refrigeration Drive FC 103
- VLT® Aqua Drive FC 202
- VLT® Automation Drive FC 301/FC 302

Note: This option is compatible only with MK-II control cards & upto 90 KW supporting A,B & C Frames.

Image coming soon

134B7207

cable clamp/d=44-48 k48b

For more information, please use this link to visit the product page on Danfoss Product Store

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories

Image
coming
soon**134B7209** [🔗](#)

cable clamp/d=36-40 k40b

**130B0295** [🔗](#)

sparepart/terminals accessory bag

Image
coming
soon**134B1983** [🔗](#)

Accessory bag for framesize B4 small

Accessory bag for framesize B4 small

Image
coming
soon**134B1984** [🔗](#)

Accessory bag for framesize B4 big

Accessory bag for framesize B4 big

Image
coming
soon**130B4847** [🔗](#)

extension cable for lcp+communication

**134B8814** [🔗](#)

VLT® PROFINET MCA120 coated 5pcs

**134B8492** [🔗](#)

Transducer 0-10g, 4-20mA; HS-22B50

**134B8493** [🔗](#)

Transducer 0-25mm/s RMS 4-20mA

CBM Transducer 0-25mm/s RMS 4-20mA

**134B8494** [🔗](#)

Transducer w, temp 0-25mm/s RMS 4-20mA

**134B8496** [🔗](#)

CABLE ASSY 10M, STRAIGHT SOCKET CONNETC.

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories

Image
coming
soon**134B8497** **Cable assy, M12 female connec.10m screen**Image
coming
soon**134B6883** **VLT Progr. Contr. MCB 301, coated****134B9414** **Antifreeze Thermostat FS20, 0/+15C**

TWO-PHASE FROST PROTECTION THERMOSTATS FS-20-UW

Electronic frost protection thermostat or frost monitor with switching relay output, continuous temperature and valve output (summation output 0–10 V) and control and cascading output (0–10 V), optionally with connection for a heating element. A IP65 resistant plastic housing with display with the actual temperature, measuring range, overrange/underrange of the set switch point (frost protection temperature) and alarm indicator for "frost" or "error" (capillary breakage, overvoltage/undervoltage), quick-locking screws and a fully active sensor rod made of copper. The delivery scope includes a set of MK-05-K mounting clamps for expert attachment of the sensor rod.

Measuring range: 0...+15 °C / 32...+59 °F

Accuracy: typical ± 1 K (at +10 °C)

Sensor type: 3m Copper rod active along the entire sensor length, min. response length of 25 cm

Input: 1 x 0 -10 V control input DDC & 1 x 0 -10 V cascading input

Output: 1 x 0 -10 V output temperature (corresponding to 0...+15 °C) & 1 x 0 -10 V output valve (frost signal with control voltage and cascading)

1 x 0 -10 V output valve (frost signal with control voltage and cascading)

1 x potential-free changeover contact (24 V), range of adjustment 0...+15 °C

1 x potential-free changeover contact (24 V), range of adjustment 0...+15 °C

Current consumption: max. 100 mA at 24 V DC

Load resistance: RL > 50 kOhm

Ambient temperature: –15...+50 °C / 5...+122 °F (Housing) & –20...+60 °C / –4...+140 °F Sensor and capillary tube > 20 cm from the housing.

Power: 24VAC/DC (± 10%) 24DC < 2,4W

T2-IP65 plastic housing with three-line display 70x40 mm (WxH), a M16 cable glands and MK-05-K mounting clamps.

Housing dimensions: 126 x 90 x 50 mm / 4.96 x 3.54 x 1.97 in

For more information, please use this link to visit the product page on Danfoss Product Store 

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories



134B9413

Airflow Sensor KLQ CO2 & Air Quality

DUCT AIR QUALITY (VOC) AND CO2 SENSOR KLQ-CO2-MB

Maintenance-free duct sensor covering air quality (VOC 0...100 %), carbon dioxide (CO2 0...5000 ppm) and atmospheric pressure (hPa). The air quality is detected by a VOC sensor (mixed gas sensor for volatile organic substances) and include an automatic calibration. It determines the loading of the room air due to contaminated gases such as cigarette smoke, body perspiration, exhaled breathing air, solvent vapors, emissions etc. The air contamination can be selected into different sensitivity ranges as low, medium or high. The CO2 measurement is performed using an optical NDIR sensor (non-dispersive infra-red technology), and the detection range is calibrated for standard applications such as monitoring residential rooms and conference rooms. A microprocessor-controlled solution with factory sensor calibration, Modbus RTU connection in a resistant IP65 plastic housing with mounting flange, quick-locking screws and two M16 cable gland for cable connection. International SI units (default) can be changed to imperial (via Modbus).

VOC Sensor: Volatile Organic Compounds sensor (metal oxide) with automatic calibration

VOC measuring range: 0...100 % air quality; referred to calibrating gas & selection of VOC sensitivities (low/medium/high)

VOC measuring accuracy: typical $\pm 20\%$ of final value (referred to calibrating gas)

CO2 Sensor: optical NDIR sensor (non-dispersive infra-red technology) including atmospheric pressure compensation (up to 1100 mbar) with manual or automatic calibration

CO2 measuring range: 0...5000 ppm

CO2 measuring accuracy: typical ± 30 ppm ($\pm 3\%$ of measured value) & temperature dependence: ± 5 ppm pro $^{\circ}\text{C}$ or $\pm 0,5\%$ of measured value pro $^{\circ}\text{C}$ (whichever is higher) & pressure dependence: $\pm 0.13\%$ per mm Hg

Medium: clean air and non-aggressive, non-combustible gases

Power: 24VAC/DC ($\pm 10\%$) 24DC <1,6W

Operation temperature: $-10...+60$ $^{\circ}\text{C}$ / $14...+140$ $^{\circ}\text{F}$

T2-IP65 plastic housing two M20 cable glands

Housing dimensions: 126 x 90 x 50 mm / 4.96 x 3.54 x 1.97 in

For more information, please use this link to visit the product page on Danfoss Product Store 

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories

**134B9412** [🔗](#)**Airflow Sensor TF65 PT1000 Temperature**

DUCT TEMPERATURE SENSOR TF 65

The TF 65 temperature measuring transducer is a PT1000 class B resistance sensor with passive output. Measuring range from $-30...+150^{\circ}\text{C}$. In a resistant IP67 plastic housing and M16 cable gland for cable connection and a straight protective measuring tube and a mounting flange.

Sensor type: PT1000 class B (DIN EN 60751) 1000ohm at $0^{\circ}\text{C} \pm 0,3\text{ K}$ Measuring range: $-30...+150^{\circ}\text{C} / -22...+302^{\circ}\text{F}$ Ambient temperature: $-20...+100^{\circ}\text{C} / -4...+212^{\circ}\text{F}$ Testing current: $< \mathit{0.6\text{ mA}}$ Insulating resistance: 100 M#, at $+20^{\circ}\text{C}$ (500V DC)

Connection type: 2-wire connection

Measuring tube: stainless steel, V4A (1.4571), $\varnothing 6\text{ mm}$, inserted length = 300 mm / 11.8 in

T1-IP67 plastic housing with a M16 cable glands and a mounting flange.

Housing dimensions: 72 x 64 x 37.8 mm / 2.83 x 2.52 x 1.49 in

**134B9411** [🔗](#)**Wall Sensor AFTF Temp & Humidity**

ON-WALL- HUMIDITY- AND TEMPERATURE SENSORS AFTF-MB

Calibratable outside humidity and temperature sensor AFTF, detect the relative humidity (0...100% RH) and the temperature ($-35...+80^{\circ}\text{C}$), including various parameters in the humidity measurement. Applied in clean air and non-aggressive, dust-free environment. With a Modbus connection in a resistant IP65 plastic housing and M20 cable gland for cable connection, with quick-locking screws and an exchangeable plastic sinter filter. International SI units (default) can be changed to imperial (via Modbus).

Measuring range: 0...100 % RH (humidity) / $-35...+80^{\circ}\text{C}$ (temperature)

Medium: clean air and non-aggressive, non-combustible gases

Deviation, humidity: typical $\pm 2.0\%$ (20...80 % RH) at $+25^{\circ}\text{C}$, otherwise $\pm 3.0\%$ Deviation, temperature: typical $\pm 0.4\text{ K}$ at $+25^{\circ}\text{C} / \pm 77^{\circ}\text{F}$ Zero point offset: $\pm 10\%$ RH (humidity) / $\pm 5^{\circ}\text{C}$ (temperature)Power: 24VAC ($\pm 20\%$) / 15...36VDC - 24DC $< \mathit{1,2\text{ W}}$ Operation temperature: $-30...+70^{\circ}\text{C} / -22...+158^{\circ}\text{F}$

T3-IP65 plastic housing with two M20 cable glands

Housing dimensions: 108 x 78.5 x 43.3 mm / 4.25 x 3.1 x 1.7 in

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories

**134B9410****Wall Sensor ATM2 Temperature**

OUTSIDE / WET ROOM TEMPERATURE SENSOR ATM2-MB

Calibratable outside temperature sensor ATM2, PT1000 measure temperature (-50...+150 °C), with Modbus RTU connection, in a resistant IP65 plastic housing with quick-locking screws and M20 cable gland for cable connection. International SI units (default) can be changed to imperial (via Modbus).

Sensor type: PT1000 class B (DIN EN 60751)

Measuring range: - 50...+150°C / -31... +176°F

Deviation: typical ± 0.2 K at +25 °C / ± 77 °F

Zero point offset: ± 10 °C / ± 50 °F

Ambient temperature: Measuring transducer -30...+70 °C / -22... +158°F

Medium: clean air and non-aggressive, non-combustible gases

Power: 24VAC (± 20%) / 15...36VDC - 24DC &lt;1,2W

Operation temperature: -30...+70 °C / -22...+158 °F

T3-IP65 plastic housing with two M20 cable glands

Housing dimensions: 108 x 78.5 x 43.3 mm / 4.25 x 3.1 x 1.7 in

Image
coming
soon**134B9409****Airflow Sensor 8147 Temp&Humidity&7000Pa**

DUCT HUMIDITY-, TEMPERATURE- AND PRESSURE SENSORS ±7000PA-MB

Maintenance-free duct sensor covering humidity, temperature and pressure in one transducer. Microprocessor-controlled with Modbus RTU connection in a resistant IP65 plastic housing with quick-locking screws and M16 cable gland for cable connection. Including mounting flange to detect the relative humidity (0...100% RH) and the temperature (-35...+80 °C) inside a tube, with an exchangeable plastic sinter filter. A differential air pressure (max. ± 7000 Pa) with connection nozzles for pressure hose (Ø 6 mm). The duct sensor is applied in a non-aggressive and dust-free environment and is suitable for installation in ceilings, ducts and devices. International SI units (default) can be switched to Imperial (via Modbus).

Measuring range: 0...100 % RH (humidity) / - 35...+80°C / -31... +176°F (temperature)

Medium: clean air and non-aggressive, non-combustible gases

Deviation, humidity: typical ± 2.0 % (20...80 % RH) at +25°C/+77°F , otherwise ± 3.0 %

Deviation, temperature: typical ± 0.2 K at +25 °C / ± 0.4 °F at +77 °F

Pressure range: ± 7000 Pa

Accuracy: 7000 Pa/28 inWC: typical ± 105 Pa at +25 °C / ± 0.12 inWC at +77 °F

Above- # below-pressure: max. ± 50 kPa

Power: 24VAC (± 20%) / 15...36VDC - 24DC &lt;0,2W

Operation temperature: -30...+70 °C / -22...+158 °F

Media temperature -20...+50 °C / -4...+122 °F IP65 plastic housing two

M16 cable glands

Housing dimensions: 126 x 90 x 50 mm / 4.96 x 3.54 x 1.97 in

For more information, please use this link to visit the product page on Danfoss Product Store

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories

Image
coming
soon**134B9408****Airflow Sensor 8148 Temp&Humidity&500Pa**

DUCT HUMIDITY-, TEMPERATURE- AND PRESSURE SENSORS ±500PA-MB
Maintenance-free duct sensor covering humidity, temperature and pressure in one transducer. Microprocessor-controlled with Modbus RTU connection in a resistant IP65 plastic housing with quick-locking screws and M16 cable gland for cable connection. Including mounting flange to detect the relative humidity (0...100% RH) and the temperature (-35...+80 °C) inside a tube, with an exchangeable plastic sinter filter. A differential air pressure (max. ± 500 Pa) with connection nozzles for pressure hose (Ø 6 mm). The duct sensor is applied in a non-aggressive and dust-free environment and is suitable for installation in ceilings, ducts and devices. International SI units (default) can be switched to Imperial (via Modbus).

Measuring range: 0...100 % RH (humidity) / - 35...+80°C / -31... +176°F (temperature)

Medium: clean air and non-aggressive, non-combustible gases

Deviation, humidity: typical ± 2.0 % (20...80 % RH) at +25°C/+77°F , otherwise ± 3.0 %

Deviation, temperature: typical ± 0.2 K at +25 °C / ± 0.4 °F at +77 °F

Pressure range: ± 500 Pa

Accuracy: 500 Pa/2.0 inWC: typical ± 13 Pa at +25 °C / ± 0.05 inWC at + 77 °F

Above- # below-pressure: max. ± 50 kPa

Power: 24VAC (± 20%) / 15...36VDC - 24DC <0,2W

Operation temperature: -30...+70 °C / -22...+158 °F

Media temperature -20...+50 °C / -4...+122 °F IP65 plastic housing two

M16 cable glands

Housing dimensions: 126 x 90 x 50 mm / 4.96 x 3.54 x 1.97 in

For more information, please use this link to visit the product page on Danfoss Product Store

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories

**134B9407** [🔗](#)**Airflow Sensor KFTF Temp & Humidity**

DUCT HUMIDITY- AND TEMPERATURE SENSORS KFTF-MB

Calibratable duct humidity and temperature sensor KFTF-T3 ($\pm 2.0\%$) with Modbus RTU connection, in a resistant IP65 plastic housing with quick-locking screws and M16 cable gland for cable connection and a plastic sinter filter (exchangeable). Including mounting flange to detect the relative humidity (0...100% RH) and the temperature ($-35...+80\text{ }^\circ\text{C}$) inside a tube, including various parameters in the humidity measurement. The duct sensor is applied in a non-aggressive and dust-free environment and is suitable for installation in ceilings, ducts and devices.

International SI units (default) can be switched to Imperial (via Modbus).

Measuring range: 0...100 % RH (humidity) / $-35...+80\text{ }^\circ\text{C}$ (temperature)

Medium: clean air and non-aggressive, non-combustible gases

Deviation, humidity: typical $\pm 2.0\%$ (20...80 % RH) at $+25\text{ }^\circ\text{C}$, otherwise $\pm 3.0\%$

Deviation, temperature: typical $\pm 0.2\text{ K}$ at $+25\text{ }^\circ\text{C}$

Zero point offset: $\pm 10\%$ RH (humidity) / $\pm 5\text{ }^\circ\text{C}$ (temperature)

Power: 24VAC ($\pm 20\%$) / 15...36VDC - 24DC <1,2W

Operation temperature: $-30...+70\text{ }^\circ\text{C}$ / $-22...+158\text{ }^\circ\text{F}$

T3-IP65 plastic housing with two M20 cable glands

Housing dimensions: 108 x 78.5 x 43.3 mm / 4.25 x 3.1 x 1.7 in

**134B9406** [🔗](#)**Pressure Sensor 7227 2x7000Pa, Analog**DUAL AIR PRESSURE SENSOR $\pm 7000\text{ Pa}$ & $\pm 7000\text{ Pa}$, ANALOGUE

Dual pressure transmitter with 2x8 switchable measuring ranges and 2 automated analogue output signals in a resistant IP65 plastic housing with quick-locking screws, connection nozzles for pressure hose ($\varnothing 6\text{ mm}$) and a M16 cable gland for cable connection. The pressure measuring transducer automatically detects the required output type and converts the measurands into the required standard signal of 0-10 V or 4...20 mA.

Pressure range selection: $\pm 7000\text{ Pa}$ - 0...1000Pa / 2000Pa / 3000Pa / 5000Pa / 7000Pa

Accuracy: 7000 Pa typical $\pm 105\text{ Pa}$

Zero point offset: $\pm 10\%$ of measuring range

Above- # below-pressure: max. $\pm 50\text{ kPa}$

Power: 24VAC/DC ($\pm 10\%$) <1,3W,

Output: automatically switching 0-10 V # 4...20 mA

Working resistance: R_a (ohms) = 25...450 Ohm (at I output)

Load resistance: R_L > 15 kOhm (at U output)

Operation / Media temperature: $-20...+50\text{ }^\circ\text{C}$ / $-4...+122\text{ }^\circ\text{F}$

T2-IP65 plastic housing with one M16 cable gland

Housing dimensions: 126 x 90 x 50 mm / 4.96 x 3.54 x 1.97 in

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories

**134B9405****Pressure Sensor 7229 500/7000Pa, Analog**

DUAL AIR PRESSURE SENSOR $\pm 500\text{Pa}$ & $\pm 7000\text{Pa}$, ANALOGUE
 Dual pressure transmitter with 2x8 switchable measuring ranges and 2 automated analogue output signals in a resistant IP65 plastic housing with quick-locking screws, connection nozzles for pressure hose (\varnothing 6 mm) and a M16 cable gland for cable connection. The pressure measuring transducer automatically detects the required output type and converts the measurands into the required standard signal of 0–10 V or 4...20 mA.
 Pressure range selection: $\pm 500\text{ Pa} - 0 \dots 100\text{Pa} / 200\text{Pa} / 300\text{Pa} / 500\text{Pa}$
 Pressure range selection: $\pm 7000\text{ Pa} - 0 \dots 1000\text{Pa} / 2000\text{Pa} / 3000\text{Pa} / 5000\text{Pa} / 7000\text{Pa}$
 Accuracy: 500 Pa typical $\pm 13\text{ Pa}$
 Accuracy: 7000 Pa typical $\pm 105\text{ Pa}$
 Zero point offset: $\pm 10\%$ of measuring range
 Above- # below-pressure: max. $\pm 50\text{ kPa}$
 Power: 24VAC/DC ($\pm 10\%$) <1,3W,
 Output: automatically switching 0 -10 V # 4...20 mA
 Working resistance: R_a (ohms) = 25...450 Ohm (at I output)
 Load resistance: R_L > 15 kOhm (at U output)
 Operation / Media temperature: $-20 \dots +50\text{ }^\circ\text{C} / -4 \dots +122\text{ }^\circ\text{F}$
 T2-IP65 plastic housing with one M16 cable gland
 Housing dimensions: 126 x 90 x 50 mm / 4.96 x 3.54 x 1.97 in

**134B9404****Pressure Sensor 7225 2x500Pa, Analog**

DUAL AIR PRESSURE SENSOR $\pm 500\text{Pa}$ & $\pm 500\text{Pa}$, ANALOGUE
 Dual pressure transmitter with 2x8 switchable measuring ranges and 2 automated analogue output signals in a resistant IP65 plastic housing with quick-locking screws, connection nozzles for pressure hose (\varnothing 6 mm) and a M16 cable gland for cable connection. The pressure measuring transducer automatically detects the required output type and converts the measurands into the required standard signal of 0–10 V or 4...20 mA.
 Pressure range selection: $\pm 500\text{ Pa} - 0 \dots 100\text{Pa} / 200\text{Pa} / 300\text{Pa} / 500\text{Pa}$
 Accuracy: 500 Pa typical $\pm 13\text{ Pa}$
 Zero point offset: $\pm 10\%$ of measuring range
 Above- # below-pressure: max. $\pm 50\text{ kPa}$
 Power: 24VAC/DC ($\pm 10\%$) <1,3W,
 Output: automatically switching 0 -10 V # 4...20 mA
 Working resistance: R_a (ohms) = 25...450 Ohm (at I output)
 Load resistance: R_L > 15 kOhm (at U output)
 Operation / Media temperature: $-20 \dots +50\text{ }^\circ\text{C} / -4 \dots +122\text{ }^\circ\text{F}$
 T2-IP65 plastic housing with one M16 cable gland
 Housing dimensions: 126 x 90 x 50 mm / 4.96 x 3.54 x 1.97 in

For more information, please use this link to visit the product page on Danfoss Product Store

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories

**134B9402****Pressure Sensor 7247T 2x7000Pa & PT1000**DUAL AIR PRESSURE SENSOR $\pm 7000\text{Pa}$ & $\pm 7000\text{Pa-MB}$

Dual maintenance-free pressure sensor with connection facility for external Pt1000 sensor ($-50\dots+150^\circ\text{C}$). Microprocessor-controlled with Modbus RTU connection in a resistant IP65 plastic housing with quick-locking screws, connection nozzles for pressure hose ($\varnothing 6\text{ mm}$) and M16 cable gland for cable connection. International SI units (default) can be switched to Imperial (via Modbus). Incl. connection set ASD-06 (2 m connecting hose, two pressure port nipples, screws).

Pressure range: $\pm 7000\text{ Pa}$ and $\pm 7000\text{ Pa}$ Accuracy: 7000 Pa/28 inWC: typical $\pm 105\text{ Pa}$ at $+25^\circ\text{C}$ / $\pm 0.12\text{ inWC}$ at $+77^\circ\text{F}$ Linearity: $\pm 1\%$ of final value & Temperature drift: $\pm 0.1\%$ per $^\circ\text{C}$ #
 $^\circ\text{F}$ Zero point offset: $\pm 10\%$ of measuring rangeAbove- # below-pressure: max. $\pm 50\text{ kPa}$ / $\pm 200\text{ inWC}$ Power: 24VAC ($\pm 20\%$) & $0,2\text{W}$ / 15...36VDCOperation temperature: $-30\dots+70^\circ\text{C}$ / $-22\dots+158^\circ\text{F}$ Media temperature $-20\dots+50^\circ\text{C}$ / $-4\dots+122^\circ\text{F}$

T2-IP65 plastic housing with two M16 cable glands & one M12 for temperature

Housing dimensions: 126 x 90 x 50 mm / 4.96 x 3.54 x 1.97 in

**134B9401****Pressure Sensor 7249T 500/7000Pa & PT1000**DUAL AIR PRESSURE SENSOR $\pm 500\text{Pa}$ & $\pm 7000\text{Pa-MB}$

Dual maintenance-free pressure sensor with connection facility for external Pt1000 sensor ($-50\dots+150^\circ\text{C}$). Microprocessor-controlled with Modbus RTU connection in a resistant IP65 plastic housing with quick-locking screws, connection nozzles for pressure hose ($\varnothing 6\text{ mm}$) and M16 cable gland for cable connection. International SI units (default) can be switched to Imperial (via Modbus). Incl. connection set ASD-06 (2 m connecting hose, two pressure port nipples, screws).

Pressure range: $\pm 500\text{ Pa}$ and $\pm 7000\text{ Pa}$ Accuracy: 500 Pa/2.0 inWC: typical $\pm 13\text{ Pa}$ at $+25^\circ\text{C}$ / $\pm 0.05\text{ inWC}$ at $+77^\circ\text{F}$ Accuracy: 7000 Pa/28 inWC: typical $\pm 105\text{ Pa}$ at $+25^\circ\text{C}$ / $\pm 0.12\text{ inWC}$ at $+77^\circ\text{F}$ Linearity: $\pm 1\%$ of final value & Temperature drift: $\pm 0.1\%$ per $^\circ\text{C}$ #
 $^\circ\text{F}$ Zero point offset: $\pm 10\%$ of measuring rangeAbove- # below-pressure: max. $\pm 50\text{ kPa}$ / $\pm 200\text{ inWC}$ Power: 24VAC ($\pm 20\%$) & $0,2\text{W}$ / 15...36VDCOperation temperature: $-30\dots+70^\circ\text{C}$ / $-22\dots+158^\circ\text{F}$ Media temperature $-20\dots+50^\circ\text{C}$ / $-4\dots+122^\circ\text{F}$

T2-IP65 plastic housing with two M16 cable glands & one M12 for temperature

Housing dimensions: 126 x 90 x 50 mm / 4.96 x 3.54 x 1.97 in

For more information, please use this link to visit the product page on Danfoss Product Store

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories

**134B9400** [🔗](#)**Pressure Sensor 7245T 2x500Pa & PT1000**DUAL AIR PRESSURE SENSOR $\pm 500\text{Pa}$ & $\pm 500\text{Pa-MB}$

Dual maintenance-free pressure sensor with connection facility for external Pt1000 sensor ($-50\dots+150^\circ\text{C}$). Microprocessor-controlled with Modbus RTU connection in a resistant IP65 plastic housing with quick-locking screws, connection nozzles for pressure hose ($\varnothing 6\text{ mm}$) and M16 cable gland for cable connection. International SI units (default) can be switched to Imperial (via Modbus). Incl. connection set ASD-06 (2 m connecting hose, two pressure port nipples, screws).

Pressure range: $\pm 500\text{ Pa}$ and $\pm 500\text{ Pa}$ Accuracy: $500\text{ Pa}/2.0\text{ inWC}$: typical $\pm 13\text{ Pa}$ at $+25^\circ\text{C}$ / $\pm 0.05\text{ inWC}$ at $+77^\circ\text{F}$ Linearity: $\pm 1\%$ of final value & Temperature drift: $\pm 0.1\%$ per $^\circ\text{C}/^\circ\text{F}$ Zero point offset: $\pm 10\%$ of measuring rangeAbove-/below-pressure: max. $\pm 50\text{ kPa}$ / $\pm 200\text{ inWC}$ Power: 24VAC ($\pm 20\%$) & 0.2W / $15\dots36\text{VDC}$ Operation temperature: $-30\dots+70^\circ\text{C}$ / $-22\dots+158^\circ\text{F}$ Media temperature $-20\dots+50^\circ\text{C}$ / $-4\dots+122^\circ\text{F}$

T2-IP65 plastic housing with two M16 cable glands & one M12 for temperature

Housing dimensions: $126 \times 90 \times 50\text{ mm}$ / $4.96 \times 3.54 \times 1.97\text{ in}$ **130B5601** [🔗](#)**VLT® DeviceNet converter MCA194 coated**VLT® DeviceNet converter MCA194 coated

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.