



134U7776

FC-280P4K0T4E20H2BXCXXXSXXXAL

Frequency converter
 FC-280P4K0T4E20H2BXCXXXSXXXAL
 VLT® Midi Drive FC-280
 4.0 kW / 5.0 HP, Three phase 380-480 VAC
 IP20 / Chassis, EMC Cat C3 (200/400V)
 Brake chopper, No display
 Coated PCB, Latest release
 Integrated PROFINET
 Frame: K2
 Other options according to Model code

Model code: FC-280P4K0T4E20H2BXCXXXSXXXAL

Note: The FC 280 does not include an LCP display or Memory Module.
 The LCP and the Memory Module can be ordered as an Accessory.
 Note: Mounting adapter plates for VLT2800 are available as an Accessory.

View Efficiency Data

PRODUCT DETAILS

Gross weight	4.52 Kilogram	
Net weight	4 Kilogram	
Volume	20.16 Liter	
EAN	5710108038281	
Product View (Switch)	GLBL	Global (Standard)
Product Group	FC-	VLT® Midi Drive FC-
Series	280	280
Power Size	P4K0	4.0 kW / 5.0 HP
Voltage	T4	Three phase 380-480 VAC
Enclosure	E20	IP20 / Chassis
RFI Filter	H2	EMC Cat C3 (200/400V)
Brake & Stop	B	Brake chopper
Display	X	No display
Coating	C	Coated PCB
Mains Option	X	No mains options
Adaptation A	X	No Adaption
Adaptation B	X	No Adaption
Special Version	SXXX	Latest release
Software Language Pack	X	Standard language pack
Control Card	AL	Integrated PROFINET
Frame Size	K2	K2
Typecode Part 1	FC-280P4K0T4E20H2BXC	
Typecode Part 2	XXXSXXXAL	
Product Catalog	NO_VIEW	NO VIEW
STAT NO	64011	
Calculated Gross Weight [kg]	3.9	
Calculated Package Weight	0.3	
Calculated Net Weight [kg]	3.6	
Intermittent Current (HO) [A]	14.4	14.4

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Product Detail | FC-280P4K0T4E20H2BXCXXXSXXXAL

PRODUCT DETAILS

Intermittent Current (HO) [A]	14.4	14.4
Continuous Current (HO) [A]	9	9
Continuous Current (HO) [A]	8.2	8.2
Power Loss HO [W]	115.5	115.5
kVA	6.2	6.2
Power 160% (HO) [KW]	4	4
Height [mm]	272.5	272.5
Width w/ no C options [mm]	90.0	90.0
Depth [mm]	168.0	168.0
Vendor	ERR01	Cannot Determine Vendor
Recommended Factory	ERR01	Cannot Determine Vendor
Modelcode01		FC-280P4K0T4E20H2BXC
Modelcode02		XXXSXXXAL
ECCN EU	Y901	Y901
ECCN US	3A999.a	3A999.a
Recommended Plant	ERR01	ERR01
Division	87	87
Product Group	D45	D45

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Accessories

**132B0262** [🔗](#)**LCP Blind cover, IP20/21**

Use the blind cover to mount on a VLT® Midi Drive FC 280 when you does not need a control panel.

**132B0254** [🔗](#)**VLT® Control Panel LCP 21, numeric**

VLT® Control Panel LCP 21 Numerical

**132B0102** [🔗](#)**LCP Remote Mounting Kit, w/ 3m cable**

Remote installation kit for VLT Micro Drive FC 51 for installing an LCP 11 or LCP

12 control unit in a control cabinet door or similar. (can also be retrofitted).

Contains fastening elements, seal and 3 m connection cable with plugs. LCP is not included in the scope of delivery.

**132B0368** [🔗](#)**VLT® 24 V DC Supply MCB 106**

VLT® 24 V DC Supply MCB 106 for FC-280

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories



132B0365 [🔗](#)

Adapter Plate, VLT2800 size C

Adapter plate, VLT2800 size C

VLT 2822 220 - 240 V, PD2

VLT 2840 200-240 volts

VLT 2855-2875 380-480 volts



132B0364 [🔗](#)

Adapter Plate, VLT2800 size B

Adapter plate, VLT2800 size B VLT 2822 200-240 volts

VLT 2822-2840 380-480 volts



132B0281 [🔗](#)

Adaptor, Graphical LCP

Graphic LCP adapter for LCP102

Image
coming
soon

132B0336 [🔗](#)

IP21 / Type 1 conversion kit, K2

IP21 / Type 1 conversion kit, K2



134B0792 [🔗](#)

VLT® Memory Module Programmer MCM 101

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.