



060G1413 [↗](#)

Pressure transmitter, MBS 3000, 0 bar - 16 bar, 0 psi - 232 psi

Pressure reference: Sealed gauge, Output signal: Current, Electrical

connection: Angular connector, Pressure connection type: G, Pressure connection

size: 1/2, Specification key: MBS 3000-2231-A1AB08-0

Product details

Characteristic	Value
Gross weight	0.208 Kilogram
Net weight	0.186 Kilogram
Volume	0.405 Liter
EAN	5702423100255
Type	MBS 3000
Product group	Sensors
Product Line	04
Product Name Description	Pressure transmitter
+ supply	Pin 1
- common	Pin 2
Accuracy, max. [±FS%]	1 %
Accuracy, typical [±FS%]	0.5 %
Ambient temperature range [°C] [max]	85 °C
Ambient temperature range [°C] [min]	-40 °C
Ambient temperature range [°F] [max]	185 °F
Ambient temperature range [°F] [min]	-40 °F
Approval	ATEX C UL US UL Recognized CE
Approval comments	ATEX Ex ec IIA T4 Gc
CE mark	Yes
China RoHS compliance	Out of scope
Compensated temp. range [°C] [max]	80 °C



Product details

Characteristic	Value
Compensated temp. range [°C] [min]	0 °C
Compensated temp. range [°F] [max]	176 °F
Compensated temp. range [°F] [min]	32 °F
Contains batteries	No
EEE category	5 small equipment (any external dimension < 50 cm)
Electrical conn. Male/Female	Male and Female
Electrical connection	Angular connector
Electrical connection size	Pg 9
Electrical connection standard	EN 175301-803-A
Enclosure rating IP	IP65
EU RoHS compliance	Yes with exemptions
EU RoHS exemption clause	6(c)
Flush diaphragm	No
High Clipping Level	22.4
Identical product	060G4152
In scope of WEEE	Yes
International Article Number	5702423100255
Intrinsically safe	No
Low Clipping level	3.6
Medium temperature range [°C] [max]	85 °C
Medium temperature range [°C] [min]	-40 °C
Medium temperature range [°F] [max]	185 °F
Medium temperature range [°F] [min]	-40 °F
Non-linearity BFSL [±FS%]	0.5 %
Other RoHS documentation	Saudi Arabia RoHS
Output signal	Current
Output signal [mA] [max]	20 mA
Output signal [mA] [min]	4 mA
Overload pressure max. [bar]	96 bar
Overload pressure max. [psi]	1392 psi
Packing format	Multi pack

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.



Product details

Characteristic	Value
Pressure connection HEX [mm]	27 mm
Pressure connection size	1/2
Pressure connection standard	EN 837
Pressure connection type	G
Pressure Male/Female	Male
Pressure range [bar] [max]	16 bar
Pressure range [bar] [min]	0 bar
Pressure range [psi] [max]	232 psi
Pressure range [psi] [min]	0 psi
Pressure reference	Sealed gauge
Pulse-snobber	No
Quantity per packing format	14 pc
REACH Candidate List substances	Lead (CAS no. 7439-92-1)
Response time max. [ms]	4 ms
SCIP dossier no.	16d2efc6-64f3-4a4e-ae98-a3fd7ce0218d
SCIP dossier product name	AKS/MBS
Specification key	MBS 3000-2231-A1AB08-0
Supply voltage [V] DC [max]	32 V
Supply voltage [V] DC [min]	9 V
UL mark	Yes

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [↗](#)

Accessories



060G0007 [↗](#)

Accessories, sensors, Electrical connector

Used for product: AKS/MBS, Parts included: Angular con. PG11 w.knife cont; Gasket, Packing format: Multi pack, Quantity per packing format: 96

For more information, please use this link to visit the product page on Danfoss Product Store [↗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.



Accessories



[060G0252](#)

Accessories, sensors, Process con. adapter

Used for product: AKS/MBS, Parts included: Pulse snubber; Adapter G 1/2, Packing format: Multi pack, Quantity per packing format: 6



[060G0008](#)

Accessories, sensors, Electrical connector

Used for product: AKS/MBS, Parts included: Gasket; Angular con. PG9 w.knife cont., Packing format: Multi pack, Quantity per packing format: 96



[060G1021](#)

Accessories, sensors, Process con. adapter

Used for product: AKS/MBS, Parts included: Adapter G1/2 fe-G1/4 ma, Packing format: Multi pack, Quantity per packing format: 120



[060G1023](#)

Accessories, sensors, Process con. adapter

Used for product: AKS/MBS, Parts included: Adapter G1/2 fe-G3/8 ma, Packing format: Multi pack, Quantity per packing format: 120

Image coming soon

[060G1024](#)

Accessories, sensors, Process con. adapter

Used for product: AKS/MBS, Parts included: Adapter G1/2 fe-1/4 Flare ma, Packing format: Multi pack, Quantity per packing format: 120



[060G1034](#)

Accessories, sensors, Cable

Used for product: AKS/MBS, Parts included: Plug w. 5,0 m cable, Packing format: Multi pack, Quantity per packing format: 8



[060G2850](#)

Accessories, sensors, Display

Used for product: MBS (4-20mA); MBT5560; MBT 3560; AKS (4-20mA), Parts included: Display, Packing format: Single pack, Quantity per packing format: 1

For more information, please use this link to visit the product page on Danfoss Product Store

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.