

## Bus terminating plug Desina Hybrid

Art.No.: 7000-33021-0000000

Weight: 0,029 kg

Country of origin: DE

Model designation: DESINA Abschlusssteckverbinder

DESINA® copper  
for ECOFast®, DESINA®

Plastic housings with good resistance against chemicals and oils.

The resistance to aggressive media should be individually tested for your application. Further details on request.

### Link to Product

#### Illustration



Product may differ from Image

#### Commercial data

ECLASS-6.0	19070403
ECLASS-6.1	19070403
ECLASS-7.0	19070403
ECLASS-8.0	19070403
ECLASS-9.0	27440190
ECLASS-10.1	27440190
ECLASS-11.1	27440190
ECLASS-12.0	27440190
ETIM-5.0	EC001855
customs tariff number	85366990
customs tariff number	85366990
EAN	4048879186766
EAN	4048879186766
Packaging unit	1
Packaging unit	1

#### Industrial communication

Data transmission rate max.	12 MBit/s
-----------------------------	-----------

#### Installation | Connection

Family construction form	DESINA® ECOFAST®
--------------------------	------------------

#### Device protection | Electrical

Degree of protection (EN IEC 60529)	IP67
Pollution Degree	2

Overvoltage category (EN 60950-1) III

**Mechanical data | Material data**

Material housing PC GF

Locking material PA

**Environmental characteristics | Climatic**

Operating temperature min. -25 °C

Operating temperature max. 50 °C

**Important installation notes**

Note on strain relief Protect the connectors by suitable measures from mechanical loads, e.g. by the usage of cable ties.

Note on bending radius **Attention:** Observe the permissible bending radii when laying cables, as the IP protection class can be endangered by excessive bending forces.