



R88M-K5K030F-S2

G5 series AC servo motor, 5 kW, 400 VAC, 3000 rpm, 15.9 Nm, Incremental encoder

Specifications

Servo control method	Analog, EtherCAT, MECHATROLINK II, Pulse train
Drive supply voltage	400 V three phase
Rated output	5 kW
Rated speed	3000 r/min
Rated torque	15.9 Nm
Peak torque	47.7 Nm
Encoder type	Incremental
Encoder resolution	20 Bit
Motor with brake	✘
Motor with oil seal	✘
Flange size square (LC)	130 mm
Shaft diameter	24 mm
Shaft with key	✔
Shaft with tap	✔
Product Weight (unpacked)	14000 g



R88D-KN50F-ECT

G5 Series servo drive,
EtherCAT type, 5 kW, 3~
400 VAC



R88D-KN50F-ML2

Accurax G5 servo drive, 3~
400 VAC, MECHATROLINK
II type, 5.0 kW



R88D-KT50F

Accurax G5 servo drive, 3~
400 VAC, analog/pulse type,
5.0 kW

Accessories



R88A-CAGD003SR-E

G5 series servo motor power cable, 3 m, w/o brake, 3-5 kW



R88A-CAGD005SR-E

G5 series servo motor power cable, 5 m, w/o brake, 3-5 kW



R88A-CAGD010SR-E

G5 series servo motor power cable, 10 m, w/o brake, 3-5 kW



R88A-CRKC001-5NR-E

G5 series servo encoder cable, 1.5 m, 200 V: 1 to 1.5 kW, 400 V: 400 W to 5 kW



R88A-CRKC003NR-E

G5 series servo encoder cable, 3 m, 200 V: 1 to 1.5 kW, 400 V: 400 W to 5 kW



R88A-CRKC005NR-E

G5 series servo encoder cable, 5 m, 200 V: 1 to 1.5 kW, 400 V: 400 W to 5 kW



R88A-CRKC010NR-E

G5 series servo encoder cable, 10 m, 200 V: 1 to 1.5 kW, 400 V: 400 W to 5 kW



R88A-CRKC015NR-E

G5 series servo encoder cable, 15 m, 200 V: 1 to 1.5 kW, 400 V: 400 W to 5 kW



R88A-CRKC020NR-E

G5 series servo encoder cable, 20 m, 200 V: 1 to 1.5 kW, 400 V: 400 W to 5 kW

CAD Library



Accurax-G5 Brochure

EN PDF 6.83 MB



G5 Instruction Sheet

EN PDF 803 KB



R88M-K Accurax G5 servo motors Datasheet

EN PDF 1 MB



Sysmac Catalogue

EN PDF 43.5 MB



Sysmac: A Fully Integrated Platform Brochure

EN PDF 12 MB



motor_sizing_tool_v1.80.1.21 Configurator

EN ZIP 37.8 MB