

CIRCUIT BREAKER 3VA1 IEC FRAME 160 BREAKING CAPACITY CLASS H ICU=70KA @ 415 V 3-POLE, MOTOR STARTER PROTECTION TM120M, AM, IN=125A WITHOUT OVERLOAD PROTECTION SHORT CIRCUIT PROTECTION II=5...15 X IN BUSBAR CONNECTION 1 AUXILIARY SWITCH HQ 1 TRIP ALARM SWITCH HQ



| Model  |   |
|--|---|
| product brandname  | SENTRON                                     |
| Product designation  | Molded case circuit breaker                 |
| Design of the product  | Starter protection                          |
| Design of the overcurrent release  | TM120M                                      |
| Protective function of the overcurrent release   | I   |
| Number of poles  | 3   |
| Design of the auxiliary release  | without auxiliary release                   |
| Design of the auxiliary switch   | 1 auxiliary switch + 1 trip alarm switch HQ |
| General technical data   |   |
| Tension assignée d'isolement Ui  | 800 V                                       |
| Max. rated operational voltage Ue with AC 50/60Hz  | 690 V                                       |
| Max. rated operational voltage Ue with DC  | 500 V                                       |
| Operating power / at AC-3 / at 400 V   | 0 W   |
| Operating power / at AC-3 / at 230 V   | 0 W   |
| Active power loss / for rated value of the current / at AC / in hot operating state / per device | 23.2 W                                      |
| Mechanical service life (switching cycles) / typical   | 15 000                                      |

|   |         |
|---|---------|
| Electrical endurance (switching cycles) / at AC-1 / at 380/415 V 50/60 Hz | 8 000   |
| Neutral conductors / upgradeable/retrofitable                             | No      |
| Ground fault monitoring version   | Without |
| Product function  |         |
| • communication function  | No      |
| • Phase failure detection   | No      |
| • other measurement function  | No      |
| Net weight  | 0.96 kg |

### Electricity

|   |       |
|---|-------|
| Max. rated operational voltage of the size of the circuit-breaker | 160 A |
| Courant permanent assigné Iu                                      | 125 A |
| Operating current   |       |
| • at 40 °C  | 125 A |
| • at 45 °C  | 125 A |
| • at 50 °C  | 125 A |
| • at 55 °C  | 122 A |
| • at 60 °C  | 120 A |
| • at 65 °C  | 117 A |
| • at 70 °C  | 114 A |

### Switching capacity according to IEC 60947

|   |         |
|---|---------|
| Switching capacity class of the circuit breaker           | H       |
| Maximum short-circuit current breaking capacity (Icu)     |         |
| • at 240 V  | 100 kA  |
| • at 415 V  | 70 kA   |
| • at 440 V  | 36 kA   |
| • at 690 V  | 5 kA    |
| Operational short-circuit current breaking capacity (Ics) |         |
| • at 240 V  | 100 kA  |
| • at 415 V  | 70 kA   |
| • at 440 V  | 36 kA   |
| • at 690 V  | 5 kA    |
| Short-circuit current making capacity (Icm)               |         |
| • at 240 V  | 220 kA  |
| • at 415 V  | 154 kA  |
| • at 440 V  | 75.6 kA |
| • at 690 V  | 8.5 kA  |

### Adjustable parameters

|   |     |
|---|-----|
| Adjustable response value current / I <sub>g</sub> min. | 0 A |
|---|-----|

|   |     |
|---|-----|
| Adjustable response value current / Ig min. | 0 A |
| Adjustable response value current / Ig min. | 0 A |
| Adjustable response value current / Ig min. | 0 A |
| Adjustable response value current / Ii min. | 0 A |
| Adjustable response value current / Ii max. | 0 A |

### Mechanical Design

|        |         |
|--------|---------|
| Height | 130 mm  |
| Width  | 76.2 mm |
| Depth  | 70 mm   |

### Connections

|   |                |
|---|----------------|
| Arrangement of electrical connectors / for main current circuit                         | Front terminal |
| Type of electrical connection / for main current circuit                                | lug terminal   |
| Type of connectable conductor cross-section, connection screw, width x thickness , min. | 12 x 1         |
| Type of connectable conductor cross-section, connection screw, width x thickness , max. | 17 x 6.5       |

### Auxiliary circuit

|   |     |
|---|-----|
| Product component   |     |
| <ul style="list-style-type: none"> <li>• undervoltage release</li> </ul>                      | No  |
| <ul style="list-style-type: none"> <li>• Voltage trigger</li> </ul>                           | No  |
| <ul style="list-style-type: none"> <li>• undervoltage release with leading contact</li> </ul> | No  |
| <ul style="list-style-type: none"> <li>• Trip indicator</li> </ul>                            | Yes |
| Number of CO contacts / for auxiliary contacts  | 2   |

### Accessories

|   |                                    |
|---|------------------------------------|
| Product extension / optional / motor drive  | Yes                                |
| Manufacturer's article number   |                                    |
| <ul style="list-style-type: none"> <li>• of the supplied basic switch</li> </ul>                    | <a href="#">3VA1112-6MH32-0AA0</a> |
| <ul style="list-style-type: none"> <li>• of the integrated auxiliary switch/alarm switch</li> </ul> | <a href="#">3VA9988-0AA12</a>      |
| <ul style="list-style-type: none"> <li>• of the integrated auxiliary switch/alarm switch</li> </ul> | <a href="#">3VA9988-0AB12</a>      |
| <ul style="list-style-type: none"> <li>• of the integrated auxiliary trip</li> </ul>                | <a href="#">3VA9608-0BB25</a>      |

### Environmental conditions

|  |        |
|--|--------|
| Protection class IP / on the front   | IP40   |
| Ambient temperature  |        |
| <ul style="list-style-type: none"> <li>• during operation / minimum</li> </ul> | -25 °C |
| <ul style="list-style-type: none"> <li>• during operation / maximum</li> </ul> | 70 °C  |
| <ul style="list-style-type: none"> <li>• during storage / minimum</li> </ul>   | -40 °C |
| <ul style="list-style-type: none"> <li>• during storage / maximum</li> </ul>   | 80 °C  |

### Certificates

|  |   |
|--|---|
| Equipment marking / acc. to DIN EN 81346-2 | Q |
|--|---|

| General Product Approval | EMC | Declaration of Conformity | Test Certificates |
|--------------------------|-----|---------------------------|-------------------|
|--------------------------|-----|---------------------------|-------------------|



CCC



VDE



RCM



EG-Konf.

[sonstig](#)

**other**

[Bestätigungen](#)

[sonstig](#)

**Further information**

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3VA1112-6MH32-0AF0>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<http://support.automation.siemens.com/WW/view/en/3VA1112-6MH32-0AF0/all>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**


[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3VA1112-6MH32-0AF0](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA1112-6MH32-0AF0)


**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://www.siemens.com/specifications>





last modified:

10/24/2016