



Main

Range	Acti 9
Product or component type	Earth leakage add-on block
Device short name	Vigi iC60
Range compatibility	Acti 9 Reflex iC60 Acti 9 iC60
Poles description	3P
[In] rated current	25 A
Earth-leakage sensitivity	500 mA
Earth-leakage protection time delay	Instantaneous
Earth leakage protection type	Class A
Network type	AC
Network frequency	50/60 Hz
[Ue] rated operational voltage	400/415 V AC 50/60 Hz conforming to IEC 61009-1 400 V AC 50/60 Hz conforming to EN 61009-1
Standards	EN 61009-1 IEC 61009-1
9 mm pitches	6

Complementary

Device location in system	Outgoer
Overvoltage protection	Without
Residual current tripping technology	Voltage independent
[Ui] rated insulation voltage	500 V AC 50/60 Hz conforming to IEC 60947-2
[Uimp] rated impulse withstand voltage	6 kV conforming to IEC 60947-2
Local signalling	Trip indicator
Mounting mode	Clip-on
Mounting support	DIN rail
Electrical connection to mcb	Plug in
Comb busbar distribution block compatibility	Bottom: YES
Height	91 mm
Width	54 mm
Depth	73.5 mm
Product weight	0.21 kg
Colour	White
Connections - terminals	Tunnel type terminal downside 1 cable(s) 1...16 mm ² flexible with cable end Tunnel type terminal downside 1 cable(s) 1...16 mm ² flexible without cable end Tunnel type terminal downside 1 cable(s) 1...25 mm ² rigid without cable end
Wire stripping length	14 mm (bottom)
Tightening torque	2 N.m (bottom)
Product compatibility	Single terminal

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

IP degree of protection	IP20
Pollution degree	3 conforming to IEC 60947-2
Electromagnetic compatibility	8/20 μ s impulse withstand 250 A conforming to IEC 61009-1
Ambient air temperature for operation	-25...60 °C
Ambient air temperature for storage	-40...85 °C

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1201 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations