



Main

| | |
|-------------------------------------|---|
| Range | Acti 9 |
| Product or component type | Earth leakage add-on block |
| Device short name | Vigi iC60 |
| Range compatibility | Acti 9 Reflex iC60 Acti 9 iC60 |
| Poles description | 3P |
| [In] rated current | 25 A |
| Earth-leakage sensitivity | 30 mA |
| Earth-leakage protection time delay | Instantaneous |
| Earth leakage protection type | Class SI |
| Network type | AC |
| Network frequency | 50/60 Hz |
| [Ue] rated operational voltage | 400/415 V AC 50/60 Hz conforming to IEC 61009-1 400 V AC 50/60 Hz conforming to EN 61009-1 |
| Standards | EN 61009-1 IEC 61009-1 |
| 9 mm pitches | 6 |

Complementary

| | |
|--|--|
| Device location in system | Outgoer |
| Overvoltage protection | Without |
| Residual current tripping technology | Voltage independent |
| [Ui] rated insulation voltage | 500 V AC 50/60 Hz conforming to IEC 60947-2 |
| [Uimp] rated impulse withstand voltage | 6 kV conforming to IEC 60947-2 |
| Local signalling | Trip indicator |
| Mounting mode | Clip-on |
| Mounting support | DIN rail |
| Electrical connection to mcb | Plug in |
| Comb busbar distribution block compatibility | Bottom: YES |
| Height | 91 mm |
| Width | 54 mm |
| Depth | 73.5 mm |
| Product weight | 0.21 kg |
| Colour | White |
| Connections - terminals | Tunnel type terminal downside 1 cable(s) 1...16 mm ² flexible with cable end Tunnel type terminal downside 1 cable(s) 1...16 mm ² flexible without cable end Tunnel type terminal downside 1 cable(s) 1...25 mm ² rigid without cable end |
| Wire stripping length | 14 mm (bottom) |
| Tightening torque | 2 N.m (bottom) |
| Product compatibility | Single terminal |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

| | |
|---------------------------------------|---|
| IP degree of protection | IP20 |
| Pollution degree | 3 conforming to IEC 60947-2 |
| Electromagnetic compatibility | 8/20 μ s impulse withstand 3000 A conforming to IEC 61009-1 |
| Ambient air temperature for operation | -25...60 °C |
| Ambient air temperature for storage | -40...85 °C |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 1201 - Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold |
| Product environmental profile | Available |
| Product end of life instructions | Need no specific recycling operations |