



### Main

Relay application	Remote control
Range of product	C120 C60
Device short name	ATm
Signal contacts composition	1 NO
Number of feeders controlled	1

### Complementary

Reset	Non differential general electric fault
Control type	Automatic
Local signalling	Indicator light
Type of setting	Maximal duration Number of permissible reclosures On/Off Time before automatic reclosure
Signalling circuit voltage	AC: 230 V 50/60 Hz
Signalling output current	2 A
[Us] rated supply voltage	230 V AC 50/60 Hz
Supply maximum power	14 VA
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
Height	81 mm
Width	18 mm
Depth	66 mm
Product weight	0.066 kg
Auxiliary connection terminal	Tunnel type terminal 2 pin(s) rigid 2.5 mm <sup>2</sup> Tunnel type terminal 2 pin(s) flexible 1.5 mm <sup>2</sup>

### Environment

Standards	EN 60669-2 EN 60947-1
IP degree of protection	IP50 conforming to EN 60947-1 IP50 conforming to EN 60669-2
Electrical shock protection class	Class II
Tropicalisation	2 conforming to EN 60947-1 2 conforming to EN 60669-2
Relative humidity	95 % ( 55 °C )
Operating altitude	2000 m
Ambient air temperature for operation	-5...55 °C
Ambient air temperature for storage	-40...70 °C

### Contractual warranty

Period	18 months
--------	-----------