



Main

Range	Acti 9
Product or component type	Earth leakage add-on block
Device short name	Vigi iC65
Range compatibility	Acti 9 Reflex iC60 Acti 9 iC60
Poles description	2P
[In] rated current	63 A
Earth-leakage sensitivity	100 mA
Earth-leakage protection time delay	Selective
Earth leakage protection type	Class AC
Network type	AC
Network frequency	50/60 Hz
[Ue] rated operational voltage	400 V AC 50/60 Hz conforming to GB 16917.22
Standards	GB 16917.22
9 mm pitches	4

Complementary

Device location in system	Outgoer
Overvoltage protection	Without
Residual current tripping technology	Voltage dependent
Local signalling	Trip indicator
Mounting mode	Clip-on
Mounting support	DIN rail
Electrical connection to mcb	By screws
Height	91 mm
Width	72 mm
Depth	73.5 mm
Colour	White
Connections - terminals	Tunnel type terminal downside
Product compatibility	Single terminal

Environment

IP degree of protection	IP20
-------------------------	------

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1111 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available Download End Of Life Manual

Contractual warranty

Warranty period	18 months
-----------------	-----------
