



Main

Range	Acti 9
Product or component type	Earth leakage add-on block
Device short name	Vigi iPN
Poles description	1P + N
Neutral position	Left
[In] rated current	25 A
Earth-leakage sensitivity	30 mA
Earth-leakage protection time delay	Instantaneous
Earth leakage protection type	Class AC
Network type	AC
Network frequency	50/60 Hz
[Ue] rated operational voltage	230 V AC 50/60 Hz conforming to GB 16917.22
Standards	GB 16917.22
9 mm pitches	2

Complementary

Device location in system	Outgoer
Overvoltage protection	With 280 V
Residual current tripping technology	Voltage dependent
Local signalling	Trip indicator
Mounting mode	Clip-on
Mounting support	DIN rail
Electrical connection to mcb	By screws
Width	36 mm
Colour	White
Connections - terminals	Tunnel type terminal downside

Environment

IP degree of protection	IP20
-------------------------	------

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1111 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available

Contractual warranty

Warranty period	18 months
-----------------	-----------