



Main

| | |
|---------------------------------------|---|
| Range of product | AS-Interface |
| Accessory / separate part category | Connection accessories |
| Accessory / separate part type | Repeater |
| Accessory / separate part designation | Repeater |
| Accessory / separate part destination | AS-Interface line |
| Supply | Via AS-I cable |
| [Ue] rated operational voltage | 18.5...31.6 V |
| Status LED | 1 LED per segment red for communication fault 1 LED per segment green for power ON |
| Additional information | Galvanic isolation between the segments |

Complementary

| | |
|-----------------------|---------|
| Electrical connection | IDC |
| Material | Plastic |
| Current consumption | 120 mA |
| Product weight | 0.19 kg |

Environment

| | |
|---------------------------------------|-------------|
| Ambient air temperature for operation | -10...55 °C |
| Ambient air temperature for storage | -25...75 °C |
| IP degree of protection | IP65 |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.