

SITOP PSU8200 24 V/10 A  
 SITOP PSU8200 24 V/10 A STABILIZED POWER SUPPLY INPUT:  
 120/230 V AC OUTPUT: 24 V/10 A DC



Input	
Input	1-phase AC
Supply voltage	
<ul style="list-style-type: none"> <li>• 1 at AC Rated value</li> <li>• 2 at AC Rated value</li> <li>• Note</li> </ul>	120 V 230 V Automatic range selection
Input voltage	
<ul style="list-style-type: none"> <li>• 1 at AC</li> <li>• 2 at AC</li> </ul>	85 ... 132 V 170 ... 264 V
Wide-range input	No
Mains buffering at I <sub>out</sub> rated, min.	35 ms; at V <sub>in</sub> = 120/230 V
Rated line frequency 1	50 Hz
Rated line frequency 2	60 Hz
Rated line range	47 ... 63 Hz
Input current	
<ul style="list-style-type: none"> <li>• at rated input voltage 120 V</li> <li>• at rated input voltage 230 V</li> </ul>	4 A 1.9 A
Switch-on current limiting (+25 °C), max.	10 A
I <sup>2</sup> t, max.	0.3 A <sup>2</sup> ·s

Built-in incoming fuse	T 6.3 A (not accessible)
Protection in the mains power input (IEC 898)	Recommended miniature circuit breaker at 1-phase operation: from 6 A (10 A) characteristic C (B); required at 2-phase operation: circuit breaker 2-pole connected or circuit breaker 3RV2011-1EA10 (setting 3.8 A) or 3RV2711-1ED10 (UL 489) at 230 V; 3RV2011-1DA10 (setting 3 A) or 3RV2711-1DD10 (UL 489) at 400/500 V

## Output

Output	Controlled, isolated DC voltage
Rated voltage $V_{out}$ DC	24 V
Total tolerance, static $\pm$	3 %
Static mains compensation, approx.	0.1 %
Static load balancing, approx.	0.3 %
Residual ripple peak-peak, max.	50 mV
Spikes peak-peak, max. (bandwidth: 20 MHz)	200 mV
Adjustment range	24 ... 28.8 V
Product function Output voltage adjustable	Yes
Output voltage setting	via potentiometer; max. 240 W
Status display	Green LED for 24 V OK
Signaling	Relay contact (NO contact, rating 60 V DC/ 0.3 A) for "24 V OK"
On/off behavior	Overshoot of $V_{out}$ approx. 3 %
Startup delay, max.	1 s
Voltage rise, typ.	70 ms
Rated current value $I_{out}$ rated	10 A
Current range	0 ... 10 A
• Note	+60 ... +70 °C: Derating 2%/K; as of $U_a > 24$ V: 4% $[I_a]/V [U_a]$ ; at $U_e < 100$ V/ $< 200$ V: 80% $I_a$ rated
Supplied active power typical	240 W
Short-term overload current	
• at short-circuit during operation typical	30 A
Duration of overloading capability for excess current	
• at short-circuit during operation	25 ms
Constant overload current	
• on short-circuiting during the start-up typical	12 A
Parallel switching for enhanced performance	Yes; switchable characteristic
Numbers of parallel switchable units for enhanced performance	2

## Efficiency

Efficiency at $V_{out}$ rated, $I_{out}$ rated, approx.	94 %
Power loss at $V_{out}$ rated, $I_{out}$ rated, approx.	18 W
Power loss [W] during no-load operation maximum	1.5 W

## Closed-loop control

Dynamic mains compensation ( $V_{in}$ rated $\pm 15\%$ ), max.	0.1 %
Dynamic load smoothing (I <sub>out</sub> : 50/100/50 %), U <sub>out</sub> $\pm$ typ.	4 %
Load step setting time 50 to 100%, typ.	0.25 ms
Load step setting time 100 to 50%, typ.	0.5 ms
Dynamic load smoothing (I <sub>out</sub> : 10/90/10 %), U <sub>out</sub> $\pm$ typ.	4 %
Load step setting time 10 to 90%, typ.	0.25 ms
Load step setting time 90 to 10%, typ.	0.5 ms
Setting time maximum	1 ms

### Protection and monitoring

Output overvoltage protection	< 33 V
Current limitation, typ.	12 A
Property of the output Short-circuit proof	Yes
Short-circuit protection	Alternatively, constant current characteristic approx. 12 A or latching shutdown
Enduring short circuit current RMS value <ul style="list-style-type: none"> <li>• typical</li> </ul>	12 A
Overcurrent overload capability in normal operation	overload capability 150 % I <sub>out</sub> rated up to 5 s/min
Overload/short-circuit indicator	LED yellow for "overload", LED red for "latching shutdown"

### Safety

Primary/secondary isolation	Yes
Galvanic isolation	Safety extra-low output voltage U <sub>out</sub> acc. to EN 60950-1 and EN 50178
Protection class	Class I
Leakage current <ul style="list-style-type: none"> <li>• maximum</li> <li>• typical</li> </ul>	3.5 mA 1 mA
CE mark	Yes
UL/cUL (CSA) approval	cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259, cCSAus (CSA C22.2 No. 60950-1, UL 60950-1, UL 1604)
Explosion protection	IECEX Ex nA nC IIC T4 Gc; ATEX (EX) II 3G Ex nA nC IIC T4 Gc; cCSAus (CSA C22.2 No. 213, ANSI/ISA-12.12.01) Class I, Div. 2, Group ABCD, T3
FM approval	-
CB approval	Yes
Marine approval	GL, ABS
Degree of protection (EN 60529)	IP20

### EMC

Emitted interference	EN 55022 Class B
Supply harmonics limitation	EN 61000-3-2
Noise immunity	EN 61000-6-2

Operating data	
Ambient temperature	
<ul style="list-style-type: none"> <li>during operation</li> <li>during transport</li> <li>during storage</li> </ul>	<p>-25 ... +70 °C</p> <p>-40 ... +85 °C</p> <p>-40 ... +85 °C</p>
Humidity class according to EN 60721	Climate class 3K3, no condensation

Mechanics	
Connection technology	screw-type terminals
Connections	
<ul style="list-style-type: none"> <li>Supply input</li> <li>Output</li> <li>Auxiliary</li> </ul>	<p>L, N, PE: 1 screw terminal each for 0.2 ... 2.5 mm<sup>2</sup> single-core/finely stranded</p> <p>+, -: 2 screw terminals each for 0.2 ... 2.5 mm<sup>2</sup></p> <p>13, 14 (alarm signal): 1 screw terminal each for 0.14 ... 1.5 mm<sup>2</sup>;</p> <p>15, 16 (Remote): 1 screw terminal each for 0.14 ... 1.5 mm<sup>2</sup></p>
Width of the enclosure	55 mm
Height of the enclosure	125 mm
Depth of the enclosure	125 mm
Required spacing	
<ul style="list-style-type: none"> <li>top</li> <li>bottom</li> <li>left</li> <li>right</li> </ul>	<p>50 mm</p> <p>50 mm</p> <p>0 mm</p> <p>0 mm</p>
Weight, approx.	1 kg
Product feature of the enclosure housing for side-by-side mounting	Yes
Installation	Snaps onto DIN rail EN 60715 35x7.5/15
Electrical accessories	Buffer module
MTBF at 40 °C	1 292 102 h
Other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)