

SITOP PSU8200 24 V/20 A
 SITOP PSU8200 24 V/20 A STABILIZED POWER SUPPLY INPUT:
 3 400-500 V AC OUTPUT: 24 V/20 A DC



| Input | |
|---|---|
| Input | 3-phase AC |
| Rated voltage value V_{in} rated | 400 ... 500 V |
| Voltage range AC | 320 ... 575 V |
| Wide-range input | Yes |
| Mains buffering at I_{out} rated, min. | 15 ms; at $V_{in} = 400$ V |
| Rated line frequency 1 | 50 Hz |
| Rated line frequency 2 | 60 Hz |
| Rated line range | 47 ... 63 Hz |
| Input current | |
| • at rated input voltage 400 V | 1.2 A |
| • at rated input voltage 500 V | 1 A |
| Switch-on current limiting (+25 °C), max. | 16 A |
| I^2t , max. | 0.8 A ² ·s |
| Built-in incoming fuse | none |
| Protection in the mains power input (IEC 898) | Required: 3-pole connected miniature circuit breaker 6 ... 16 A characteristic C or circuit breaker 3RV2011-1DA10 (setting 3 A) or 3RV2711-1DD10 (UL 489) |

Output

| | |
|---|---|
| Output | Controlled, isolated DC voltage |
| Rated voltage V_{out} DC | 24 V |
| Total tolerance, static \pm | 3 % |
| Static mains compensation, approx. | 0.1 % |
| Static load balancing, approx. | 0.2 % |
| Residual ripple peak-peak, max. | 100 mV |
| Spikes peak-peak, max. (bandwidth: 20 MHz) | 200 mV |
| Adjustment range | 24 ... 28 V |
| Product function Output voltage adjustable | Yes |
| Output voltage setting | via potentiometer; max. 480 W |
| Status display | Green LED for 24 V OK |
| Signaling | Relay contact (NO contact, rating 60 V DC/ 0.3 A) for "24 V OK" |
| On/off behavior | No overshoot of V_{out} (soft start) |
| Startup delay, max. | 2.5 s |
| Voltage increase time of the output voltage maximum | 500 ms |
| Rated current value I_{out} rated | 20 A |
| Current range | 0 ... 20 A |
| • Note | +60 ... +70 °C: Derating 2%/K |
| Supplied active power typical | 480 W |
| Short-term overload current | |
| • at short-circuit during operation typical | 60 A |
| Duration of overloading capability for excess current | |
| • at short-circuit during operation | 25 ms |
| Constant overload current | |
| • on short-circuiting during the start-up typical | 22 A |
| Parallel switching for enhanced performance | Yes; switchable characteristic |
| Numbers of parallel switchable units for enhanced performance | 2 |

Efficiency

| | |
|---|------|
| Efficiency at V_{out} rated, I_{out} rated, approx. | 94 % |
| Power loss at V_{out} rated, I_{out} rated, approx. | 31 W |

Closed-loop control

| | |
|---|--------|
| Dynamic mains compensation (V_{in} rated ± 15 %), max. | 0.1 % |
| Dynamic load smoothing (I_{out} : 50/100/50 %), $U_{out} \pm$ typ. | 1 % |
| Load step setting time 50 to 100%, typ. | 0.2 ms |
| Load step setting time 100 to 50%, typ. | 0.2 ms |
| Dynamic load smoothing (I_{out} : 10/90/10 %), $U_{out} \pm$ typ. | 2 % |
| Load step setting time 10 to 90%, typ. | 0.2 ms |
| Load step setting time 90 to 10%, typ. | 0.2 ms |
| Setting time maximum | 10 ms |

| Protection and monitoring | |
|---|--|
| Output overvoltage protection | < 32 V |
| Current limitation, typ. | 22 A |
| Property of the output Short-circuit proof | Yes |
| Short-circuit protection | Alternatively, constant current characteristic approx. 22 A or latching shutdown |
| Enduring short circuit current RMS value | |
| • typical | 22 A |
| Overcurrent overload capability in normal operation | overload capability 150 % I _{out} rated up to 5 s/min |
| Overload/short-circuit indicator | LED yellow for "overload", LED red for "latching shutdown" |

| Safety | |
|---------------------------------|---|
| Primary/secondary isolation | Yes |
| Galvanic isolation | Safety extra low output voltage V _{out} according to EN 60950-1 |
| Protection class | Class I |
| Leakage current | |
| • maximum | 3.5 mA |
| • typical | 0.9 mA |
| CE mark | Yes |
| UL/cUL (CSA) approval | cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259 |
| Explosion protection | IECEx Ex nA nC IIC T4 Gc; ATEX (EX) II 3G Ex nA nC IIC T4 Gc; cCSAus (CSA C22.2 No. 213, ANSI/ISA-12.12.01) Class I, Div. 2, Group ABCD, T4 |
| FM approval | - |
| CB approval | Yes |
| Marine approval | GL, ABS |
| Degree of protection (EN 60529) | IP20 |

| EMC | |
|-----------------------------|------------------|
| Emitted interference | EN 55022 Class B |
| Supply harmonics limitation | EN 61000-3-2 |
| Noise immunity | EN 61000-6-2 |

| Operating data | |
|--------------------------------------|------------------------------------|
| Ambient temperature | |
| • during operation | -25 ... +70 °C |
| • during transport | -40 ... +85 °C |
| • during storage | -40 ... +85 °C |
| Humidity class according to EN 60721 | Climate class 3K3, no condensation |

| Mechanics | |
|-----------------------|---|
| Connection technology | screw-type terminals |
| Connections | |
| • Supply input | L1, L2, L3, PE: 1 screw terminal each for 0.2 ... 4 mm ² single-core/finely stranded |
| • Output | +, -: 2 screw terminals each for 0.2 ... 4 mm ² |

| | |
|--|--|
| <ul style="list-style-type: none"> • Auxiliary | 13, 14 (alarm signal): 1 screw terminal each for 0.14 ... 1.5 mm ² ; 15, 16 (Remote): 1 screw terminal each for 0.14 ... 1.5 mm ² |
| Width of the enclosure | 70 mm |
| Height of the enclosure | 125 mm |
| Depth of the enclosure | 125 mm |
| Required spacing | |
| <ul style="list-style-type: none"> • top | 50 mm |
| <ul style="list-style-type: none"> • bottom | 50 mm |
| <ul style="list-style-type: none"> • left | 0 mm |
| <ul style="list-style-type: none"> • right | 0 mm |
| Weight, approx. | 1.2 kg |
| Product feature of the enclosure housing for side-by-side mounting | Yes |
| Installation | Snaps onto DIN rail EN 60715 35x7.5/15 |
| Electrical accessories | Buffer module |
| Mechanical accessories | Device identification label 20 mm × 7 mm, pale turquoise 3RT1900-1SB20 |
| MTBF at 40 °C | 590 573 h |
| Other information | Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified) |