


OPU209



Optical fork sensor

OPU-FNKG/AS



- 1 potentiometer sensitivity
- 2 output function switch



Electrical data

Operating voltage	[V]	10...35 DC
Current consumption	[mA]	< 30
Protection class		III
Reverse polarity protection		yes
Type of light		red light
Wave length	[nm]	660

Outputs

Electrical design		NPN
Output function		light-on/dark-on mode; (selectable)
Max. voltage drop switching output DC	[V]	2.8
Permanent current rating of switching output DC	[mA]	200
Switching frequency DC	[Hz]	4000
Short-circuit protection		yes
Type of short-circuit protection		pulsed
Overload protection		yes

Detection zone

Diameter of the smallest detectable object	[mm]	0.5
--	------	-----

Operating conditions

Ambient temperature	[°C]	-25...60
Protection		IP 67

OPU209



Optical fork sensor

OPU-FNKG/AS

Tests / approvals

EMC		EN 60947-5-2	
MTTF	[years]		572

Mechanical data

Weight	[g]		103
Dimensions	[mm]		70 x 10 x 80
Fork depth D	[mm]		55
Fork width W	[mm]		50
Materials		housing: diecast zinc black anodised; lens: glass	

Displays / operating elements

Display		switching status	1 x LED, yellow
---------	--	------------------	-----------------

Remarks

Pack quantity			1 pcs.
---------------	--	--	--------

Electrical connection

Connector: 1 x M8



Connection

