


Fibre optic diffuse reflection sensor

FT-11-EPA-M4/F2X0,5/2M



Application

Function principle	Diffuse reflection sensor
--------------------	---------------------------

Detection zone

Range with fibre optic amplifier type	OB50; OBF; OO50
---------------------------------------	-----------------

OB50

Range fibre optics [mm]	20
-------------------------	----

OBF

Range fibre optics [mm]	25
-------------------------	----

OO50

Range fibre optics [mm]	60
-------------------------	----

Operating conditions

Ambient temperature [°C]	-40...70
--------------------------	----------

E20639



Fibre optic diffuse reflection sensor

FT-11-EPA-M4/F2X0,5/2M

Mechanical data	
Weight [g]	33.4
Version of sensing head	straight
Sensing head thread	M4
Total length [mm]	2000
Min. bending radius [mm]	10
Fibre arrangement	⊙
Core diameter [mm]	2 x 0.5
Fibre material	PMMA
Fibre head material	aluminium
Fibre sheath material	PE
Accessories	
Accessories (supplied)	hexagon nuts: 2 x M4 tooth lock washers: 2 knurled nut: 1 x M11
Accessories (optional)	Cutter for fibre optics, E20600
Remarks	
Pack quantity	1 pcs.