


EVC470



Connecting cable with plug

ASTGF040MSS0010H04



Application

Free from silicone yes

Electrical data

Operating voltage [V] < 50 AC / < 60 DC

Protection class III

Max. current load total [A] 3

Operating conditions

Ambient temperature [°C] -25...90

Note on ambient temperature cULus: ...80

Ambient temperature (moving) [°C] -25...90

Note on ambient temperature (moving) cULus: ...80

Protection IP 65; IP 67; IP 68; IP 69K

Mechanical data

Weight [g] 213.8

Dimensions [mm] 10 x 10 x 36

Materials housing: TPU orange

Material nut brass

	bending radius for flexible use	min. 10 x cable diameter
Drag chain suitability	travel speed	max. 3.3 m/s for a horizontal travel length of 5 m and max. acceleration of 5 m/s ²
	bending cycles	> 5 Mio.
	torsional strain	± 180 °/m

Drag chain suitability yes

EVC470



Connecting cable with plug

ASTGF040MSS0010H04

Remarks

Pack quantity 1 pcs.

Electrical connection


Cable: 10 m, PUR, Halogen-free, black, Ø 3.7 mm; 4 x 0.25 mm²

Electrical connection - plug

Connector: 1 x M8, straight; Locking: brass, nickel-plated; Contacts: gold-plated; Tightening torque: 0.3...0.5 Nm



Connection



Core colours :

BK = black
BN = brown
BU = blue
WH = white