

C5210-0030 | 19-inch slide-in Industrial PC

Variants	Processor	available
C5210-0030	Intel® Celeron®, 2 Cores (TC3: 50*) or Intel® Pentium®, 2 Cores (TC3: 50*) or Intel® Core™ i3, 2 Cores (TC3: 60*) or Intel® Core™ i5, 4 Cores (TC3: 70*) or Intel® Core™ i7, 4 Cores (TC3: 80*) (6th/7th generation)	yes
C5210-0020	Intel® Celeron®, 2 Cores (TC3: 50*) or Intel® Core™ i3, 2 Cores (TC3: 60*) or Intel® Core™ i5, 2 Cores (TC3: 70*) or Intel® Core™ i7, 4 Cores (TC3: 80*) (4th generation)	yes
C5210-0010	Intel® Celeron®, 2 Cores (TC3: 50*) or Intel® Core™ i3, 2 Cores (TC3: 60*) or Intel® Core™ i5, 2 Cores (TC3: 70*) or Intel® Core™ i7, 4 Cores (TC3: 80*)	No longer available

*The TwinCAT 3 performance class defines the exact ordering number for the respective TwinCAT 3 product. Please see [here](#) for an overview of the TC3 performance classes.

C5210-0030	19-inch slide-in Industrial PC
Housing	slide-in housing for 19-inch racks, 1 rack unit all drives accessible from the front 2 removable frames for hard disks 1 DVD drive slot, 2 USB sockets, reset key and ATX key behind a lockable front flap status LEDs all connectors at the rear side 2 PCIe module slots to plug-in Beckhoff PCIe modules or to lead out interfaces of the motherboard ex factory protection class IP 20 operating temperature 0...55 °C dimensions (W x H x D) 482.7 x 44 x 493.8 mm (19" x 1.7" x 19.44") depth behind the front 471.3 mm (18.56")
Features	processor Intel® Celeron® G3900TE 2.3 GHz, 2 cores (TC3: 50) 3½-inch motherboard for 6th and 7th Generation Intel® Core™ i3, Core™ i5, Core™ i7, Celeron® or Pentium® 4 GB DDR4 RAM, expandable to 32 GB, with a 32 bit operating system only 3 GB are addressable. graphic adapter integrated inside the Intel® processor, 1 DVI-D connector on-board dual Ethernet adapter with 2 x 100/1000BASE-T connector on-board SATA RAID 1 controller, Intel® Rapid Storage Technology hard disk, 3½-inch, 1 TB 1 serial port and 4 USB 3.0 ports at the rear side, 2 USB 2.0 ports behind the front flap 100...240 V AC full range power supply

Options	C5210-0030
C9900-C607	processor 6th Generation Intel® Pentium® G4400TE, 2.4 GHz, 2 cores (TC3: 50), instead of Intel® Celeron® G3900TE 2.3 GHz (TC3: 50)
C9900-C608	processor 6th Generation Intel® Core™ i3-6100TE, 2.7 GHz, 2 cores (TC3: 60), instead of Intel® Celeron® G3900TE 2.3 GHz (TC3: 50)
C9900-C618	processor 7th Generation Intel® Core™ i3-7101(T)E, 3.4 GHz, 2 cores (TC3: 60), requires Windows 10, 64 bit, instead of Intel® Celeron® G3900TE 2.3 GHz (TC3: 50)
C9900-C609	processor 6th Generation Intel® Core™ i5-6500TE, 2.3 GHz, 4 cores (TC3: 70), instead of Intel® Celeron® G3900TE 2.3 GHz (TC3: 50)
C9900-C619	processor 7th Generation Intel® Core™ i5-7500(T), 2.7 GHz, 4 cores (TC3: 70), requires Windows 10b 64 bit, instead of Intel® Celeron® G3900TE 2.3 GHz (TC3: 50)
C9900-C610	processor 6th Generation Intel® Core™ i7-6700TE, 2.4 GHz, 4 cores (TC3: 80), instead of Intel® Celeron® G3900TE 2.3 GHz (TC3: 50)
C9900-C620	processor 7th Generation Intel® Core™ i7-7700(T), 2.9 GHz, 4 cores (TC3: 80), requires Windows 10, 64 bit, instead of Intel® Celeron® G3900TE 2.3 GHz (TC3: 50)
C9900-R270	memory extension to 8 GB DDR4 RAM, instead of 4 GB, requires a 64 bit operating system
C9900-R271	memory extension to 16 GB DDR4 RAM, instead of 4 GB, requires a 64 bit operating system
C9900-R272	memory extension to 32 GB DDR4 RAM, instead of 4 GB, requires a 64 bit operating system
FC9062	Gigabit Ethernet PCIe module for PCs with Beckhoff PCIe module slots, 2-channel, PCI Express x1 bus

C9900-E301	RS232 PCIe module – 2 serial interfaces RS232 – transfer rate up to 921,600 bps – 2 sockets Harting ix type B – requires 2 adapter cable C9900-K920 Harting ix type B to D-Sub 9 pin
C9900-K920	adapter cable Harting ix Type B to D-sub 9-pin for C9900-E301 RS232 PCIe module, length 45 cm
C9900-E277	USB 3.0 PCIe module - 2-port USB 3.0 interfaces - USB transfer rate up to 5 Gbit/s for USB 3.0 - compatible to all USB standards - delivers up to 1 A supply current at each USB port
C9900-D102	CD/DVD-ROM drive slimline
C9900-D118	multi DVD drive slimline, reads CD-ROM and DVD-ROM, reads and writes CD-R/-RW, DVD-R/+R/-RW/+RW 4.7 GB and DVD-R/+R DL 8.5 GB
C9900-M712	telescope rails for C5210, rails including bracket set for 19-inch rack assembly
C9900-E292	additional DisplayPort interface, led out on the PCIe module bracket of a C5210, C65xx or C69xx with PCIe module slots ex factory. Max. resolution 1920 x 1080
C9900-E294	additional DisplayPort interface, occupies the fieldbus connection section. Max. resolution 1920 x 1080
C9900-E237	additional DVI-D plug led out on a module bracket
FC9071-0000	Gigabit Ethernet PC interface card, 10/100/1000 Mbit/s, 1-channel, PCIe interface, occupies the connecting area of the Mini PCI card
C9900-H201	hard disk drive, 3½-inch, 2 TB, instead of hard disk 1 TB
C9900-H202	hard disk drive, 3½-inch, 4 TB, instead of hard disk 1 TB, requires a 64 bit operating system and UEFI instead of BIOS
C9900-B528	BIOS for booting from storage media bigger than 2 TB, UEFI activated
C9900-H152	additional hard disk drive, 3½-inch, 1 TB
C9900-H203	additional hard disk drive, 3½-inch, 2 TB
C9900-H204	additional hard disk drive, 3½-inch, 4 TB
C9900-M629	removable frame for a 2½-inch SSD, instead of removable frame for a 3½-inch hard disk
C9900-H741	solid-state disk SSD, 3D flash, 2½-inch, 120 GB
C9900-H749	solid-state disk SSD, 3D flash, 2½-inch, 240 GB
C9900-H745	solid-state disk SSD, 3D flash, 2½-inch, 480 GB
C9900-H743	solid-state disk SSD, 3D flash, 2½-inch, 120 GB, instead of 3½-inch hard disk
C9900-H751	solid-state disk SSD, 3D flash, 2½-inch, 240 GB, instead of 3½-inch hard disk
C9900-H747	solid-state disk SSD, 3D flash, 2½-inch, 480 GB, instead of 3½-inch hard disk
C9900-H700	solid-state disk SSD, SLC flash, 2½-inch, 32 GB
C9900-H705	solid-state disk SSD, SLC flash, 2½-inch, 64 GB
C9900-H735	solid-state disk SSD, SLC flash, 2½-inch, 128 GB
C9900-H702	solid-state disk SSD, SLC flash, 2½-inch, 32 GB, instead of 3½-inch hard disk
C9900-H707	solid-state disk SSD, SLC flash, 2½-inch, 64 GB, instead of 3½-inch hard disk
C9900-H737	solid-state disk SSD, SLC flash, 2½-inch, 128 GB, instead of 3½-inch hard disk
C9900-P208	24 V DC power supply, instead of 100–240 V AC full range power supply, occupies one serial port
C9900-P209	24 V DC power supply with integrated UPS, instead of 100–240 V AC full range power supply, occupies one serial port
C9900-U330	battery pack for PCs with 24 V power supply and integrated UPS C9900-P209 or C9900-U209, external, for DIN rail mounting, 3.4 Ah, operating temperature 0...50 °C
C9900-U120	uninterruptible power supply UPS, external, 230 V
C9900-U122	uninterruptible power supply UPS, external, 115 V
C9900-M623	wall mounting frame for uninterruptible power supply C9900-U120, C9900-U122 and C9900-U124