

TwinCAT 3 Connectivity



TF6220 | TC3 EtherCAT Redundancy 250

TwinCAT EtherCAT Redundancy 250 extends the TwinCAT EtherCAT Master by the possibility to implement cable redundancy for up to 250 EtherCAT devices: from the last logical device a cable is returned back to the master. Configuration and diagnostics take place in the TwinCAT 3 engineering environment.

Technical data	TF6220
Required	TC1100
Target system	Windows XP, Windows 7/8/10, Windows CE

Ordering information	
TF6220-0040	TC3 EtherCAT Redundancy 250, platform 40 (Performance)
TF6220-0050	TC3 EtherCAT Redundancy 250, platform 50 (Performance Plus)
TF6220-0060	TC3 EtherCAT Redundancy 250, platform 60 (Mid Performance)
TF6220-0070	TC3 EtherCAT Redundancy 250, platform 70 (High Performance)
TF6220-0080	TC3 EtherCAT Redundancy 250, platform 80 (Very High Performance)
TF6220-0081	TC3 EtherCAT Redundancy 250, platform 81 (Many-core 5...8 cores)
TF6220-0082	TC3 EtherCAT Redundancy 250, platform 82 (Many-core 9...16 cores)
TF6220-0083	TC3 EtherCAT Redundancy 250, platform 83 (Many-core 17...32 cores)
TF6220-0084	TC3 EtherCAT Redundancy 250, platform 84 (Many-core 33...64 cores)
TF6220-0090	TC3 EtherCAT Redundancy 250, platform 90 (Other)
TF6220-0091	TC3 EtherCAT Redundancy 250, platform 91 (Other 5...8 cores)
TF6220-0092	TC3 EtherCAT Redundancy 250, platform 92 (Other 9...16 cores)
TF6220-0093	TC3 EtherCAT Redundancy 250, platform 93 (Other 17...32 cores)
TF6220-0094	TC3 EtherCAT Redundancy 250, platform 94 (Other 33...64 cores)

Related products	
TF6221	TC3 EtherCAT Redundancy 250+