



TF6255 | TC3 Modbus RTU

TwinCAT Modbus RTU implements Modbus RTU communication via a serial RS232, RS422 or RS485 interface and is thus suitable both for the PC/CX interfaces and for operation with the KL6xxx serial Bus Terminals. It contains function blocks for master and slave operating mode with simple configuration.

Technical data	TF6255
Required	TC1200
Target system	Windows XP, Windows 7/8/10, Windows CE

Ordering information	
TF6255-0020	TC3 Modbus RTU, platform 20 (Economy)
TF6255-0030	TC3 Modbus RTU, platform 30 (Economy Plus)
TF6255-0040	TC3 Modbus RTU, platform 40 (Performance)
TF6255-0050	TC3 Modbus RTU, platform 50 (Performance Plus)
TF6255-0060	TC3 Modbus RTU, platform 60 (Mid Performance)
TF6255-0070	TC3 Modbus RTU, platform 70 (High Performance)
TF6255-0080	TC3 Modbus RTU, platform 80 (Very High Performance)
TF6255-0081	TC3 Modbus RTU, platform 81 (Many-core 5...8 cores)
TF6255-0082	TC3 Modbus RTU, platform 82 (Many-core 9...16 cores)
TF6255-0083	TC3 Modbus RTU, platform 83 (Many-core 17...32 cores)
TF6255-0084	TC3 Modbus RTU, platform 84 (Many-core 33...64 cores)
TF6255-0090	TC3 Modbus RTU, platform 90 (Other)
TF6255-0091	TC3 Modbus RTU, platform 91 (Other 5...8 cores)
TF6255-0092	TC3 Modbus RTU, platform 92 (Other 9...16 cores)
TF6255-0093	TC3 Modbus RTU, platform 93 (Other 17...32 cores)
TF6255-0094	TC3 Modbus RTU, platform 94 (Other 33...64 cores)