TF2200 | TC3 HMI Extension SDK

The TwinCAT HMI Server can be expanded modularly and flexibly via extensions. The software development kit (C++/.NET) can be used for programming application-specific solutions (e.g. business logics, proprietary protocols). In addition, user IP (intellectual property) is protected, and existing functions can be accessed by the server (e.g. ADS, logging).

Technical data	TF2200
Required	TF2000
Target system	Windows 7/8/10

Ordering information	
TF2200-0040	TC3 HMI Extension SDK, platform 40 (Performance)
TF2200-0050	TC3 HMI Extension SDK, platform 50 (Performance Plus)
TF2200-0060	TC3 HMI Extension SDK, platform 60 (Mid Performance)
TF2200-0070	TC3 HMI Extension SDK, platform 70 (High Performance)
TF2200-0080	TC3 HMI Extension SDK, platform 80 (Very High Performance)
TF2200-0081	TC3 HMI Extension SDK, platform 81 (Many-core 5…8 cores)
TF2200-0082	TC3 HMI Extension SDK, platform 82 (Many-core 9…16 cores)
TF2200-0083	TC3 HMI Extension SDK, platform 83 (Many-core 17…32 cores)
TF2200-0084	TC3 HMI Extension SDK, platform 84 (Many-core 33…64 cores)
TF2200-0090	TC3 HMI Extension SDK, platform 90 (Other)
TF2200-0091	TC3 HMI Extension SDK, platform 91 (Other 5…8 cores)
TF2200-0092	TC3 HMI Extension SDK, platform 92 (Other 9…16 cores)
TF2200-0093	TC3 HMI Extension SDK, platform 93 (Other 17…32 cores)
TF2200-0094	TC3 HMI Extension SDK, platform 94 (Other 33…64 cores)

We reserve the right to make technical changes.