

TwinCAT 3 Industry specific



## TF8010 | TC3 Building Automation Basic

The TC3 Building Automation Basic software library allows the implementation of all functions which are important for room automation. Among these are lighting (constant light control, light dimmer,...), facade control, scaling functions, filter blocks, timer functions and peak load limiter for energy optimisation.

<b>Technical data</b>	TF8010
<b>Required</b>	TC1200
<b>Target system</b>	Windows XP, Windows 7/8/10, Windows CE

<b>Ordering information</b>	
TF8010-0020	TC3 Building Automation Basic, platform 20 (Economy)
TF8010-0030	TC3 Building Automation Basic, platform 30 (Economy Plus)
TF8010-0040	TC3 Building Automation Basic, platform 40 (Performance)
TF8010-0050	TC3 Building Automation Basic, platform 50 (Performance Plus)
TF8010-0060	TC3 Building Automation Basic, platform 60 (Mid Performance)
TF8010-0070	TC3 Building Automation Basic, platform 70 (High Performance)
TF8010-0080	TC3 Building Automation Basic, platform 80 (Very High Performance)
TF8010-0081	TC3 Building Automation Basic, platform 81 (Many-core 5...8 cores)
TF8010-0082	TC3 Building Automation Basic, platform 82 (Many-core 9...16 cores)
TF8010-0083	TC3 Building Automation Basic, platform 83 (Many-core 17...32 cores)
TF8010-0084	TC3 Building Automation Basic, platform 84 (Many-core 33...64 cores)
TF8010-0090	TC3 Building Automation Basic, platform 90 (Other)
TF8010-0091	TC3 Building Automation Basic, platform 91 (Other 5...8 cores)
TF8010-0092	TC3 Building Automation Basic, platform 92 (Other 9...16 cores)
TF8010-0093	TC3 Building Automation Basic, platform 93 (Other 17...32 cores)
TF8010-0094	TC3 Building Automation Basic, platform 94 (Other 33...64 cores)