

TwinCAT 3 Industry specific



TF8010 | TC3 Building Automation Basic

Die Softwarebibliothek TC3 Building Automation Basic realisiert alle für die Raumautomatisierung wichtige Funktionen: Beleuchtung (Konstantlichtregelung, Lichtdimmer...), Fassadensteuerung, Skalierungsfunktionen, Filterbausteine, Zeitschaltfunktionen und Maximumwächter zur Energieoptimierung.

Technische Daten	TF8010
Benötigt	TC1200
Zielsystem	Windows XP, Windows 7/8/10, Windows CE

Bestellangaben	
TF8010-0020	TC3 Building Automation Basic, Plattform 20 (Economy)
TF8010-0030	TC3 Building Automation Basic, Plattform 30 (Economy Plus)
TF8010-0040	TC3 Building Automation Basic, Plattform 40 (Performance)
TF8010-0050	TC3 Building Automation Basic, Plattform 50 (Performance Plus)
TF8010-0060	TC3 Building Automation Basic, Plattform 60 (Mid Performance)
TF8010-0070	TC3 Building Automation Basic, Plattform 70 (High Performance)
TF8010-0080	TC3 Building Automation Basic, Plattform 80 (Very High Performance)
TF8010-0081	TC3 Building Automation Basic, Plattform 81 (Many-core 5...8 Cores)
TF8010-0082	TC3 Building Automation Basic, Plattform 82 (Many-core 9...16 Cores)
TF8010-0083	TC3 Building Automation Basic, Plattform 83 (Many-core 17...32 Cores)
TF8010-0084	TC3 Building Automation Basic, Plattform 84 (Many-core 33...64 Cores)
TF8010-0090	TC3 Building Automation Basic, Plattform 90 (Other)
TF8010-0091	TC3 Building Automation Basic, Plattform 91 (Other 5...8 Cores)
TF8010-0092	TC3 Building Automation Basic, Plattform 92 (Other 9...16 Cores)
TF8010-0093	TC3 Building Automation Basic, Plattform 93 (Other 17...32 Cores)
TF8010-0094	TC3 Building Automation Basic, Plattform 94 (Other 33...64 Cores)