



CU8802-0000 | Transmitter box for CP-Link-4 – The Two Cable Display Link

The CP29xx-0010 multi-touch built-in panels and the CP39xx-0010 multi-touch panels for mounting arm installation can be operated up to 100 m away from the PC. CP-Link 4 – The Two Cable Display Link – transfers DVI and USB together via a Cat.6_A cable. The CU8802 CP-Link 4 transmitter box is connected to the PC via DVI and USB, or else the C9900-E276 PCIe module for CP-Link 4 is installed in the PC.

CU8802	Transmitter box for CP-Link-4 – The Two Cable Display Link
	CP-Link 4 Extender Tx for connecting a Control Panel with CP-Link 4 interface CP29xx-0010 or CP39xx-0010
	1 USB input with USB B socket to be connected to the PC in maximum 1 m distance
	1 DVI input with DVI-D socket to be connected to the PC in maximum 1 m distance
	1 CP-Link 4 output with RJ45 socket for up to 100 m Cat.6 _A cable for connecting a Control Panel with CP-Link 4 interface CP29xx-0010 or CP39xx-0010
	power supply for the Control Panel with connection of 24 V at the Control Panel
	metal housing for DIN rail installation
	CP-Link 4 transfers USB 2.0 with 100 Mbit/s and DVI.
	24 V input for power supply of the CU8802 transmitter box
	protection class IP 20
	operating temperature 0...55 °C
	dimensions (W x H x D) 45 x 100 x 80 mm (1.8" x 3.9" x 3.1")
	1 m USB connecting cable
	1 m DVI connecting cable
Accessories	
CU8803-0000	Transmitter box for CP-Link-4 – The One Cable Display Link
C9900-E276	PCIe module for CP-Link 4 – The Two Cable Display Link