



EP2028-000x | 8-channel digital output 24 V DC, I_{MAX} = 2 A (Σ 4 A)

The EP2028 EtherCAT Box with digital outputs connects binary control signals from the controller on to the actuators at the process level. The eight outputs handle load currents of up to 2 A each, although the total current is limited to 4 A. This makes these modules particularly suitable for applications in which not all of the outputs are active at the same time, or in which not all of the actuators draw 2 A signal current.

The signal state is indicated by means of light emitting diodes. The signals are optionally connected via M8 (EP2028-0001) or M12 (EP2028-0002) screw type connectors. The outputs are short-circuit-proof and protected against inverse connection.

Technical data	EP2028-0001	EP2028-0002
Number of outputs	8	
Output connections	M8, screw type	M12, screw type
Protocol	EtherCAT	
Bus interface	2 x M8 socket, shielded, screw type	
Load type	ohmic, inductive, lamp load	
Nominal output voltage	24 V DC (-15 %/+20 %)	
Max. output current	2 A per channel, individually short-circuit safe, total current max. 4 A	
Short circuit current	max. 7 A	
Distributed clocks	–	
Auxiliary power current	typ. 20 mA + load	
Current consumption from Us (without sensor current)	120 mA	
Power supply connection	feed: 1 x M8 male socket, 4-pin; downstream connection: 1 x M8 female socket, 4-pin	
Bit width in the process image	8 outputs	
Electrical isolation	500 V	
Weight	approx. 165 g	
Operating/storage temperature	-25...+60 °C/-40...+85 °C	
Vibration/shock resistance	conforms to EN 60068-2-6/EN 60068-2-27	
EMC immunity/emission	conforms to EN 61000-6-2/EN 61000-6-4	
Protect. class/installation pos.	IP 65/66/67 (conforms to EN 60529)/variable	
Approvals	CE, UL, Ex	

Accessories	
ZK1090-3xxx-xxxx	Cables for EtherCAT signal in- and -output
ZK2000-2xxx-xxxx	Cables for M8 I/O connection sockets
ZK2000-6xxx-xxxx	Cables for M12 I/O connection sockets
ZK2020-xxxx-xxxx	Cables for M8 power supply