



KL3214 | 4-channel input terminal PT100 (RTD) for 3-wire connection

The KL3214 analog input terminal allows four resistance sensors to be connected directly. The Bus Terminal circuit can operate sensors using the 3-wire technique in a compact 12 mm housing. A microprocessor handles linearisation across the whole temperature range, which is freely selectable. The Bus Terminal's standard settings are: resolution 0.1 °C. Sensor malfunctions such as broken wires are indicated by error LEDs.

Technical data	KL3214
Number of inputs	4
Power supply	via the K-bus
Input filter limit frequency	typ. 1 kHz
Sensor types	PT100/200/500/1000, Ni100/120/1000, potentiometer: 10 Ω...1.2/4 kΩ, KTY sensors (types see documentation)
Connection method	3-wire
Measuring range	-200...+850 °C (PT sensors); -60...+250 °C (Ni sensors)
Conversion time	approx. 170 ms default setting
Measuring current	< 0.5 mA (load-dependent)
Resolution	0.1 °C per digit
Measuring error	< ±0.5 °C for PT sensors
Electrical isolation	500 V (K-bus/signal voltage)
Current consumption power contacts	–
Current consumption K-bus	typ. 120 mA
Special features	open-circuit recognition
Weight	approx. 60 g
Operating/storage temperature	0...+55 °C/-25...+85 °C
Relative humidity	95 %, no condensation
Vibration/shock resistance	conforms to EN 60068-2-6/EN 60068-2-27
EMC immunity/emission	conforms to EN 61000-6-2/EN 61000-6-4
Protect. class/installation pos.	IP 20/variable
Approvals	CE, UL