



KL3122 | 2-channel analog input terminal 4...20 mA

The KL3122 analog input terminal handles signals in the range from 4 to 20 mA. The current is digitised to a resolution of 16 bits (the default is 15 bits), and is transmitted, in an electrically isolated form, to the higher-level automation device. The input channels of the Bus Terminal have differential inputs and possess a common, internal ground potential. The KL3122 combines two channels in a housing. An open lead or overload condition are detected, and the terminal status is relayed to the controller via the K-bus. The run LEDs give an indication of the data exchange with the Bus Coupler. The error LEDs indicate an overload condition.

Technical data	KL3122 KS3122
Number of inputs	2
Power supply	via the K-bus
Signal current	4...20 mA
Technology	differential input
Internal resistance	50 Ω typ. shunt, load: 60 Ω + diode voltage
Common-mode voltage U_{CM}	35 V max.
Resolution	15 bit, configurable to 16 bit
Conversion time	140 ms, configurable to 2 ms
Filter	50 Hz, configurable
Measuring error	< ± 0.3 % (relative to full scale value)
Surge voltage resistance	35 V DC
Electrical isolation	500 V (K-bus/signal voltage)
Current consumption power contacts	– (no power contacts)
Current consumpt. K-bus	typ. 60 mA
Bit width in the process image	input: 2 x 16 bit data (2 x 8 bit control/status optional)
Configuration	no address or configuration setting
Weight	approx. 70 g
Operating/storage temperature	0...+55 °C/-25...+85 °C
Relative humidity	95 %, no condensation
Vibration/shock resistance	conforms to EN 60068-2-6/EN 60068-2-27
EMC immunity/emission	conforms to EN 61000-6-2/EN 61000-6-4
Protect. class/installation pos.	IP 20/variable
Pluggable wiring	for all KSxxxx Bus Terminals
Approvals	CE, UL, Ex

Special terminals	
KL3122-0050	Siemens S7 format