



## TF6310 | TC3 TCP/IP

TwinCAT TCP/IP enables the implementation and realisation of one or several TCP/IP servers and/or TCP/IP clients within the TwinCAT 3 PLC. Corresponding blocks exist for the establishment/disconnection of communication as well as for the pure exchange of data (send and receive). The function blocks also support the use of multicast addresses.

<b>Technical data</b>	<b>TF6310</b>
Required	TC1200
Target system	Windows XP, Windows 7/8/10, Windows CE

Ordering information	
TF6310-0020	TC3 TCP/IP, platform 20 (Economy)
TF6310-0030	TC3 TCP/IP, platform 30 (Economy Plus)
TF6310-0040	TC3 TCP/IP, platform 40 (Performance)
TF6310-0050	TC3 TCP/IP, platform 50 (Performance Plus)
TF6310-0060	TC3 TCP/IP, platform 60 (Mid Performance)
TF6310-0070	TC3 TCP/IP, platform 70 (High Performance)
TF6310-0080	TC3 TCP/IP, platform 80 (Very High Performance)
TF6310-0081	TC3 TCP/IP, platform 81 (Many-core 5...8 cores)
TF6310-0082	TC3 TCP/IP, platform 82 (Many-core 9...16 cores)
TF6310-0083	TC3 TCP/IP, platform 83 (Many-core 17...32 cores)
TF6310-0084	TC3 TCP/IP, platform 84 (Many-core 33...64 cores)
TF6310-0090	TC3 TCP/IP, platform 90 (Other)
TF6310-0091	TC3 TCP/IP, platform 91 (Other 5...8 cores)
TF6310-0092	TC3 TCP/IP, platform 92 (Other 9...16 cores)
TF6310-0093	TC3 TCP/IP, platform 93 (Other 17...32 cores)
TF6310-0094	TC3 TCP/IP, platform 94 (Other 33...64 cores)