

C6640-0050 | Control cabinet Industrial PC

Variants	Processor	available
C6640-0030	Intel® Celeron®, 2 Cores (TC3: 50*) or Intel® Core™ i3, 2 Cores (TC3: 60*) or Intel® Core™ i5, 2 Cores (TC3: 70*) or Intel® Core™ i7, 4 Cores (TC3: 80*)	yes, but not recommended for new projects
C6640-0040	Intel® Pentium®, 2 Cores (TC3: 50*) or Intel® Core™ i3, 2 Cores (TC3: 60*) or Intel® Core™ i5, 2 Cores (TC3: 70*) or Intel® Core™ i5, 4 Cores (TC3: 70*) or Intel® Core™ i7, 4 Cores (TC3: 80*) (4th generation)	yes
C6640-0050	Intel® Celeron®, 2 Cores (TC3: 50*) or Intel® Pentium®, 2 Cores (TC3: 50*) or Intel® Core™ i3, 2 Cores (TC3: 60*) or Intel® Core™ i5, 4 Cores (TC3: 70*) or Intel® Core™ i7, 4 Cores (TC3: 80*) (6th/7th generation)	yes

*The TwinCAT 3 performance class defines the exact ordering number for the respective TwinCAT 3 product. Please see [here](#) for an overview of the TC3 performance classes.

C6640-0050	Control cabinet PC
Housing	7-slot ATX Industrial PC for control cabinet installation
	all slots for up to 210 mm long plug-in cards
	drives and plug-in cards easily accessible
	2 brackets to led out serial interfaces
	all connectors on the top
	detailed PC configuration information on the front
	card holders, actuated without tools
	protection class IP 20
	operating temperature 0...55 °C
	weight of the basic configuration 11 kg (24.3 lbs)
dimensions (W x H x D) 371 x 336 x 198 mm (14.6" x 13.2" x 7.8")	
Features	processor Intel® Celeron® G3900 2.8 GHz, 2 cores (TC3: 50)
	ATX motherboard for 6th and 7th Generation Intel® Core™ i3, Core™ i5, Core™ i7, Celeron® or Pentium®
	2 PCIe x1 slots, 2 PCIe x4 slots, 1 PCIe x16 slot and 2 PCI slots free
	4 GB DDR4 RAM, expandable to 64 GB, with a 32 bit operating system only 3 GB are addressable.
	Graphic adapter integrated inside the Intel® processor, 2 DVI and 1 DisplayPort connector.
	on-board dual Ethernet adapter with 2 x 100/1000BASE-T connector
	on-board SATA RAID 1 controller, Intel® Rapid Storage Technology
	hard disk, 3½-inch, 1 TB
	4 serial ports RS232 on-board, 1 of these RS232 ports is led out with D-sub 9 connector; 10 USB 2.0 on-board, not led out; 4 USB 3.0 ports are led out
	PS/2 keyboard socket and PS/2 mouse socket
100–240 V AC full range power supply	

Options	C6640-0050
C9900-C611	processor 6th Generation Intel® Pentium® G4400, 3.3 GHz, 2 cores (TC3: 50), instead of Intel® Celeron® G3900 2.8 GHz (TC3: 50)
C9900-C612	processor 6th Generation Intel® Core™ i3-6100, 3.7 GHz, 2 cores (TC3: 60), instead of Intel® Celeron® G3900 2.8 GHz (TC3: 50)
C9900-C615	processor 7th Generation Intel® Core™ i3-7101E, 3.9 GHz, 2 cores (TC3: 60), requires Windows 10, 64 bit, instead of Intel® Celeron® G3900 2.8 GHz (TC3: 50)
C9900-C613	processor 6th Generation Intel® Core™ i5-6500, 3.2 GHz, 4 cores (TC3: 70), instead of Intel® Celeron® G3900 2.8 GHz (TC3: 50)
C9900-C616	processor 7th Generation Intel® Core™ i5-7500, 3.4 GHz, 4 cores (TC3: 70), requires Windows 10, 64 bit, instead of Intel® Celeron® G3900 2.8 GHz (TC3: 50)
C9900-C614	processor 6th Generation Intel® Core™ i7-6700, 3.4 GHz, 4 cores (TC3: 80), instead of Intel® Celeron® G3900 2.8 GHz (TC3: 50)
C9900-C617	processor 7th Generation Intel® Core™ i7-7700, 3.6 GHz, 4 cores (TC3: 80), requires Windows 10, 64 bit, instead of Intel® Celeron® G3900 2.8 GHz (TC3: 50)
C9900-R270	memory extension to 8 GB DDR4 RAM, instead of 4 GB, requires a 64 bit operating system
C9900-R271	memory extension to 16 GB DDR4 RAM, instead of 4 GB, requires a 64 bit operating system
C9900-R272	memory extension to 32 GB DDR4 RAM, instead of 4 GB, requires a 64 bit operating system
C9900-R273	memory extension to 64 GB DDR4 RAM, instead of 4 GB, requires a 64 bit operating system
C9900-E195	2 USB ports of the motherboard led out in one slot bracket
C9900-E216	2 USB ports of the motherboard led out in the front of a C66xx
C9900-E231	1 serial port RS232 from the motherboard led out with a D-sub, 9-pin connector in a connector bracket on the top site of a C66xx in front of the ATX connector bracket
C9900-E166	2 serial interfaces RS232 of the motherboard led out with 2 D-sub 9-pin connectors in one slot bracket
C9900-E203	1 serial port RS232 from the motherboard led out with one D-sub, 9-pin connector in one slot bracket
C9900-E209	Module to optically link one serial RS232 port of the motherboard, with overload protection, D-sub, 9-pin, to be mounted inside of slot bracket C9900-M568, C9900-M569 or inside a C66xx at the connector bracket C9900-M571. A bracket is required.
C9900-E210	Module to convert one serial RS232 port of the motherboard into RS485, configured as an end point without echo, D-sub, 9-pin, optically linked, overload protection, to be mounted inside the slot brackets C9900-M568, C9900-M569 or inside a C66xx at the connector bracket C9900-M571. A slot bracket is required.
C9900-E211	Module to convert one serial RS232 port of the motherboard into RS422, configured as a full duplex end point, D-sub, 9-pin, optically linked, overload protection, to be mounted inside the slot brackets C9900-M568, C9900-M569 or inside a C66xx at the connector bracket C9900-M571. A bracket is required.
C9900-M568	Slot bracket for one serial port C9900-E209, C9900-E210 or C9900-E211. Can be ordered only together with one module.
C9900-M569	Slot bracket for two serial ports C9900-E209, C9900-E210 or C9900-E211. Can be ordered only together with two modules.
C9900-M571	Connector bracket for one serial port module C9900-E209, C9900-E210 or C9900-E211, to be mounted inside a C66xx in front of the ATX connector bracket. Can only be ordered in combination with a module.
C9900-D187	1 slot for 2½-inch hard disks or SSDs behind the front cover
C9900-H743	solid-state disk SSD, 3D flash, 2½-inch, 120 GB, instead of 3½-inch hard disk
C9900-H751	solid-state disk SSD, 3D flash, 2½-inch, 240 GB, instead of 3½-inch hard disk
C9900-H747	solid-state disk SSD, 3D flash, 2½-inch, 480 GB, instead of 3½-inch hard disk
C9900-H741	solid-state disk SSD, 3D flash, 2½-inch, 120 GB
C9900-H749	solid-state disk SSD, 3D flash, 2½-inch, 240 GB
C9900-H745	solid-state disk SSD, 3D flash, 2½-inch, 480 GB
C9900-H702	solid-state disk SSD, SLC flash, 2½-inch, 32 GB, instead of 3½-inch hard disk
C9900-H707	solid-state disk SSD, SLC flash, 2½-inch, 64 GB, instead of 3½-inch hard disk
C9900-H737	solid-state disk SSD, SLC flash, 2½-inch, 128 GB, instead of 3½-inch hard disk
C9900-H700	solid-state disk SSD, SLC flash, 2½-inch, 32 GB
C9900-H705	solid-state disk SSD, SLC flash, 2½-inch, 64 GB
C9900-H735	solid-state disk SSD, SLC flash, 2½-inch, 128 GB
C9900-H145	additional hard disk, 2½-inch, 320 GB
C9900-D193	1 slot for CFast cards behind the front cover
C9900-H585	30 GB CFast card, 3D flash, extended temperature range, instead of 3½-inch hard disk
C9900-H589	60 GB CFast card, 3D flash, extended temperature range, instead of 3½-inch hard disk
C9900-H558	16 GB CFast card, SLC flash, extended temperature range, instead of 3½-inch hard disk
C9900-H566	32 GB CFast card, SLC flash, extended temperature range, instead of 3½-inch hard disk
C9900-H570	64 GB CFast card, SLC flash, extended temperature range, instead of 3½-inch hard disk
C9900-H201	hard disk drive, 3½-inch, 2 TB, instead of hard disk 1 TB
C9900-H202	hard disk drive, 3½-inch, 4 TB, instead of hard disk 1 TB, requires a 64 bit operating system and UEFI instead of BIOS
C9900-B528	BIOS for booting from storage media bigger than 2 TB, UEFI activated
C9900-D102	CD/DVD-ROM drive slimline
C9900-D118	multi DVD drive slimline, reads CD-ROM and DVD-ROM, reads and writes CD-R/-RW, DVD-R/+R/-RW/+RW 4.7 GB and DVD-R/+R DL 8.5 GB
C9900-P208	24 V DC power supply, instead of 100–240 V AC full range power supply, occupies one serial port

C9900-P209	24 V DC power supply with integrated UPS, instead of 100–240 V AC full range power supply, occupies one serial port
C9900-U330	battery pack for PCs with 24 V power supply and integrated UPS C9900-P209 or C9900-U209, external, for DIN rail mounting, 3.4 Ah, operating temperature 0...50 °C
C9900-U120	uninterruptible power supply UPS, external, 230 V
C9900-U122	uninterruptible power supply UPS, external, 115 V
C9900-M623	wall mounting frame for uninterruptible power supply C9900-U120, C9900-U122 and C9900-U124
C9900-xxxx	Flash cards, PCI and PCIe cards as listed in the attachment. Examples: Compact Flash, CFast, fieldbus interface, network adapter, serial interface card, modem