



EP1816-0008 | 16-channel digital input 24 V DC

The EP1816 EtherCAT Box with digital inputs acquires the binary control signals from the process level and transmits them, in an electrically isolated form, to the controller. The state of the signals is indicated by light emitting diodes. The signals are connected via 25-pin D-sub socket.

The sensors are supplied from the box supply voltage U_s . The auxiliary voltage U_p is not used in the input module, but may be connected in order to be relayed downstream.

Technical data	EP1816-0008	EP1816-1008
Specification	EN 61131-2, type 1/3	
Number of inputs	16	
Input connections	D-sub socket, 25-pin	
Protocol	EtherCAT	
Bus interface	2 x M8 socket, shielded, screw type	
Nominal input voltage	24 V DC (-15 %/+20 %)	
Input filter	10 μ s	
"0" signal voltage	-3...+5 V (EN 61131-2, type 3)	
"1" signal voltage	11...30 V (EN 61131-2, type 3)	
Input current	typ. 3 mA (EN 61131-2, type 3)	
Distributed clocks	yes	
Sensor supply	from control voltage, max. 0.5 A total, short-circuit-proof	
Power supply connection	feed: 1 x M8 male socket, 4-pin; downstream connection: 1 x M8 female socket, 4-pin	
Bit width in the process image	16 inputs	
Current consumption from U_s (without sensor current)	120 mA	
Electrical isolation	500 V	
Weight	approx. 165 g	
Operating/storage temperature	-25...+60 °C/-40...+85 °C	
Vibration/shock resistance	conforms to EN 60068-2-6/EN 60068-2-27	
EMC immunity/emission	conforms to EN 61000-6-2/EN 61000-6-4	
Protect. class/installation pos.	IP 65/66/67 (conforms to EN 60529)/variable	
Approvals	CE, UL	

Accessories	
ZK1090-3xxx-xxxx	Cables for EtherCAT signal in- and -output
ZK2020-xxxx-xxxx	Cables for M8 power supply