



C9900-E276 | PCIe module for CP-Link 4 – The Two Cable Display Link

The CP29xx-0010 multi-touch built-in panels and the CP39xx-0010 multi-touch panels for mounting arm installation can be operated up to 100 m away from the PC. CP-Link 4 – The Two Cable Display Link – transfers DVI and USB together via a Cat.6_A cable. The CU8802 CP-Link 4 transmitter box is connected to the PC via DVI and USB, or else the C9900-E276 PCIe module for CP-Link 4 is installed in the PC.

C9900-E276	PCIe module for CP-Link 4 – The Two Cable Display Link
	CP-Link 4 Extender Tx PCIe module
	CP-Link 4 transmitter module for ex factory installation in PCs with Beckhoff PCIe module slots
	1 CP-Link 4 output with RJ45 socket for up to 100 m Cat.6 _A cable for connecting a Control Panel with CP-Link 4 interface CP29xx-0010 or CP39xx-0010
	CP-Link 4 transfers USB 2.0 with 100 Mbit/s and DVI.
	power supply for the Control Panel with connection of 24 V at the Control Panel

Accessories	
CU8802-0000	Transmitter box for CP-Link-4 – The Two Cable Display Link
CU8803-0000	Transmitter box for CP-Link-4 – The One Cable Display Link