



## EP1008-000x | 8-channel digital input 24 V DC, 3.0 ms

The EP1008 EtherCAT Box with digital inputs acquires the binary control signals from the process level and transmits them, in an electrically isolated form, to the controller. The state of the signals is indicated by light emitting diodes. The signals are optionally connected via M8 (EP1008-0001) or M12 (EP1008-0002) screw type connectors.

The sensors are supplied from the box supply voltage  $U_s$ . The auxiliary voltage  $U_p$  is not used in the input module, but may be connected in order to be relayed downstream.

Technical data	EP1008-0001	EP1008-0002
Specification	EN 61131-2, type 1/3	
Number of inputs	8	
Input connections	M8, screw type	M12, screw type
Protocol	EtherCAT	
Bus interface	2 x M8 socket, shielded, screw type	
Nominal input voltage	24 V DC (-15 %/+20 %)	
Input filter	3 ms	
"0" signal voltage	-3...+5 V (EN 61131-2, type 3)	
"1" signal voltage	11...30 V (EN 61131-2, type 3)	
Input current	typ. 3 mA (EN 61131-2, type 3)	
Distributed clocks	-	
Sensor supply	from control voltage, max. 0.5 A total, short-circuit-proof	
Power supply connection	feed: 1 x M8 male socket, 4-pin; downstream connection: 1 x M8 female socket, 4-pin	
Bit width in the process image	8 inputs	
Current consumption from $U_s$	120 mA	
Electrical isolation	500 V	
Weight	approx. 165 g	
Operating/storage temperature	-25...+60 °C/-40...+85 °C	
Vibration/shock resistance	conforms to EN 60068-2-6/EN 60068-2-27	
EMC immunity/emission	conforms to EN 61000-6-2/EN 61000-6-4	
Protect. class/installation pos.	IP 65/66/67 (conforms to EN 60529)/variable	
Approvals	CE, UL, Ex	

Accessories	
ZK1090-3xxx-xxxx	Cables for EtherCAT signal in- and -output
ZK2000-xxxx-xxxx	Cables for M8 I/O connection sockets
ZK2000-6xxx-xxxx	Cables for M12 I/O connection sockets
ZK2020-3xxx-xxxx	Cables for M8 power supply

Related products	
EQ1008-0002	EtherCAT Box, stainless steel housing, 8 digital inputs, 24 V DC, filter 3.0 ms