



TF6600 | TC3 RFID Reader Communication

RFID Reader Communication allows various RFID readers to be addressed via a serial interface. The new TwinCAT RFID reader library offers a general abstract interface that can be used for all readers. The configuration can easily be adapted to a specific reader.

Technical data	TF6600
Required	TC1200
Target system	Windows XP, Windows 7/8/10, Windows CE

Ordering information	
TF6600-0020	TC3 RFID Reader Communication, platform 20 (Economy)
TF6600-0030	TC3 RFID Reader Communication, platform 30 (Economy Plus)
TF6600-0040	TC3 RFID Reader Communication, platform 40 (Performance)
TF6600-0050	TC3 RFID Reader Communication, platform 50 (Performance Plus)
TF6600-0060	TC3 RFID Reader Communication, platform 60 (Mid Performance)
TF6600-0070	TC3 RFID Reader Communication, platform 70 (High Performance)
TF6600-0080	TC3 RFID Reader Communication, platform 80 (Very High Performance)
TF6600-0081	TC3 RFID Reader Communication, platform 81 (Many-core 5...8 cores)
TF6600-0082	TC3 RFID Reader Communication, platform 82 (Many-core 9...16 cores)
TF6600-0083	TC3 RFID Reader Communication, platform 83 (Many-core 17...32 cores)
TF6600-0084	TC3 RFID Reader Communication, platform 84 (Many-core 33...64 cores)
TF6600-0090	TC3 RFID Reader Communication, platform 90 (Other)
TF6600-0091	TC3 RFID Reader Communication, platform 91 (Other 5...8 cores)
TF6600-0092	TC3 RFID Reader Communication, platform 92 (Other 9...16 cores)
TF6600-0093	TC3 RFID Reader Communication, platform 93 (Other 17...32 cores)
TF6600-0094	TC3 RFID Reader Communication, platform 94 (Other 33...64 cores)