



EPI2008-000x | 8-channel digital output 24 V DC, $I_{\max} = 0.5$ A ($\Sigma 4$ A)

The EPI2008 IO-Link box with digital outputs connects binary control signals from the controller on to the actuators at the process level. The eight outputs handle load currents of up to 0.5 A, and although the total current is limited to 4 A, they indicate their status through light emitting diodes. The signals are optionally connected via M8 (EPI2008-0001) or M12 (EPI2008-0002) screw type connectors. The outputs are short-circuit proof and protected against inverse connection.

Technical data	EPI2008-0001	EPI2008-0002
Communication	IO-Link	
Data transfer rates	230.4 kbaud (COM 3)	
Specification version	IO-Link V1.1, Class B	
Number of outputs	8	
Output connections	M8, screw type	M12, screw type
Interfaces	1 x M12 plug, A-coded	
Load type	ohmic, inductive, lamp load	
Nominal output voltage	24 V DC (-15 %/+20 %)	
Max. output current	0.5 A per channel, individually short-circuit proof	
Short circuit current	typ. 1.5 A	
Current consumption	typ. 100 mA from L+	
Auxiliary power current	typ. 20 mA + load	
Bit width in the process image	8 outputs	
Electrical isolation	L+/2L+: yes	
Operating/storage temperature	-25...+60 °C/-40...+85 °C	
Vibration/shock resistance	conforms to EN 60068-2-6/EN 60068-2-27	
EMC immunity/emission	conforms to EN 61000-6-2/EN 61000-6-4	
Protect. class/installation pos.	IP 65/66/67 (conforms to EN 60529)/variable	
Approvals	CE, UL	

Related products	
EP6228	EtherCAT Box, industrial housing, 8-channel IO-Link master, IP 67
EP6224	EtherCAT Box, industrial housing, 4-channel IO-Link master, IP 67
EL6224	EtherCAT Terminal, IO-Link master, IP 20
KL6224	Bus Terminal, IO-Link master, IP 20