



BK9055 | EtherNet/IP Bus Coupler

EtherNet/IP The “Compact” BK9055 Bus Coupler connects EtherNet/IP with the modular, extendable electronic terminal blocks. One unit consists of one Bus Coupler, any number from 1 to 64 terminals (255 with K-bus extension) and one end terminal.

The Bus Coupler recognises the terminals to which it is connected, and performs the assignment of the inputs and outputs to the words of the process image automatically. The BK9055 Bus Coupler supports 10 Mbit/s and 100 Mbit/s Ethernet. Connection is through normal RJ45 connectors. The IP address is set on the DIP switch (offset to a freely selectable start address). In networks with DHCP (a service for the allocation of the logical IP address to the physical node address [MAC-ID]) the Bus Coupler obtains its IP address from the DHCP server.

Ethernet/IP is the Industrial Ethernet standard of ODVA (Open DeviceNet Vendor Association). Ethernet/IP is based on Ethernet TCP/IP and UDP/IP – IP stands for Industrial Protocol. Essentially, the CIP (Common Industrial Protocol) used in ControlNet and DeviceNet was ported to Ethernet TCP/IP and UDP/IP.

System data	EtherNet/IP BK9055
Number of I/O stations	only limited by IP addresses
Number of I/O points	depending on controller
Data transfer medium	4 x 2 twisted pair copper cable; category 3 (10 Mbaud), category 5 (100 Mbaud)
Distance between stations	100 m between hub/switch and Bus Coupler
Data transfer rates	10/100 Mbaud
Topology	star wiring

Technical data	BK9055
Number of Bus Terminals	64 (255 with K-bus extension)
Max. number of bytes fieldbus	512 byte input and 512 byte output
Digital peripheral signals	1,020 inputs/outputs
Analog peripheral signals	128 inputs/outputs
Protocol	EtherNet/IP
Configuration possibility	via KS2000
Data transfer rates	10/100 Mbaud, automatic recognition of the transmission rate
Bus interface	1 x RJ45
Power supply	24 V DC (-15 %/+20 %)
Input current	320 mA max.
Starting current	2.5 x continuous current
Recommended fuse	≤ 10 A
Current supply K-bus	1750 mA
Power contacts	max. 24 V DC/max. 10 A
Electrical isolation	500 V (power contact/supply voltage/fieldbus)
Weight	approx. 100 g
Operating/storage temperature	0...+55 °C/-25...+85 °C
Relative humidity	95 %, no condensation
Vibration/shock resistance	conforms to EN 60068-2-6/EN 60068-2-27
EMC immunity/emission	conforms to EN 61000-6-2/EN 61000-6-4
Protect. class/installation pos.	IP 20/variable

Approvals	CE, UL, Ex
------------------	------------

Accessories	
KS2000	configuration software for extended parameterisation
Cordsets	cordsets and connectors
FC9001-0010 FC9011	Ethernet PCI fieldbus cards

Ordering information	Description
BK9055	EtherNet/IP "Compact" Bus Coupler for up to 64 Bus Terminals (255 with K-bus extension)
BK9055-1000	EtherNet/IP "Compact" Bus Coupler for up to 64 Bus Terminals (255 with K-bus extension), default IP address: 192.168.1.xxx
BK9105	EtherNet/IP Bus Coupler for up to 64 Bus Terminals (255 with K-bus extension)
BK9105-1000	EtherNet/IP Bus Coupler for up to 64 Bus Terminals (255 with K-bus extension), default IP address: 192.168.1.xxx
CX8095	EtherNet/IP Embedded PC

Further information	
EtherNet/IP	EtherNet/IP solutions in IP 20 and IP 67

System	
EtherNet/IP	For further EtherNet/IP products please see the system overview