

# CPX29xx-0000 | Multi-touch built-in Control Panel with DVI/USB Extended interface

For use in hazardous areas, Zone 2/22

Variants	Transmission technology	available
CPX29xx-0000	DVI/USB Extended	yes

CPX29xx-0000	
Features	aluminium housing with glass front, front side IP 65, rear side IP 20
	for use in hazardous areas, Zone 2/22
	multi-finger touch screen
	– multi-finger touch screen driver included in Windows 7 and Windows 10
	– single-finger touch screen driver available for Windows XP and Windows CE 6
	integrated DVI/USB extension technology
	– DVI-E and USB-E 2.0 enable remote panel operation at a distance of up to 50 m from the PC.
	– USB-E 2.0 transmits USB 2.0 with 480 Mbit/s.
	– DVI-E input is compatible to the standard DVI output of a PC.
	USB 3.0 input for the direct connection to a standard USB output of a PC with distances of up to 3 m
	2-port USB 3.0 socket inside the Control Panel backplane, for USB-E 2.0 limited to USB 2.0
all connectors at the lower rear side	
24 V power supply	
operating temperature 0...55 °C	
pull-out clamping levers for fast installation without loose parts	
solid clamping frame for even pressure distribution on the seal	

Options	Multi-touch built-in Control Panel with DVI/USB Extended interface
C9900-K622	connecting kit 1 m for CP29xx-0000 and CPX29xx-0000, containing: 1 m DVI cable, 1 m USB cable
C9900-K623	connecting kit 3 m for CP29xx-0000 and CPX29xx-0000, containing: 3 m DVI cable, 3 m USB cable
C9900-K624	connecting kit 5 m for CP29xx-0000 and CPX29xx-0000, containing: 5 m DVI cable, 5 m USB cable
C9900-K625	connecting kit 10 m for CP29xx-0000 and CPX29xx-0000 including: 10 m DVI cable, 10 m CAT 5 cable for USB-E 2.0, USB-to-USB-E 2.0 converter CU8801 for mounting rail installation close to the PC and 1 m USB cable to connect the USB-to-USB-E 2.0 converter to the PC
C9900-K626	connecting kit 20 m for CP29xx-0000 and CPX29xx-0000 including: 20 m DVI cable, 20 m CAT 5 cable for USB-E 2.0, USB-to-USB-E 2.0 converter CU8801 for mounting rail installation close to the PC and 1 m USB cable to connect the USB-to-USB-E 2.0 converter to the PC
C9900-K627	connecting kit 30 m for CP29xx-0000 and CPX29xx-0000 including: 30 m DVI cable, 30 m CAT 5 cable for USB-E 2.0, USB-to-USB-E 2.0 converter CU8801 for mounting rail installation close to the PC and 1 m USB cable to connect the USB-to-USB-E 2.0 converter to the PC
C9900-K628	connecting kit 40 m for CP29xx-0000 and CPX29xx-0000 including: 40 m DVI cable, 40 m CAT 5 cable for USB-E 2.0, USB-to-USB-E 2.0 converter CU8801 for mounting rail installation close to the PC and 1 m USB cable to connect the USB-to-USB-E 2.0 converter to the PC
C9900-K629	connecting kit 50 m for CP29xx-0000 and CPX29xx-0000 including: 50 m DVI cable, 50 m CAT 5 cable for USB-E 2.0, USB-to-USB-E 2.0 converter CU8801 for mounting rail installation close to the PC and 1 m USB cable to connect the USB-to-USB-E 2.0 converter to the PC

CPX29xx-0000	Multi-touch built-in Control Panel with DVI/USB Extended interface
CPX2915-0000	15-inch display 1024 x 768 Display only, Multi-finger touch screen
CPX2919-0000	19-inch display 1280 x 1024 Display only, Multi-finger touch screen
CPX2921-0000	21.5-inch display 1920 x 1080 Display only, Multi-finger touch screen