



EP7041-1002 | Stepper motor module 50 V DC, 1.5 A, with incremental encoder

The EP7041-1002 EtherCAT Box is intended for the direct connection of different Stepper Motors. The PWM output stages for two motor coils with compact design are located in the module together with two inputs for limit switches and cover a wide voltage and current range. The EP7041-1002 can be adjusted to the motor and the application by changing just a few parameters. 64-fold micro-stepping ensures particularly quiet and precise motor operation. Connection of an incremental encoder enables a simple servo axis to be realised. Two digital inputs and a digital 0.5 A output enable connection of end switches and a motor brake.

Technical data	EP7041-1002
Number of outputs	1 stepper motor, 1 digital 24 V DC output
Number of inputs	2 digital inputs, encoder system (24 V DC encoder)
Connection method	M12, screw type
Load type	uni- or bipolar stepper motors
Nominal voltage	8...50 V DC
Distributed clocks	yes
Protocol	EtherCAT
Output current	2 x 1 A, 2 x 1.5 A peak current (overload- and short-circuit-proof)
Maximum step frequency	1000, 2000, 4000 or 8000 full steps/s (configurable)
Step pattern	64-fold micro stepping
Current controller frequency	approx. 30 kHz
Diagnostics LED	error phase A and B, loss of step/stagnation, power, enable
Resolution	approx. 5000 positions (per revolution)
Bit width in the process image	input/output: 2 x 16 bit data + 1 x 16 bit control/status
Electrical isolation	control voltage/fieldbus: yes
Current consumption from Us	120 mA
Special features	travel distance control, encoder input
Weight	approx. 165 g
Operating/storage temperature	-25...+60 °C/-40...+85 °C
Vibration/shock resistance	conforms to EN 60068-2-6/EN 60068-2-27
EMC immunity/emission	conforms to EN 61000-6-2/EN 61000-6-4
Protect. class/installation pos.	IP 65/66/67 (conforms to EN 60529)/variable
Approvals	CE, Ex

Accessories	
ZK1090-3xxx-xxxx	Cables for EtherCAT signal in- and -output
ZK2020-3xxx-xxxx	Cables for M8 power supply
AS2021-wCy0	stepper motor, 50 V DC, 0.83 Nm standstill torque, 2.0 A standstill current
Cables, gears and couplings	accessories for AS2000 stepper motors

Further information Internet	
EP7041-0002	stepper motor EtherCAT Box (industrial housing), I _{MAX} = 5 A, 50 V, IP 67
EP7041-2002	EtherCAT Box, industrial housing, Stepper Motor module 50 V DC, 5 A, 2 phases, with incremental encoder, 2 digital inputs 24 V DC, 1 digital output 24 V DC, motor connection via plug
EP7041-3002	EtherCAT Box, industrial housing, Stepper Motor module 50 V DC, 5 A, 2 phases, with incremental encoder, 2 digital inputs 24 V DC, 1 digital output 24 V DC, for high speed applications
EL7041	stepper motor EtherCAT Terminal, I _{MAX} = 5 A, 50 V, IP 20
EL7031	stepper motor EtherCAT Terminal, I _{MAX} = 1.5 A, 24 V, IP 20