



BC9050 | Ethernet TCP/IP Bus Terminal Controller

Ethernet TCP/IP The BC9050 "Compact" Bus Terminal Controller with compact housing is a Bus Coupler with integrated PLC functionality and has a fieldbus interface for Ethernet. It is an intelligent slave that can be used as a non-central intelligence in the Ethernet system.

One unit consists of the Bus Terminal Controller, any number of terminals between 1 and 64, and a bus end terminal. With the K-bus extension, up to 255 Bus Terminals can be connected.

The Bus Terminal Controller is programmed using the TwinCAT programming system according to IEC 61131-3. The configuration/programming interface of the BC9050 is used for loading the PLC program. If the software PLC TwinCAT is in use, the PLC program can also be loaded via Ethernet.

In the default setting the inputs and outputs of the connected Bus Terminals are assigned to the controller. Each Bus Terminal can be configured in such a way that it exchanges data directly through the fieldbus with the higher-level automation device.

Controller for distributed signal processing

The BC9000 and BC9050 Bus Terminal Controllers support the operation of all Bus Terminal types. As far as the user is concerned, the inputs and outputs are not handled any differently from the way they are by other coupler series. The information is made available for use as a byte array in the process image of the automation device.

The analog and multi-functional Bus Terminals can be adapted to each specific application using the KS2000 configuration set. Depending on the type, the analog Bus Terminals' registers contain temperature ranges, gain values and linearisation characteristics. With the KS2000, the required parameters can be set on a PC. The Bus Terminals store settings permanently and in a fail-safe manner.

Having the controller (PLC, IPC) carry out the configuration of the Bus Terminals is a further option. The PLC or IPC uses function blocks (FB) to take care of the configuration of all the peripherals during the start-up phase. The controller can, if required, upload the non-centrally generated configuration data in order to manage and store them centrally. This means that it is not necessary to carry out the setting procedure again if a Bus Terminal is exchanged. The controller carries out the desired setting automatically after switching on.

PLC data	BC9050
Programming	via TwinCAT and programming interface or Ethernet
Program memory	48 kbytes
Data memory	32 kbytes
Remanent data	2 kbytes
Runtime system	1 PLC task
PLC cycle time	approx. 1.5 ms for 1,000 instructions (without I/O cycle, K-bus)
Programming languages	IEC 61131-3 (IL, LD, FBD, SFC, ST)
Online change	yes

Technical data	BC9050
Number of Bus Terminals	64 (255 with K-bus extension)
Max. number of bytes fieldbus	512 byte input and 512 byte output
Max. number of bytes process image	2048 byte input and 2048 byte output
Digital peripheral signals	2,040 inputs/outputs
Analog peripheral signals	512 inputs/outputs
Protocol	TwinCAT ADS, Modbus TCP
Configuration possibility	via KS2000 or Ethernet
Data transfer rates	10/100 Mbaud, automatic recognition of the transmission rate
Bus interface	1 x RJ45
Power supply	24 V DC (-15 %/+20 %)
Input current	65 mA + (total K-bus current)/4
Starting current	approx. 2.5 x continuous current
Recommended fuse	≤ 10 A
Current supply K-bus	1750 mA
Power contacts	max. 24 V DC/max. 10 A
Electrical isolation	500 V (power contact/supply voltage/fieldbus)
Weight	approx. 100 g
Operating/storage temperature	0...+55 °C/-25...+85 °C
Protect. class/installation pos.	IP 20/variable
Approvals	CE, UL, Ex

Accessories	
KS2000	configuration software for extended parameterisation
TwinCAT PLC	programming system conforms to IEC 61131-3
Cordsets	cordsets and connectors
FC9001-0010 FC9011	Ethernet PCI fieldbus cards

Related products	
BC9000	Ethernet Bus Terminal Controller for up to 64 Bus Terminals
BC9020	Ethernet TCP/IP "Economy plus" Bus Terminal Controller for up to 64 Bus Terminals (255 with K-bus extension)
BC9100	Ethernet TCP/IP Bus Terminal Controller for up to 64 Bus Terminals (with integrated 2-channel switch)
BC9120	Ethernet TCP/IP "Economy plus" Bus Terminal Controller for up to 64 Bus Terminals (255 with K-bus extension, with integrated 2-channel switch)
BX9000	Ethernet Bus Terminal Controller for up to 64 Bus Terminals (255 with K-bus extension)
BK9000	Ethernet TCP/IP Bus Coupler for up to 64 Bus Terminals
BK9050	Ethernet TCP/IP "Compact" Bus Coupler for up to 64 Bus Terminals (255 with K-bus extension)
CX8090	Ethernet Embedded PC

System	
Ethernet TCP/IP	For further Ethernet TCP/IP products please see the system overview