



EL3151 | 1-channel analog input terminal 4...20 mA, single-ended, 16 bit

The job of the EL3151 analog input terminal is to supply power to measuring transducers located in the field and to transmit analog measurement signals with electrical isolation to the automation device. The voltage for the sensors is supplied to the terminals via the power contacts. The power contacts can optionally be supplied with operating voltage in the standard way or via a supply terminal (EL9xxx) with electrical isolation. The input electronics are independent of the supply voltage of the power contacts. The reference potential for the inputs is the 0 V power contact. The EtherCAT Terminal indicates its signal state by means of light emitting diodes. The error LEDs indicate an overload condition and a broken wire.

Technical data	EL3151 ES3151
Number of inputs	1 (single-ended)
Power supply	via the E-bus
Technology	single-ended
Signal current	4...20 mA
Distributed clocks	yes
Internal resistance	85 Ω typ. + diode voltage
Input filter limit frequency	5 kHz
Dielectric strength	max. 30 V
Conversion time	~ 40 μ s
Resolution	16 bit (incl. sign)
Measuring error	< ± 0.3 % (relative to full scale value)
Electrical isolation	500 V (E-bus/signal voltage)
Current consumption power contacts	–
Current consumption E-bus	typ. 130 mA
Bit width in the process image	inputs: 4 byte
Special features	standard and compact process image, activatable FIR/IIR filters, limit value monitoring
Weight	approx. 60 g
Operating/storage temperature	-25...+60 °C/-40...+85 °C
Relative humidity	95 %, no condensation
Vibration/shock resistance	conforms to EN 60068-2-6/EN 60068-2-27
EMC immunity/emission	conforms to EN 61000-6-2/EN 61000-6-4
Protect. class/installation pos.	IP 20/variable
Pluggable wiring	for all ESxxxx terminals

Special terminals	
EL3152-1002	enhanced sensor supply