



ER2008-000x | 8-channel digital output 24 V DC, I_{MAX} = 0.5 A

The ER2008 EtherCAT Box with digital outputs connects binary control signals from the controller on to the actuators at the process level. The eight outputs handle load currents of up to 0.5 A and indicate their status through light emitting diodes. The signals are optionally connected via M8 (ER2008-0001) or M12 (ER2008-0002) screw type connectors. The outputs are short-circuit-proof and protected against inverse connection.

The EtherCAT Box modules with zinc die-cast housing are ready for use in harsh industrial and process environments. With the fully sealed design and metal surfaces the ER series is ideal for applications requiring enhanced load capacity and protection against weld spatter, for example.

Technical data	ER2008-0001	ER2008-0002
Number of outputs	8	
Output connections	M8, screw type	M12, screw type
Protocol	EtherCAT	
Bus interface	2 x M8 socket, shielded, screw type	
Load type	ohmic, inductive, lamp load	
Nominal output voltage	24 V DC (-15 %/+20 %)	
Max. output current	0.5 A (short-circuit-proof) per channel	
Short circuit current	typ. 1.5 A	
Distributed clocks	–	
Auxiliary power current	typ. 20 mA + load	
Current consumption from Us (without sensor current)	120 mA	
Power supply connection	feed: 1 x M8 male socket, 4-pin; downstream connection: 1 x M8 female socket, 4-pin	
Bit width in the process image	8 outputs	
Electrical isolation	500 V	
Operating/storage temperature	-25...+60 °C/-40...+85 °C	
Vibration/shock resistance	conforms to EN 60068-2-6/EN 60068-2-27	
EMC immunity/emission	conforms to EN 61000-6-2/EN 61000-6-4	
Protect. class/installation pos.	IP 65/66/67 (conforms to EN 60529)/variable	
Approvals	CE, UL in preparation	

Related products	
EP2008	EtherCAT Box (industrial housing), 8-channel digital output 24 V DC, I _{MAX} = 0.5 A