

Power contactor, AC-3 110 A, 55 kW / 400 V 2 NO + 2 NC, 230 V AC, 50 Hz 3-pole, 3 NO, Size S3 screw terminal



| | |
|---|-----------------|
| Product brand name | SIRIUS |
| Product designation | Power contactor |
| Product type designation | 3RT2 |
| General technical data | |
| Size of contactor | S3 |
| Product extension | |
| • function module for communication | No |
| • Auxiliary switch | Yes |
| Power loss [W] for rated value of the current | |
| • at AC in hot operating state | 23.7 W |
| • at AC in hot operating state per pole | 7.9 W |
| Power loss [W] for rated value of the current without load current share typical | 19 W |
| Surge voltage resistance | |
| • of main circuit rated value | 8 kV |
| • of auxiliary circuit rated value | 6 kV |
| maximum permissible voltage for safe isolation | |
| • between coil and main contacts acc. to EN 60947-1 | 690 V |

| | |
|---|------------------------------|
| Protection class IP | |
| • on the front | IP20 |
| • of the terminal | IP00 |
| Shock resistance at rectangular impulse | |
| • at AC | 6.7 g / 5 ms, 4.0 g / 10 ms |
| Shock resistance with sine pulse | |
| • at AC | 10.6 g / 5 ms, 6.3 g / 10 ms |
| Mechanical service life (switching cycles) | |
| • of contactor typical | 10 000 000 |
| • of the contactor with added electronics-compatible auxiliary switch block typical | 5 000 000 |
| • of the contactor with added auxiliary switch block typical | 10 000 000 |
| Reference code acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750 | K |
| Reference code acc. to DIN EN 81346-2 | Q |

Ambient conditions

| | |
|--|----------------|
| Installation altitude at height above sea level | |
| • maximum | 2 000 m |
| Ambient temperature | |
| • during operation | -25 ... +60 °C |
| • during storage | -55 ... +80 °C |

Main circuit

| | |
|---|---------|
| Number of poles for main current circuit | 3 |
| Number of NO contacts for main contacts | 3 |
| Operating voltage | |
| • at AC-3 rated value maximum | 1 000 V |
| Operating current | |
| • at AC-1 at 400 V | |
| — at ambient temperature 40 °C rated value | 130 A |
| • at AC-1 | |
| — up to 690 V at ambient temperature 40 °C rated value | 130 A |
| — up to 690 V at ambient temperature 60 °C rated value | 110 A |
| — up to 1000 V at ambient temperature 40 °C rated value | 70 A |
| — up to 1000 V at ambient temperature 60 °C rated value | 60 A |
| • at AC-2 at 400 V rated value | 110 A |
| • at AC-3 | |
| — at 400 V rated value | 110 A |

| | |
|--|--------------------|
| — at 500 V rated value | 110 A |
| — at 690 V rated value | 98 A |
| • at AC-4 at 400 V rated value | 97 A |
| • at AC-5a up to 690 V rated value | 120 A |
| • at AC-5b up to 400 V rated value | 110 A |
| • at AC-6a | |
| — up to 230 V for current peak value n=20 rated value | 98 A |
| — up to 400 V for current peak value n=20 rated value | 98 A |
| — up to 500 V for current peak value n=20 rated value | 98 A |
| — up to 690 V for current peak value n=20 rated value | 98 A |
| • at AC-6a | |
| — up to 230 V for current peak value n=30 rated value | 65.3 A |
| — up to 400 V for current peak value n=30 rated value | 65.3 A |
| — up to 500 V for current peak value n=30 rated value | 65.3 A |
| — up to 690 V for current peak value n=30 rated value | 65.3 A |
| Minimum cross-section in main circuit | |
| • at maximum AC-1 rated value | 50 mm ² |
| Operating current for approx. 200000 operating cycles at AC-4 | |
| • at 400 V rated value | 46 A |
| • at 690 V rated value | 36 A |
| Operating current | |
| • at 1 current path at DC-1 | |
| — at 24 V rated value | 100 A |
| — at 110 V rated value | 9 A |
| — at 220 V rated value | 2 A |
| — at 440 V rated value | 0.6 A |
| — at 600 V rated value | 0.4 A |
| • with 2 current paths in series at DC-1 | |
| — at 24 V rated value | 100 A |
| — at 110 V rated value | 100 A |
| — at 220 V rated value | 10 A |
| — at 440 V rated value | 1.8 A |
| — at 600 V rated value | 1 A |
| • with 3 current paths in series at DC-1 | |

| | |
|--|---------|
| — at 24 V rated value | 100 A |
| — at 110 V rated value | 100 A |
| — at 220 V rated value | 80 A |
| — at 440 V rated value | 4.5 A |
| — at 600 V rated value | 2.6 A |
| Operating current | |
| • at 1 current path at DC-3 at DC-5 | |
| — at 24 V rated value | 40 A |
| — at 110 V rated value | 2.5 A |
| — at 220 V rated value | 1 A |
| — at 440 V rated value | 0.15 A |
| — at 600 V rated value | 0.06 A |
| • with 2 current paths in series at DC-3 at DC-5 | |
| — at 24 V rated value | 100 A |
| — at 110 V rated value | 100 A |
| — at 220 V rated value | 7 A |
| — at 440 V rated value | 0.42 A |
| — at 600 V rated value | 0.16 A |
| • with 3 current paths in series at DC-3 at DC-5 | |
| — at 24 V rated value | 100 A |
| — at 110 V rated value | 100 A |
| — at 220 V rated value | 35 A |
| — at 440 V rated value | 0.8 A |
| — at 600 V rated value | 0.35 A |
| Operating power | |
| • at AC-1 | |
| — at 230 V rated value | 49 kW |
| — at 230 V at 60 °C rated value | 42 kW |
| — at 400 V rated value | 86 kW |
| — at 400 V at 60 °C rated value | 72 kW |
| — at 690 V rated value | 148 kW |
| — at 690 V at 60 °C rated value | 125 kW |
| • at AC-2 at 400 V rated value | 55 kW |
| • at AC-3 | |
| — at 230 V rated value | 30 kW |
| — at 400 V rated value | 55 kW |
| — at 500 V rated value | 75 kW |
| — at 690 V rated value | 90 kW |
| Operating power for approx. 200000 operating cycles at AC-4 | |
| • at 400 V rated value | 24.3 kW |

| | |
|--|-----------|
| <ul style="list-style-type: none"> • at 690 V rated value | 32.9 kW |
| Thermal short-time current limited to 10 s | 880 A |
| No-load switching frequency | |
| <ul style="list-style-type: none"> • at AC | 5 000 1/h |
| Operating frequency | |
| <ul style="list-style-type: none"> • at AC-1 maximum | 900 1/h |
| <ul style="list-style-type: none"> • at AC-2 maximum | 350 1/h |
| <ul style="list-style-type: none"> • at AC-3 maximum | 850 1/h |
| <ul style="list-style-type: none"> • at AC-4 maximum | 200 1/h |

Control circuit/ Control

| | |
|---|------------------|
| Type of voltage of the control supply voltage | AC |
| Control supply voltage at AC | |
| <ul style="list-style-type: none"> • at 50 Hz rated value | 230 V |
| Operating range factor control supply voltage rated value of magnet coil at AC | |
| <ul style="list-style-type: none"> • at 50 Hz | 0.8 ... 1.1 |
| Apparent pick-up power of magnet coil at AC | |
| <ul style="list-style-type: none"> • at 50 Hz | 296 V·A |
| Inductive power factor with closing power of the coil | |
| <ul style="list-style-type: none"> • at 50 Hz | 0.61 |
| Apparent holding power of magnet coil at AC | |
| <ul style="list-style-type: none"> • at 50 Hz | 19 V·A |
| Inductive power factor with the holding power of the coil | |
| <ul style="list-style-type: none"> • at 50 Hz | 0.38 |
| Closing delay | |
| <ul style="list-style-type: none"> • at AC | 13 ... 50 ms |
| Opening delay | |
| <ul style="list-style-type: none"> • at AC | 10 ... 21 ms |
| Arcing time | 10 ... 20 ms |
| Control version of the switch operating mechanism | Standard A1 - A2 |

Auxiliary circuit

| | |
|---|------|
| Number of NC contacts for auxiliary contacts | |
| <ul style="list-style-type: none"> • instantaneous contact | 2 |
| Number of NO contacts for auxiliary contacts | |
| <ul style="list-style-type: none"> • instantaneous contact | 2 |
| Operating current at AC-12 maximum | 10 A |
| Operating current at AC-15 | |
| <ul style="list-style-type: none"> • at 500 V rated value | 2 A |
| <ul style="list-style-type: none"> • at 690 V rated value | 1 A |
| Operating current at DC-12 | |
| <ul style="list-style-type: none"> • at 48 V rated value | 6 A |

| | |
|--|---|
| <ul style="list-style-type: none"> • at 60 V rated value • at 110 V rated value • at 125 V rated value • at 220 V rated value • at 600 V rated value | 6 A 3 A 2 A 1 A 0.15 A |
| Operating current at DC-13 | |
| <ul style="list-style-type: none"> • at 48 V rated value • at 60 V rated value • at 110 V rated value • at 125 V rated value • at 220 V rated value • at 600 V rated value | 2 A 2 A 1 A 0.9 A 0.3 A 0.1 A |
| Contact reliability of auxiliary contacts | 1 faulty switching per 100 million (17 V, 1 mA) |

UL/CSA ratings

| | |
|---|---|
| Full-load current (FLA) for three-phase AC motor | |
| <ul style="list-style-type: none"> • at 480 V rated value • at 600 V rated value | 96 A 99 A |
| Yielded mechanical performance [hp] | |
| <ul style="list-style-type: none"> • for single-phase AC motor <ul style="list-style-type: none"> — at 110/120 V rated value — at 230 V rated value • for three-phase AC motor <ul style="list-style-type: none"> — at 200/208 V rated value — at 220/230 V rated value — at 460/480 V rated value — at 575/600 V rated value | 10 hp 20 hp 30 hp 40 hp 75 hp 100 hp |
| Contact rating of auxiliary contacts according to UL | A600 / P600 |

Short-circuit protection

| | |
|---|--|
| Design of the fuse link | |
| <ul style="list-style-type: none"> • for short-circuit protection of the main circuit <ul style="list-style-type: none"> — with type of coordination 1 required — with type of assignment 2 required • for short-circuit protection of the auxiliary switch required | gG: 250 A (690 V, 100 kA), aM: 160 A (690 V, 100 kA), BS88: 200 A (415 V, 80 kA) gG: 200A (690V,100kA), aM: 100A (690V,100kA), BS88: 160A (415V,80kA) gG: 10 A (500 V, 1 kA) |

Installation/ mounting/ dimensions

| | |
|--------------------------|--|
| Mounting position | +/-180° rotation possible on vertical mounting surface; can be tilted forward and backward by +/- 22.5° on vertical mounting surface |
| Mounting type | screw and snap-on mounting onto 35 mm standard mounting rail according to DIN EN 60715 |

| | |
|------------------------------|--------|
| • Side-by-side mounting | Yes |
| Height | 140 mm |
| Width | 70 mm |
| Depth | 195 mm |
| Required spacing | |
| • with side-by-side mounting | |
| — forwards | 20 mm |
| — upwards | 10 mm |
| — downwards | 10 mm |
| — at the side | 0 mm |
| • for grounded parts | |
| — forwards | 20 mm |
| — upwards | 10 mm |
| — at the side | 10 mm |
| — downwards | 10 mm |
| • for live parts | |
| — forwards | 20 mm |
| — upwards | 10 mm |
| — downwards | 10 mm |
| — at the side | 10 mm |

| Connections/ Terminals | |
|---|---|
| Type of electrical connection | |
| • for main current circuit | screw-type terminals |
| • for auxiliary and control current circuit | screw-type terminals |
| • at contactor for auxiliary contacts | Screw-type terminals |
| • of magnet coil | Screw-type terminals |
| Type of connectable conductor cross-sections | |
| • for main contacts | |
| — finely stranded with core end processing | 2x (2.5 ... 35 mm ²), 1x (2.5 ... 50 mm ²) |
| • at AWG conductors for main contacts | 2x (10 ... 1/0), 1x (10 ... 2) |
| Connectable conductor cross-section for main contacts | |
| • solid | 2.5 ... 16 mm ² |
| • stranded | 6 ... 70 mm ² |
| • finely stranded with core end processing | 2.5 ... 50 mm ² |
| Connectable conductor cross-section for auxiliary contacts | |
| • single or multi-stranded | 0.5 ... 2.5 mm ² |
| • finely stranded with core end processing | 0.5 ... 2.5 mm ² |
| Type of connectable conductor cross-sections | |
| • for auxiliary contacts | |
| — single or multi-stranded | 2x (0,5 ... 1,5 mm ²), 2x (0,75 ... 2,5 mm ²) |

| | |
|--|---|
| — finely stranded with core end processing | 2x (0.5 ... 1.5 mm ²), 2x (0.75 ... 2.5 mm ²) |
| • at AWG conductors for auxiliary contacts | 2x (20 ... 16), 2x (18 ... 14) |
| AWG number as coded connectable conductor cross section | |
| • for main contacts | 10 ... 2 |
| • for auxiliary contacts | 20 ... 14 |

| Safety related data | |
|---|--|
| B10 value | |
| • with high demand rate acc. to SN 31920 | 1 000 000 |
| Proportion of dangerous failures | |
| • with low demand rate acc. to SN 31920 | 40 % |
| • with high demand rate acc. to SN 31920 | 73 % |
| Failure rate [FIT] | |
| • with low demand rate acc. to SN 31920 | 100 FIT |
| Product function | |
| • Mirror contact acc. to IEC 60947-4-1 | Yes |
| • positively driven operation acc. to IEC 60947-5-1 | No |
| T1 value for proof test interval or service life acc. to IEC 61508 | 20 y |
| Protection against electrical shock | finger-safe when touched vertically from front acc. to IEC 60529 |

Certificates/ approvals

| | | |
|--------------------------|-----|---------------------------|
| General Product Approval | EMC | Declaration of Conformity |
|--------------------------|-----|---------------------------|



CCC



CSA



UL



RCM



EG-Konf.

| | | |
|---------------------------|-------------------|-------------------|
| Declaration of Conformity | Test Certificates | Marine / Shipping |
|---------------------------|-------------------|-------------------|

[Miscellaneous](#)

[Special Test Certificate](#)



ABS



LRS



PRS



RINA

| | |
|-------------------|-------|
| Marine / Shipping | other |
|-------------------|-------|



DNVGL.COM/AF

[Confirmation](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

www.siemens.com/sirius/catalogs

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RT2047-1AP04>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RT2047-1AP04>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RT2047-1AP04>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)




http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT2047-1AP04&lang=en


Characteristic: Tripping characteristics, I^t, Let-through current

<https://support.industry.siemens.com/cs/ww/en/ps/3RT2047-1AP04/char>

Further characteristics (e.g. electrical endurance, switching frequency)

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RT2047-1AP04&objecttype=14&gridview=view1>





last modified:

11/16/2019