

SIMATIC Field PG M6 Advanced; i7-8850H (2.6 up to 4.3 GHz; 6 Cores+ Hyper-Threading; 9 MB Smart Cache); 15.6" Display; Full HD (1920x 1080); WLAN 802.11ac & Bluetooth V5.0; DVD +/-RW; UHD Graphics 630; 1x 16 GB DDR4 SD-RAM SO-DIMM; 512 GB SSD SATA (2.5"); without S5 interface, without S5-EPROMMER Without line cable; Keyboard: QWERTZ/QWERTY; Windows 10 Enterprise (Version 1803), 64 bit; License for STEP 7 Professional Combo (V15.1 & 2017 SR1); WinCC Advanced combo (V15.1 & WinCC flex. 2008 SP8); Safety Advanced Combo (V15.1 & Distr. Safety 5.4 SP5) Version of the software V15.1.0.0

General information	
Design of the programming device	Notebook
Display	
Design of display	15.6" full HD display in 16:9 format
Resolution (pixels)	
• Horizontal image resolution	1 920 Pixel
• Vertical image resolution	1 080 Pixel
General features	
• Non-reflecting	Yes
• Luminance	300 cd/m <sup>2</sup>
Backlighting	
• Type of backlighting	LED
Control elements	
Keyboard fonts	
• Design	QWERTZ/QWERTY or AZERTY (French); 87 keys
Touch operation	
• Integrated touch pad	Yes; Clickpad
Supply voltage	
Design of the power supply	External wide-range power supply; 3-pole
permissible range, lower limit (AC)	100 V; ±10 %, sinusoidal
permissible range, upper limit (AC)	240 V; ±10 %, sinusoidal
Line frequency	
• permissible range, lower limit	47 Hz
• permissible range, upper limit	63 Hz
Processor	
Processor type	Intel Core i5-8400H (2.5 to 4.2 GHz, 4 cores and hyper-threading, 8 MB Smart Cache) or i7-8850H (2.6 to 4.3 GHz 6 cores and hyper-threading, 9 MB Smart Cache)

Chipset	Intel CM246
Hyper-threading	Yes
Turbo Boost Technology 2.0	Yes

### Graphic

Graphics controller	Intel® UHD Graphics 630
---------------------	-------------------------

### Drives

SSD	Yes; Easy to replace
<ul style="list-style-type: none"> <li>• Memory capacity</li> </ul>	256 Gbyte; Up to 2 TB SSD
TPM Security Chip	Yes; 2.0 (version for China without TPM)

### Memory

Type of memory	DDR4-SDRAM SO-DIMM
Work memory	
<ul style="list-style-type: none"> <li>• Number of slots</li> </ul>	2; Can be equipped with 1x 8 GB, 1x 16 GB or 2x 16 GB

### Accumulator

Replaceable	Yes; Lithium-ion battery
Capacity	8.25 A·h

### Interfaces

PROFIBUS/MPI	1x PROFIBUS DP / MPI; 9-pin Sub-D socket; 9.6 kBaud to 12 MBaud
Number of RS 232 interfaces	1; 25-pin socket
Number of USB interfaces	4
<ul style="list-style-type: none"> <li>• Type A</li> </ul>	3; 1x USB port incl. integrated charging function for USB devices (e.g. smartphone) - also with device switched off
<ul style="list-style-type: none"> <li>• Type C</li> </ul>	1; USB 3.1 Gen. 2
Number of chip-card readers	1; Smart Card Reader (ISO/IEC 7816)
Bluetooth radio standard	Yes; V5.0
Multimedia card/SD card slot	2 in 1 (SDHC UHS-II, MMC)
Card reader for SIMATIC memory cards	SIMATIC memory cards (for S7-300/400), SMC (for S7-1x00), SIMATIC micro memory card (for S7-300/C7/ET 200) - including programming interfaces
Universal Audio Jack	Yes; Audio socket for 3.5 mm jack

### Video interfaces

<ul style="list-style-type: none"> <li>• analog video signal (VGA)</li> </ul>	Yes; via adapter from DVI to VGA
<ul style="list-style-type: none"> <li>• DVI-I</li> </ul>	Yes; 1x
<ul style="list-style-type: none"> <li>• DisplayPort</li> </ul>	Yes; 1x

### Industrial Ethernet

<ul style="list-style-type: none"> <li>• Industrial Ethernet interface</li> </ul>	2x Ethernet (RJ45)
<ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>— 100 Mbps</li> </ul> </li> </ul>	Yes
<ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>— 1000 Mbps</li> </ul> </li> </ul>	Yes
<ul style="list-style-type: none"> <li>• Wake on LAN</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• IAMT (Intel Active Management Technology)</li> </ul>	Yes

<b>WLAN</b>	
• Type	802.11ac
<b>Integrated Functions</b>	
<b>Monitoring functions</b>	
• Status LEDs	Battery status, device status, access to HDD/DVD, access to SD/MMC, MPI/DP, S5 and S7 modules / Card Reader (except Smart Card Reader), Num Lock, Caps Lock, WLAN active
<b>EMC</b>	
<b>Interference immunity against discharge of static electricity</b>	
• Interference immunity against discharge of static electricity acc. to IEC 61000-4-2	Yes
<b>Interference immunity to cable-borne interference</b>	
• Interference immunity on supply cables	±2 kV (according to IEC 61000-4-4, burst); ±1 kV (according to IEC 61000-4-5, surge pulse/line to line); ±2 kV (according to IEC 61000-4-5, surge pulse/line to ground)
• Interference immunity on signal cables	±1 kV (according to IEC 61000-4-4, burst, length < 30 m); ±2 kV (according to IEC 61000-4-4, burst, length > 30 m); ±2 kV (according to IEC 61000-4-5, surge sym./line to ground, length > 30 m)
<b>Standards, approvals, certificates</b>	
CE mark	Yes
CSA approval	Yes
UL approval	Yes
DIN/ISO 9001	Yes
<b>Ambient conditions</b>	
<b>Ambient temperature during operation</b>	
• min.	5 °C; Max. 10 °C/h (no condensation)
• max.	40 °C; Max. 10 °C/h (no condensation)
<b>Ambient temperature during storage/transportation</b>	
• min.	-20 °C; Max. 20 °C/h (no condensation)
• max.	60 °C; Max. 20 °C/h (no condensation)
<b>Relative humidity</b>	
• Operation, min.	5 %; At 30 °C/h (no condensation); Tested according to IEC 60068-2-78, IEC 60068-2-30, IEC 60068-2-14
• Operation, max.	85 %; At 30 °C/h (no condensation); Tested according to IEC 60068-2-78, IEC 60068-2-30, IEC 60068-2-14
<b>Vibrations</b>	
• Operation, tested according to IEC 60068-2-6	Yes
<b>Shock testing</b>	
• tested according to IEC 60068-2-27	Yes
<b>Operating systems</b>	

Additional info on operating system	Multi-Language User Interface (MUI): 6 languages (English, German, French, Spanish, Italian, Chinese)
<b>pre-installed operating system</b>	
• Windows 10	Yes; Windows 10 Enterprise 64-bit
<b>Software</b>	
<b>Preinstalled</b>	
• STEP 7 Professional (TIA Portal)	Yes; Software version: V15.1
• STEP 7	Yes; Professional 2017 SR1
• WinCC flexible Advanced 2008	Yes; Software version: SP5
• WinCC Advanced (TIA Portal)	Yes; Software version: V15.1
• STEP 5	Yes; Optional; software version: STEP 5 V7.23 HF2 (incl. GRAPH 5/II V7.15)
<b>Mechanics/material</b>	
Material of housing	metal
Handle	Yes; retractable
Socket for Kensington lock	Yes
rubber corner guards	Yes
<b>Dimensions</b>	
Width	385 mm
Height	53 mm
Depth	275 mm
<b>Weights</b>	
Weight, approx.	3.4 kg; incl. rechargeable battery
<b>Scope of supply</b>	
Accumulator	Yes
Power supply	Yes
Backpack	Yes
SIMATIC Software	Yes
Recovery media	Yes; Restore & Recovery
<b>Other</b>	
free hotline	Yes
Note:	Made in Germany: development and production in Germany
<b>last modified:</b>	11/27/2019