



Price\* : 8.51 GBP



### Main

Range	TeSys
Device short name	VZN
Product or component type	Additional neutral block
Performance level	Standard
Poles description	1N
Contacts type and composition	1 NO
Contact operation	Early make, late break
Product compatibility	VN12 VN20
Network type	AC DC
Network frequency	50/60 Hz
Mounting location	Right

### Complementary

Range compatibility	TeSys VARIO VCFN switch disconnecter
[Ue] rated operational voltage	690 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	6 kV
[Ith] conventional free air thermal current	20 A
[Ithe] conventional enclosed thermal current	16 A
Mechanical durability	50000 cycles
Electrical durability	30000 cycles DC-1...5 50000 cycles AC-21
Connections - terminals	Screw clamp terminals 4 mm <sup>2</sup> - flexible - with cable end Screw clamp terminals 4 mm <sup>2</sup> - solid
Tightening torque	0.7 N.m - on screw clamp terminals

Height	45.5 mm
Width	12 mm
Depth	39 mm
Product weight	0.02 kg

## Environment

Standards	IEC 60947-3
Product certifications	CSA GL UL
Protective treatment	TC
IP degree of protection	IP20 conforming to IEC 60529
Mechanical robustness	Vibrations 10...150 Hz (1 gn) conforming to IEC 60068-2-6 Shocks 11 ms (15 gn) conforming to IEC 60068-2-27
Ambient air temperature for operation	-20...50 °C
Fire resistance	960 °C conforming to IEC 60695-2-1

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

Warranty	18 months
----------	-----------