



Main

| | |
|-----------------------------|--|
| Range of product | Harmony XAP |
| Product or component type | Die-cast empty control station |
| Device short name | XAPG |
| Product destination | For Ø 30 mm control and signalling units |
| Product front plate size | 80 x 220 mm |
| Usable depth | 74.5 mm |
| Number of cut-out | 4 cut-outs |
| Colour of base of enclosure | Grey (RAL 7032) |
| Colour of cover | Grey (RAL 7032) |
| Material | Zinc alloy |
| Cable entry | 1 hole without blanking plug for cable gland, clamping capacity: 18 mm |
| Product mounting | Flush mounting |
| IP degree of protection | IP65 conforming to IEC 60529 IP657 conforming to NF C 20-010 |

Complementary

| | |
|-------------------------|----------|
| Number of vertical rows | 1 |
| Product weight | 1.375 kg |

Environment

| | |
|---------------------------------------|--|
| Protective treatment | TC |
| Ambient air temperature for storage | -40...70 °C |
| Ambient air temperature for operation | -25...70 °C |
| Electrical shock protection class | Class I conforming to IEC 60536 Class I conforming to NF C 20-030 |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End of Life Information |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|