

# BSH1003P31F2A

AC servo motor BSH - 7.8 N.m - 2500 rpm -  
keyed shaft - with brake - IP65



## Main

Product or component type	Servo motor
Device short name	BSH
Maximum mechanical speed	6000 rpm
Continuous stall torque	<p>8 N.m for LXM32.D30N4 at 10 A, 400 V, three phase</p> <p>8 N.m for LXM32.D30N4 at 10 A, 480 V, three phase</p> <p>7.8 N.m for LXM05CD28M2, 200...240 V, single phase</p> <p>7.8 N.m for LXM05AD28M2, 200...240 V, single phase</p> <p>7.8 N.m for LXM05BD28M2, 200...240 V, single phase</p> <p>7.8 N.m for LXM05BD34N4, 380...480 V, three phase</p> <p>7.8 N.m for LXM05BD42M3X, 200...240 V, three phase</p> <p>7.8 N.m for LXM05CD34N4, 380...480 V, three phase</p> <p>7.8 N.m for LXM05CD42M3X, 200...240 V, three phase</p> <p>6.7 N.m for LXM15LD21M3, 230 V, three phase</p> <p>6.7 N.m for LXM15LD17N4, 230 V, three phase</p> <p>6.7 N.m for LXM15LD17N4, 400 V, three phase</p> <p>6.7 N.m for LXM15LD17N4, 480 V, three phase</p> <p>7.8 N.m for LXM15LD28M3, 230 V, three phase</p> <p>7.8 N.m for LXM15MD28N4, 400 V, three phase</p> <p>7.8 N.m for LXM15MD28N4, 480 V, three phase</p> <p>7.8 N.m for LXM15MD40N4, 400 V, three phase</p> <p>7.8 N.m for LXM15MD40N4, 480 V, three phase</p> <p>7.8 N.m for LXM05AD34N4, 380...480 V, three phase</p> <p>7.8 N.m for LXM05AD42M3X, 200...240 V, three phase</p>
Peak stall torque	<p>28.3 N.m for LXM32.D30N4 at 10 A, 400 V, three phase</p> <p>28.3 N.m for LXM32.D30N4 at 10 A, 480 V, three phase</p> <p>19.69 N.m for LXM05AD28M2, 200...240 V, single phase</p> <p>19.69 N.m for LXM05BD28M2, 200...240 V, single phase</p> <p>19.69 N.m for LXM05CD28M2, 200...240 V, single phase</p> <p>15.5 N.m for LXM15LD21M3, 230 V, three phase</p> <p>12.5 N.m for LXM15LD17N4, 230 V, three phase</p> <p>12.5 N.m for LXM15LD17N4, 400 V, three phase</p> <p>12.5 N.m for LXM15LD17N4, 480 V, three phase</p> <p>19.69 N.m for LXM15LD28M3, 230 V, three phase</p> <p>19.69 N.m for LXM15MD28N4, 400 V, three phase</p> <p>19.69 N.m for LXM15MD28N4, 480 V, three phase</p> <p>23.17 N.m for LXM15MD40N4, 400 V, three phase</p> <p>23.17 N.m for LXM15MD40N4, 480 V, three phase</p> <p>23.01 N.m for LXM05AD34N4, 380...480 V, three phase</p>

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

	<p>23.17 N.m for LXM05AD42M3X, 200...240 V, three phase  23.01 N.m for LXM05BD34N4, 380...480 V, three phase  23.17 N.m for LXM05BD42M3X, 200...240 V, three phase  23.01 N.m for LXM05CD34N4, 380...480 V, three phase  23.17 N.m for LXM05CD42M3X, 200...240 V, three phase</p>
Nominal output power	<p>2000 W for LXM32.D30N4 at 10 A, 400 V, three phase  2600 W for LXM32.D30N4 at 10 A, 480 V, three phase  1100 W for LXM05AD28M2, 200...240 V, single phase  1100 W for LXM05BD28M2, 200...240 V, single phase  1100 W for LXM05CD28M2, 200...240 V, single phase  1100 W for LXM05AD42M3X, 200...240 V, three phase  1100 W for LXM05BD42M3X, 200...240 V, three phase  1100 W for LXM05CD42M3X, 200...240 V, three phase  1300 W for LXM15LD28M3, 230 V, three phase  1700 W for LXM15LD17N4, 230 V, three phase  1700 W for LXM15LD21M3, 230 V, three phase  1800 W for LXM05AD34N4, 380...480 V, three phase  1800 W for LXM05BD34N4, 380...480 V, three phase  1800 W for LXM05CD34N4, 380...480 V, three phase  2000 W for LXM15MD28N4, 400 V, three phase  2000 W for LXM15MD40N4, 400 V, three phase  2200 W for LXM15LD17N4, 400 V, three phase  2200 W for LXM15MD28N4, 480 V, three phase  2200 W for LXM15MD40N4, 480 V, three phase  2300 W for LXM15LD17N4, 480 V, three phase</p>
Nominal torque	<p>6.3 N.m for LXM32.D30N4 at 10 A, 400 V, three phase  6.3 N.m for LXM32.D30N4 at 10 A, 480 V, three phase  3.7 N.m for LXM15LD17N4, 480 V, three phase  6.73 N.m for LXM05AD28M2, 200...240 V, single phase  6.73 N.m for LXM05BD28M2, 200...240 V, single phase  6.73 N.m for LXM05CD28M2, 200...240 V, single phase  4.6 N.m for LXM15MD28N4, 480 V, three phase  4.6 N.m for LXM15MD40N4, 480 V, three phase  4.7 N.m for LXM15LD17N4, 400 V, three phase  5 N.m for LXM15MD28N4, 400 V, three phase  5 N.m for LXM15MD40N4, 400 V, three phase  5.7 N.m for LXM05AD34N4, 380...480 V, three phase  5.7 N.m for LXM05BD34N4, 380...480 V, three phase  5.7 N.m for LXM05CD34N4, 380...480 V, three phase  6 N.m for LXM15LD17N4, 230 V, three phase  6 N.m for LXM15LD21M3, 230 V, three phase  6.3 N.m for LXM15LD28M3, 230 V, three phase  6.73 N.m for LXM05AD42M3X, 200...240 V, three phase  6.73 N.m for LXM05BD42M3X, 200...240 V, three phase  6.73 N.m for LXM05CD42M3X, 200...240 V, three phase</p>
Nominal speed	<p>3000 rpm for LXM32.D30N4 at 10 A, 400 V, three phase  4000 rpm for LXM32.D30N4 at 10 A, 480 V, three phase  4500 rpm for LXM15LD17N4, 400 V, three phase  6000 rpm for LXM15LD17N4, 480 V, three phase  1500 rpm for LXM05AD28M2, 200...240 V, single phase  1500 rpm for LXM05BD28M2, 200...240 V, single phase  1500 rpm for LXM05CD28M2, 200...240 V, single phase  1500 rpm for LXM05AD42M3X, 200...240 V, three phase  1500 rpm for LXM05BD42M3X, 200...240 V, three phase  1500 rpm for LXM05CD42M3X, 200...240 V, three phase  2000 rpm for LXM15LD28M3, 230 V, three phase  2500 rpm for LXM15LD17N4, 230 V, three phase  2500 rpm for LXM15LD21M3, 230 V, three phase  3000 rpm for LXM05AD34N4, 380...480 V, three phase  3000 rpm for LXM05BD34N4, 380...480 V, three phase  3000 rpm for LXM05CD34N4, 380...480 V, three phase  4000 rpm for LXM15MD28N4, 400 V, three phase  4000 rpm for LXM15MD40N4, 400 V, three phase  4500 rpm for LXM15MD28N4, 480 V, three phase  4500 rpm for LXM15MD40N4, 480 V, three phase</p>
Product compatibility	<p>LXM05AD28M2 at 200...240 V single phase  LXM05BD28M2 at 200...240 V single phase  LXM05CD28M2 at 200...240 V single phase  LXM15LD21M3 at 230 V three phase  LXM05AD42M3X at 200...240 V three phase  LXM05BD42M3X at 200...240 V three phase  LXM05CD42M3X at 200...240 V three phase  LXM15LD17N4 at 230 V three phase  LXM15LD17N4 at 400 V three phase</p>

LXM15LD17N4 at 480 V three phase  
 LXM15LD28M3 at 230 V three phase  
 LXM05AD34N4 at 380...480 V three phase  
 LXM05BD34N4 at 380...480 V three phase  
 LXM05CD34N4 at 380...480 V three phase  
 LXM15MD28N4 at 400 V three phase  
 LXM15MD28N4 at 480 V three phase  
 LXM15MD40N4 at 400 V three phase  
 LXM15MD40N4 at 480 V three phase  
 LXM32.D30N4 at 400 V three phase  
 LXM32.D30N4 at 480 V three phase

Shaft end	Keyed
IP degree of protection	IP65 standard IP67 with IP67 kit
Speed feedback resolution	131072 points/turn
Holding brake	With
Mounting support	International standard flange
Electrical connection	Rotatable right-angled connectors

## Complementary

Range compatibility	Lexium 32 Lexium 15 Lexium 05
Supply voltage max	480 V
Network number of phases	Three phase
Continuous stall current	6.6 A
Maximum continuous power	3.14 W
Maximum current Irms	28.3 A for LXM15LD21M3 28.3 A for LXM15LD28M3 28.3 A for LXM15LD17N4 28.3 A for LXM15MD28N4 28.3 A for LXM15MD40N4 28.3 A for LXM05AD28M2 28.3 A for LXM05AD42M3X 28.3 A for LXM05AD34N4 28.3 A for LXM05BD28M2 28.3 A for LXM05BD42M3X 28.3 A for LXM05BD34N4 28.3 A for LXM05CD28M2 28.3 A for LXM05CD42M3X 28.3 A for LXM05CD34N4 28.3 A for LXM32.D30N4
Maximum permanent current	28.3 A
Switching frequency	8 kHz
Second shaft	Without second shaft end
Shaft diameter	19 mm
Shaft length	40 mm
Key width	30 mm
Feedback type	Single turn SinCos Hiperface
Holding torque	9 N.m holding brake
Motor flange size	100 mm
Number of motor stacks	3
Torque constant	1.22 N.m/A at 120 °C
Back emf constant	77 V/krpm at 120 °C
Number of motor poles	8
Rotor inertia	3.838 kg.cm <sup>2</sup>
Stator resistance	1.43 Ohm at 20 °C
Stator inductance	8.8 mH at 20 °C
Stator electrical time constant	6.15 ms at 20 °C
Maximum radial force Fr	1050 N at 1000 rpm 660 N at 4000 rpm

	730 N at 3000 rpm 830 N at 2000 rpm
Maximum axial force Fa	0.2 x Fr
Brake pull-in power	18 W
Type of cooling	Natural convection
Length	271.5 mm
Centring collar diameter	95 mm
Centring collar depth	3.5 mm
Number of mounting holes	4
Mounting holes diameter	9 mm
Circle diameter of the mounting holes	115 mm
Product weight	8 kg

### Offer Sustainability


Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

### Contractual warranty

Warranty	18 months
----------	-----------

Servo Motors Dimensions

Example with Straight Connectors



- a: Power supply for servo motor brake
- b: Power supply for servo motor encoder
- (1) M4 screw
- (2) Shaft end, keyed slot (optional)

Dimensions in mm

Straight connectors		Rotatable angled connectors		c (without brake)	c (with brake)	c1	c2	h	h1	Ø	Ø1 for screws
b1	b2	b1	b2								
39.5	25.5	39.5	39.5	241	272	40	30	6 N9	3.5 <sup>+0.1</sup> <sub>0</sub>	19 k6	M6 x 16


Dimensions in in.

Straight connector		Rotatable angled connectors		c (without brake)	c (with brake)	c1	c2	h	h1	Ø	Ø1 for screws
b1	b2	b1	b2								
1.55	1.00	1.55	1.55	9.48	10.70	1.57	1.18	0.24 N9	0.14 <sup>+0.1</sup> <sub>0</sub>	0.75 k6	M6 x 0.63

400 V 3-Phase Supply Voltage

Torque/Speed Curves

Servo motor with LXM32-D30N4 servo drive



- X Speed in rpm
- Y Torque in Nm
- 1 Peak torque
- 2 Continuous torque


---

480 V 3-Phase Supply Voltage

---

Torque/Speed Curves

Servo motor with LXM32•D30N4 servo drive



- X Speed in rpm
- Y Torque in Nm
- 1 Peak torque
- 2 Continuous torque