



Main

Range of product	Harmony K
Product or component type	Cam switch body
Component name	K1
[I _{th}] conventional free air thermal current	12 A
Sub-assembly composition	Contact blocks + fixing plate
Cam switch function	Switch
Mounting location	Front
Fixing mode	Ø 22 mm hole
Bezel material	Plastic

Complementary

[U _i] rated insulation voltage	690 V (pollution degree 3) conforming to IEC 60947-1
[I _{the}] conventional enclosed thermal current	10 A
Rated operational power in W	10500 W AC-21, 500 - 660 V 3 phases conforming to IEC 947-3
[I _e] rated operational current AC	1 A at 500 V AC-15 conforming to IEC 947-5-1
Electrical durability	1000000 cycles AC-15
Maximum operating rate	2.5 cyc/mn AC-21
Short-circuit current	10000 A
Short-circuit protection	20 A cartridge fuse, type gG
[U _{imp}] rated impulse withstand voltage	4 kV in isolating function
Contact operation	Slow-break
Positive opening	With
Electrical connection	Captive screw clamp terminals flexible, clamping capacity: 2 x 1.5 mm ²
Mechanical durability	1000000 cycles

Environment

Standards	CENELEC EN 50013
Product certifications	CSA 240 V 1 hp 1 phase
Protective treatment	TC

Ambient air temperature for operation	-25...55 °C
Ambient air temperature for storage	-40...70 °C
Shock resistance	30 gn conforming to IEC 68-2-27
Vibration resistance	5 gn conforming to IEC 68-2-6 (f = 10...150 Hz)
Overvoltage category	Class II conforming to IEC 536
IP degree of protection	IP40 conforming to IEC 529

Offer Sustainability

REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration

Contractual warranty

Warranty	18 months
----------	-----------