



Main

Range of product	TeSys
Device short name	LC4
Product or component type	DOL starter
Motor power kW	10 kW at 500 V AC 50/60 Hz 4 kW at 220...230 V AC 50/60 Hz 9 kW at 415 V AC 50/60 Hz 9 kW at 440 V AC 50/60 Hz 7.5 kW at 380...400 V AC 50/60 Hz
Utilisation category	AC-3
[Ue] rated operational voltage	230 V AC 50/60 Hz
[Ie] rated operational current	18 A

Complementary

Device composition	Contacteur Fuse disconnecter
Mounting support	Plate
Width	86 mm
Height	173 mm
Depth	98 mm
Product weight	1.15 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes

RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------