

Price* : 17.06 GBP



⚠ Discontinued

Main

Range of product	TeSys
Device short name	GS1AM
Product or component type	Auxiliary contact
Contact application	O and I position signalling
Contacts type and composition	1 C/O
Contact operation	Early-break
[I _{th}] conventional free air thermal current	16 A (at 40 °C)
[I _e] rated operational current	12 A at 24 V DC-13 2 A at 440 V AC-15 2 A at 48 V DC-13 3 A at 400/415 V AC-15 4 A at 230 V AC-15 5 A at 127 V AC-15 0.4 A at 220 V DC-13 0.6 A at 110 V DC-13

Complementary

Mechanical durability	1000000 cycles
Electrical durability	30000 cycles AC-15
Product compatibility	GS
Switch rated current	400 A 50 A 63 A 160 A 100 A 60 A 250 A 315 A 125 A 200 A
Fuse type	NFC DIN BS
Type of operating handle	Direct right side
Product weight	0.023 kg



Offer Sustainability

REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------

GS1AM1 is replaced by the following group of products:

	electrical auxiliaries GS1AM101 TeSys GS - auxiliary early-break contact - 1 N/C - front side - 32 A Qty 1
	electrical auxiliaries GS1AM110 TeSys GS - auxiliary early-break contact - 1 N/O - 32 A Qty 1

Reason for Substitution: End of life | Substitution date: 30 December 2007